ASSEMBLY OCCUPANCIES

OWNER / OCCUPANT INSPECTION INFORMATION



Have a minimum rating of 2A-10BC

Portable heaters: Must be an approved type and kept away from combustibles.

Manitoba Fire Code requires building owners or occupants to comply with the requirements on this checklist.

complete list; there may be additional requirements for

ASSEMBLY USES INCLUDE:

- Places of worship
- Nightclubs/pubs



Winnipeg Fire Department

Fire Prevention Branch 2nd Floor - 185 King St. Winnipeg, MB, R3B 1J1 Call 311

Email

Checklist: Common Fire Safety Requirements

Address: Must be visible from road and lane, free from foliage, trees, etc.

Aisle ways: Must provide a clear access to exits. **Decorations:** Must be non-combustible or treated. **Drapes or fabrics:** Must be treated. **Emergency lighting:** May be provided by battery packs with remote and attached heads, or by emergency generators that will illuminate specified A/C fixtures or remote light heads. Must be operational, no visible damage, with heads aimed in proper direction, and serviced and tagged annually by a certified technician. Exit doors: Must not be locked or blocked from either the inside or outside. Must be unlocked from the inside when the building is occupied. Must have panic hardware that releases when a force of 20 pounds or less is applied. **Extension cords:** Kept to a minimum and not overloaded. **Exit signs:** Must be visible and remain illuminated at all times the building is occupied. Fire alarm systems: Must have a working A/C power-on bulb and be in good working condition with no audible or visual damage. Must have a current service label (within the last 12 months). Fire Doors: Must not be blocked or wedged open, including stairwell doors. Must have closures and no wedges to hold open fire-rated doors. Fire Department Access: Fire lanes are NOT obstructed by vehicles. Exterior fire department connections are readily visible and unobstructed. Fire hydrants: Must be accessible, free of damage and serviced within the specified date. Private hydrants require annual service and label, with records kept on site. Fire Safety Plan: Must be reviewed an updated annually. **Fire Separations:** Must have no holes or openings that compromise their purpose. Garbage disposal: Commercial containers must be located three meters from combustible buildings. If inside, commercial containers should have tight-fitting lids and be in fire-separated rooms. Occupant load: Submit occupant load calculation to Fire Plan Examiner at 31-30 Fort Street for review. **Portable Fire Extinguishers must:** □ Be located adjacent to corridors or aisles that provide access to exits. Be mounted in a visible location, accessible, and serviced and tagged at least once every 12months by a certified technician. Be full and functioning (no damage, corrosion, leaks malfunctioning parts or clogged nozzles).