DAYCARE OCCUPANCIES OWNER / OCCUPANT INSPECTION INFORMATION



The Manitoba Fire **Code requires** building owners or occupants to comply with the requirements on this checklist.

These requirements are in addition to those listed in the Fire Safety & You Brochure.

DAYCARE USES INCLUDE:

- **Preschools**



Winnipeg Fire Department

2nd Floor - 185 King St. Winnipeg, MB, R3B 1J1 **Call 311**

Email

Checklist: Common Fire Safety Requirements

- **Address:** Must be visible from road and lane, free from foliage, trees, etc. **Aisle ways:** Must provide **clear** access to exits.
- Combustible Artwork: Shall not exceed 20% of the wall or ceiling area.
- Drills & Evacuation: Fire evacuation plans and procedures are complete, up-to date and prominently posted in each room of the Child Care Centre. Monthly fire drills conducted and recorded.
- Egress: Corridors, stairs and exits are unobstructed and in good repair. Exit signs and exit lighting are readily visible and illuminated.
- **Electrical:** Electrical appliances bear the label of a testing laboratory (ULC, CSA). Coffee makers, hot plates, toasters, etc. are unplugged when not in use. Outlets are protected with secure covers.
- Emergency Lighting: Tested monthly for functioning, inspected annually and labelled by a certified
- **Extension Cords:** Kept to a minimum and not overloaded.
- Fire Alarm System: Checked daily for indicator lights, tested, inspected and labelled annually by a certified technician.
- Fire Doors: Fire doors or stairway doors are NOT wedged or blocked open and doors close and latch
- Fire Department Access: Fire lanes are NOT obstructed by vehicles. Exterior fire department connections are readily visible and unobstructed.
- Fire Separations: must have no holes or openings that compromise their purpose.
- Furnace Area: Must be separated from the daycare and maintained clear of storage. Fuel-fired heating systems must be inspected and labelled annually by a certified technician.
- Housekeeping: Trash and debris are contained in non-combustible waste receptacles.
- Laundry facilities: Dryer lint trap must be cleaned after every use and dryer vent must be cleaned as required or annually.
- **Locking devices on exit doors:** Shall be readily opened from the inside.
- Portable Fire Extinguishers must:
 - Be located adjacent to corridors or aisles that provide access to exits.
 - Be mounted in a visible location, accessible, and serviced and tagged at least once every 12months by a certified technician.
 - Be full and functioning (no damage, corrosion, leaks malfunctioning parts or clogged nozzles).
 - Have a minimum rating of 2A-10BC
- **Portable Heaters:** Must be an approved type and kept away from combustibles.
- Smoke Alarms: Smoke alarms are installed on each floor area and/or in every room to be used for sleeping purposes. A written record of monthly smoke alarm tests is maintained.