HOSPITAL OCCPANCIES

OWNER / OCCUPANT INSPECTION INFORMATION



Manitoba Fire Code requires building owners or occupants to comply with the requirements on this checklist.

These requirements are not a complete list; there may be additional requirements for your occupancy.

HOSPITAL USES INCLUDE:

- Hospitals
- Personal care homes



Winnipeg Fire Department

Fire Prevention Branch 2nd Floor - 185 King St. Winnipeg, MB, R3B 1J1 Call 311 <u>Email</u>

Checklist: Common Fire Safety Requirements

Address: Must be visible from road and lane, free from foliage, trees, etc.

	Compressed gases: Must be held in a secure storage area (outside).
	Emergency lighting: May be provided by battery packs with remote and attached heads, or by
	emergency generators that will illuminate specified A/C fixtures or remote light heads. Must be
	operational, no visible damage, with heads aimed in proper direction, and serviced and tagged
	annually by a certified technician.
	Exit doors: Must not be locked or blocked from either the inside or outside. Must be unlocked
	from the inside when the building is occupied. Must have panic hardware that releases when a
	force of 20 pounds or less is applied.
	0
	3 · · · · · · · · · · · · · · · · · · ·
	with no audible or visual damage. Must have a current service label (within the last 12 months).
	3 1 , 3
	and no wedges to hold open fire-rated doors.
	,
	connections are readily visible and unobstructed.
	,
	complete with nozzles. Must have required testing label or tags.
	,
	hydrants require annual servicing label with records kept on site.
	· · · · · · · · · · · · · · · · · · ·
	, , , , , , , , , , , , , , , , , , , ,
_	MB Fire Code requirements.
	□ Be located adjacent to corridors or aisles that provide access to exits.
	 □ Be mounted in a visible location, accessible, and serviced and tagged at least once every 12months by a certified technician.
	•
	 □ Be full and functioning (no damage, corrosion, leaks malfunctioning parts or clogged nozzles). □ Have a minimum rating of 2A-10BC
_	monitored electronically. No storage permitted within 18 in. of bottom of sprinkler heads.
	monitored electronically. No storage permitted within 10 in. of bottom of spinister fleads.