



# ADDENDUM NO. 1 BID OPPORTUNITY NO. 290-2004

## CONSTRUCTION OF NEW FOUNDATION & TRAILER RELOCATION

### **URGENT**

**PLEASE FORWARD THIS DOCUMENT TO  
WHOEVER IS IN POSSESSION OF THE BID  
OPPORTUNITY**

ISSUED: July 2, 2004  
BY: Barb D'Avignon  
TELEPHONE NO. (204) 986-3901

**THIS ADDENDUM SHALL BE INCORPORATED  
INTO THE BID OPPORTUNITY AND SHALL  
FORM A PART OF THE CONTRACT  
DOCUMENTS**

Template Version: 20040128

---

**Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid Submission non-responsive.**

---

### **PART E – SPECIFICATIONS**

Revise: E9 to read:

#### **MISCELLANEOUS METAL – RAILING SECTION 05999**

##### **E9.1 GENERAL**

##### **E9.1.1 WORK INCLUDED**

- (a) All material, labour and plant necessary for the supply and installation of aluminum railings as shown on the drawings.
- (b) Submit five (5) sets of shop drawings for Contract Administrator's approval before fabrication. Drawings must clearly show size of members, size of welds, erection details, location of joint and other related information.

##### **E9.2 PRODUCTS**

##### **E9.2.1 MATERIAL**

- (a) All material shall comply with CSA G40, latest edition, sizes as shown on drawing.
- (b) Standard bolts shall comply with ASTM Specification A307.
- (c) Railing color to be Grey to match existing trailer and new deck.

##### **E9.3 EXECUTION**

##### **E9.3.1 FABRICATION/INSTALLATION**

- (a) Field fabrication shall not be permitted unless written permission is received from the Contract Administrator. All fabrication shall be constructed from approved shop drawings.
- (b) Work shall be shape and size, straight to line and true to curve. Exposed welds and exposed metal edges shall be ground smooth.
- (c) Steel surfaces shall be wire brushed, scraped or otherwise prepared to remove all loose mill scale, rust, oil, dirt, etc. before priming. All exposed iron work shall be shop primed and painted with 2 coats rust proof enamel.

(d) Field touch up all paint damage during delivery or erection.

**DRAWINGS**

Replace Drawing No. A2 with A2 R1 – Plan View, Sections & Elevations

Replace Drawing No. S1 with S1 R1 – Existing Foundation, New Foundation & Details