

178-2006 ADDENDUM 2

FRONT ENTRANCE & VESTIBUILE UPGRADES AT PAN AM POOL

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID OPPORTUNITY

ISSUED: May 5, 2006 BY: Coleen Groening TELEPHONE NO. (204) 986-2491

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid non-responsive.

PART B – BIDDING PROCEDURES

Revise: B2.1 to read: The Submission Deadline is 12:00 noon Winnipeg time, May 10, 2006

PART E - SPECIFICATIONS

Revise: E4.1 to read:	d: HW SET:1		Manual Exterior Entry Pair with fixed mullion (Doors No. 1 and 2)				
	2 E/ 2 E/ 2 E/ 2 E/ 2 E/ 2 E/ 2 E/ 2 E/	A A A A A	Continuous Hinge Panic Hardware Offset Door Pull Surface Closer Overhead Stop Door Sweep Threshold Safety Guard	FM-300 35A-EO 8190-2 4021 & 18 100S W-13S CT-10 700	630 626 630 689 630 628 627 Alum.	MAR VON IVE LCN GLY KNC KNC LCN	
	HW SET:2		Manual Exterior Entry Single (Door No. 3)				
	1 E/ 1 E/ 1 E/ 1 E/ 1 E/ 1 E/ 1 E/	A A A A A	Continuous Hinge Panic Hardware Offset Door Pull Surface Closer Overhead Stop Door Sweep Threshold Safety Guard	FM-300 35A-NL-OP 8190-2 4021 & 18 100S W-13S CT-10 700	630 626 630 689 630 628 627 Alum.	MAR VON IVE LCN GLY KNC KNC LCN	
	HW SET:3		Automatic Exterior Entry Single (Door No. 4)				
	1 E/ 1 E/ 1 E/ 1 E/ 1 E/ 1 E/	A A A A	Continuous Hinge Panic Hardware Electric Strike Offset Door Pull Auto Operator Overhead Stop Door Sweep	FM-300 35A-EO 6111 FS 8190-2 MAGIC-FORCI 100S W-13S	630 626 630 630 = 630 628	MAR VON VON IVE STANLEY GLY KNC	

Bid Opportunity No. 178-2006 Addendum 2 Page 2 of 2

1	EA	Threshold	CT-10	627	KNC
2	EA	Wall Plate Switch	7910-956	630	LCN
1	EA	Key Switch	7930-219	630	LCN
1	EA	Guiderail	CE-810-H-PI	P-X-60	Curran
2	EA	Safety Sensors	7920-912		LCN
1	EA	Remote Control	7920-959		LCN
1	EA	Safety Guard	700	Alum.	LCN

When exit device is dogged down and key switch is "ON", pressing outside or inside auto opener actuator will open door. When key switch is "OFF" outside auto opener actuator will not work. When exit device is not dogged, door cannot be opened from outside. Pressing inside auto opener actuator will momentarily release electric strike and open door. Door relocks upon closing. Fire manual egress at all times.

HW S	SET:4	Manual Vestibule Entry	Pair with fixed r	nullion (Doors N	o. 5 and	6)
2	EA	Continuous Hinge	FM-300	630	MAR		
2	EA	Pull/Pushbar	9190-2	630	IVE		
2	EA	Surface Closer	4111 EDA & 18	B ADAP	ΓER	689	LCN
2	EA	Wall Elect Hold Open	SEM 7830-24V	′	689	LCN	
1	EA	Key Switch	653 - 04	630	LOC		
1	EΑ	Power Supply	510 SERIES	GRY	LOC		
2	EA	Safety Guard	700	Alum.	LCN		
HW S	SET:5	Manual Vestibule Entry	Pair with fixed r	nullion (Doors N	o. 7 and	8)
2	Ε.Δ	Continuous Hings	EM 200	620	МАБ		
2	EΑ	Continuous Hinge	FM-300	630	MAR		
2	EA	Pull/Pushbar	9190-2	630	IVE		
2	EΑ	Surface Closer	4111 EDA & 18	B ADAP	ΓER	689	LCN
2	EΑ	Wall Elect Hold Open	SEM 7830 - 24	1V	689	LCN	
2		Safety Guard					

When key switch is "ON" low voltage electric release hold opens will hold doors when doors are opened to 90 degrees. Doors can be closed manually by pulling doors off hold open or by turning key switch "OFF".

For installation of electric release hold open devices at concrete ceiling, custom galvanized steel brackets must be fabricated to suit.

Key Switch to be situated in new 6" HSS column.

HW SET:6		Automatic Vestibule Single (Door No. 9)					
1	EA	Continuous Hinge	FM-300	630	MAR		
1	EA	Pull/Pushbar	9190-2	630	IVE		
1	EA	Auto Operator	MAGIC-FOR	MAGIC-FORCE			
1	EΑ	Overhead Stop	100S	630	GLY		
2	EA	Wall Plate Switch	7910-956	630	LCN		
1	EA	Key Switch	7930-219	630	LCN		
2	EA	Safety Sensors	7920-912		LCN		
1	EA	Remote Control	7920-959		LCN		
1	EA	Safety Guard	700	Alum.	LCN		
1	EA	Guiderail	CE-810-H-PF	P-1-36	Curran		

Key Switch will permit auto opener to be put into Hold Open.

DRAWINGS

Replace: Drawing 178-2006-A2-R1 with Drawing 178-2006-A2-R2