

SUPPLY AND DELIVER FLOOR SWEEPER/SCRUBBER

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE
REQUEST FOR PROPOSAL**

ISSUED: June 13, 2019
BY: David Ranger
TELEPHONE NO. 204 - 986-6141

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE REQUEST FOR PROPOSAL AND
SHALL FORM A PART OF THE CONTRACT
DOCUMENTS**

Template Version: Ar20160708

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Request for Proposal, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Proposal may render your Proposal non-responsive.

PART E – SPECIFICATIONS

Revise:

E2.2 Floor sweeper/scrubber:

- (i) Performance scrubbing speed - 70,400 ft²/hr - 118,600ft²/hr
- (ii) Working main brush width - 40 - 48 inches
- (iii) Waste container capacity - 70 - 198 litres
- (iv) Climbing capacity - 10 - 17 %
- (v) Working speed - 3.5 - 4 mph
- (vi) Filter Canister - 50 ft² - 115 ft²
- (vii) Weight - 4500 - 4800 lbs
- (viii) Solution tank - 75 gal
- (ix) Recovery tank - 75 - 95 gal.
- (x) Cylindrical Scrubbing Brush speed - 500 rpm
- (xi) Scrubbing Brush down pressure - 400 - 550 lbs
- (xii) Motor rating - IP44 - IP55
- (xiii) Sweeping width (dual brushes) - 61 - 67 inches
- (xiv) Minimum aisle turn - 104 - 120 inches
- (xv) Automatic filter shaker
- (xvi) Battery watering system
- (xvii) Heavy duty squeegee guard
- (xviii) Power Battery - 36 volt 750 - 770AH C6
- (xix) 3 PH Charger - 100A 200-240V 50/60Hz
- (xx) Recover Tank Full & Solution Tank Empty Indicator
- (xxi) Non Marking Drive Wheel
- (xxii) Yellow Maintenance Touch Points is an asset
- (xxiii) Recovery Tank Debris Tray
- (xxiv) In-Line Vacuum Fan Filter
- (xxv) Tracking Rear Parabolic Squeegee is an asset

- (xxvi) SmartRelease™ Breakaway Rear Squeegee
- (xxvii) Underwriters Laboratory (UL®) E Certified
- (xxviii) Dual Side Sweeping Brushes
- (xxix) Safety light Package
- (xxx) 60" / 1525 mm Hopper Dump Height
- (xxxi) Onboard Diagnostics
- (xxxii) Steering Wheel or Main Panel Mounted Horn
- (xxxiii) Steering Wheel or Main Panel Mounted Water Shut-Off
- (xxxiv) Maintenance Free Scrub Brush, Propel, & Dust Control Vac Fan Motors
- (xxxv) Duramer™ or Rotomolded Tanks & Shrouds
- (xxxvi) Variable Flow Tank Drains
- (xxxvii) No-Tool Squeegee Change
- (xxxviii) No-Tool Brush Change
- (xxxix) Full Wrap Steel Bumper with Front Cushioned Corner Rollers
 - (xl) 36 Months or 2000 hours warranty on parts
 - (xli) 24 Months warranty on labour
 - (xlii) 6 Months warranty on travel
 - (xlili) Minimum 8 Year Warranty on tanks