

PART E
SPECIFICATIONS

PART E - SPECIFICATIONS

GENERAL

E1. GENERAL

E1.1 These Specifications shall apply to the Work.

E2. GOODS

E2.1 The Contractor shall supply and deliver utility trailers in accordance with the requirements hereinafter specified.

E2.2 The trailer shall comply with all Canadian Motor Vehicle Safety Standards (C.M.V.S.S.) and the Manitoba Highway Traffic Act regulations and requirements.

E2.3 Item No. 1 – 20' trailer shall include the following as a minimum:

- (a) Trailer deck shall not be narrower than 83 inches;
- (b) Beavertail shall be a minimum of two (2) feet in addition to the twenty foot deck;
- (c) Trailer tongue deck extension area shall be a minimum of 18" with 12 " high bumper stop;
- (d) steel mesh vehicle loading ramps;
- (e) 12,000 lb jack;
- (f) Trailer wiring and lighting shall meet all regulations as recommended by Manufacturer. Wiring shall be secured, loomed and protected from wear points;
- (g) Licence plate bracket c/w light
- (h) 2 – 6,000 lb axles;
- (i) electric brakes;
- (j) 4 – 215-85-R16 tires on 16" - 5 bolt wheels;
- (k) 2 5/16 " ball hitch;
- (l) 4 leaf spring suspension;
- (m) galvanized steel construction;
- (n) treated wood floor;
- (o) safety chains and hooks;
- (p) Spare tire mounted on a rim; and
- (q) Heavy duty winch mounted to the trailer, fitted with nylon strap, capable of pulling 2000 lbs up onto the deck.
- (r) Tie-downs on the side of the trailer.

E3. DELIVERY

E3.1 Goods shall be delivered F.O.B. destination; freight prepaid within thirty (30) Business Days of the placing of an order, except where otherwise agreed at the time of ordering.

E3.2 Goods shall be delivered between 8:30 a.m. and 4:30 p.m. on Business Days.