

PART E
SPECIFICATIONS

PART E - SPECIFICATIONS

GENERAL

E1. APPLICABLE SPECIFICATIONS, STANDARD DETAILS AND DRAWINGS

- E1.1 *The City of Winnipeg Standard Construction Specifications* in its entirety, whether or not specifically listed on Form B: Prices, shall apply to the Work.
- E1.1.1 *The City of Winnipeg Standard Construction Specifications* is available in Adobe Acrobat (.pdf) format on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division internet site at <http://www.winnipeg.ca/matmgt>.
- E1.1.2 The version in effect three (3) Business Days before the Submission Deadline shall apply.
- E1.1.3 Further to GC:2.4(d), Specifications included in the Bid Opportunity shall govern over *The City of Winnipeg Standard Construction Specifications*.

E2. WORK

- E2.1 These Specifications shall apply to the Work.
- (a) Supply tiles to cover entire bottom of the lap pool, prepare and install tiles to approx. 3/5th of the floor surface of the pool.
 - (b) Contractor will supply 2"x2" Unglazed (dot mount) Mosaic Porcelain Pool Tile equal to Dal Keystones, White D317 (Colour Group 1) as the field colour and Dal Keystones, Ebony D311 (Colour Group 3) for the Black Lane markings as per existing to cover the floor of the lap pool in it's entirety.
 - (c) Tile must be certified by the manufacturer to be suitable for the use in pools.
 - (d) The Contractor will submit 3 copies of the TTMAC Maintenance Data for the Owner's use.
 - (e) Contractor will remove existing paint and coatings by shot blast (Blastrac) down to sound, clean concrete and apply a skim coat of Thinset Mortar with Polymer Additive equal to Mapei Kerabond White with Keraply Additive to provide a smooth, sound substrate for the tile and Polymer Modified Grout equal to Mapei KER 700 Ultra/Colour (White), only on the proposed 3/5th of the pool length.
 - (f) Installation of 2"x2" tile as per TTMAC Detail 317sp-2000 (without the Waterproof Membrane requirement) to the prepped 3/5th of the pool.
 - (g) Caulk control joints at perimeter and maximum 600 mm o.c. with W.R. Meadows Sealtight Deck-O-Seal sealant suitable for underwater application.
 - (h) Supply 2 additional boxes of Ebony tile and 3 additional boxes of the White tile installed on the project for maintenance use.