

**PART E**  
**SPECIFICATIONS**

## PART E - SPECIFICATIONS

### GENERAL

#### E1. GENERAL

E1.1 These Specifications shall apply to the Work.

#### E2. GOODS

E2.1 The Contractor shall supply and deliver infield mix, for baseball diamonds in accordance with the requirements hereinafter specified.

E2.2 The baseball diamond infield mix shall consist of natural sand and pink-red crushed limestone.

(a) the colour of the material is imperative as much of the material is used to patch existing sites; and

(b) a sample of the required colour is available to all Bidders; please contact the Contract Administrator as shown in Clause D5.1.

E2.3 Graduation requirements:

(a) Find Sand:

(i) Metric Sieve Size	% Passing
5000	100
2,500	90-100
435	70-90
315	60-80
80	0-3

(b) "Pink-Red" Crushed Limestone:

(i) 6 M.M. to dust "pink-red" crushed limestone with a minus 80 M.M.S proportion not exceeding 35%.

E2.4 Mixing Requirements:

(a) a mixture of 60% limestone and 40% sand in accordance to the gradation requirements; and

(b) thoroughly bucket mix the two materials at the stated ratio to create a uniform blend of said products.

E2.5 Final Screening:

(a) after mixing is completed as stated all material must then be final screened through a 1/8" slotted screener; and

(b) final gradation requirements for specified material, 100% passing 1/8" slotted screen.

#### E3. DELIVERY

E3.1 Goods shall be delivered on an "as required" basis during the term of the Contract, f.o.b. destination, freight prepaid, to various locations within the City.

E3.1.1 Goods shall be delivered within two (2) Business Days of the placing of an order, except where otherwise agreed at the time of ordering.

E3.2 Goods shall be delivered between 8:30 a.m. and 4:30 p.m. on Business Days.

E3.3 The Contractor shall off-load goods as directed at the delivery location.