

## ADDENDUM NO. 1 BID OPPORTUNITY NO. 63-2004

## LEASE OF ARTICULATED SIDEWALK TRACTORS

## **URGENT**

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID OPPORTUNITY

ISSUED: May 3, 2004 BY: Barry Tobin /bt TELEPHONE NO. (204) 986-2126

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID OPPORTUNITY AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid Opportunity, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 8 of Form A: Bid may render your Bid Submission non-responsive.

## PART A - BID SUBMISSION

Replace: Form N: Detailed Specification 04 005, page 8 of 18 with the attached revised Form N: Detailed Specification 04 005, page 8 of 18.

|       | which are normal to the City of Winnipeg.   |
|-------|---|
| 6.2   | Shall be capable of consistent top performance for snow blowing, plowing and sanding sidewalks during the winter environment which is normal to the City of Winnipeg. |
| 7.0   | <u>DIMENSIONS &amp; WEIGHTS</u> (Tractor Only)  |
|       | State the following:  |
| 7.1   | Operating weight (SAE) – approx. 5,000 lbs. (2268 kg).  |
| 7.2   | Overall width – approx. 50 in. (1270 mm).   |
| 7.3   | Overall height, to top of cab – approx. 80 in. (2032 mm).   |
| 7.4   | Overall length – approx. 150 in. (3810 mm).   |
| 7.5   | Wheelbase – approx. 75 in. (1905 mm).   |
| 7.6   | Ground clearance – 8 in. (203 mm) minimum.  |
| 8.0   | <u>ENGINE</u>   |
| 8.1   | Type – diesel fuelled, turbocharged, 4-cycle, state make and model being bid  |
| 8.1.1 | Horsepower, SAE gross – 90 hp, (67 kW) minimum.   |
| 8.2   | Cooling system – state type.  |
| 8.2.1 | Coolant – ethylene glycol based, protected to -35°F (-37°C), (water-cooled engines only).   |
| 8.3   | Fuel shut-off – electric solenoid type.   |
| 8.4   | Fuel filter and water separator.  |
| 8.5   | Fuel tank – 48 L capacity minimum, fully fuelled upon delivery.   |
| 8.5.1 | Fuel filler – remote type, accessible with any attachment installed on tractor.   |
| 8.6   | Oil filter – full flow, spin-on type, easily accessible for servicing.  |
| 8.7   | Air cleaner – two stage, dry cartridge type with pre-cleaner, easily accessible for servicing.  |
| 8.7.1 | Air cleaner restriction indicator gauge (audible alarm not acceptable), engine compartment or cab mounted. State location.  |
| 8.8   | Exhaust – mufflered. Vertical discharge exhaust systems shall have a bend and $40^{\circ}$ cut-off.   |
| 8.9   | Cold weather starting kit – required, state type.   |
| 8.9.1 | Block heater – state type and capacity.   |