



AREA	APPROX. sqm	APPROX. ANODES REQ'D
A	1.5	11
B	0.5	4
C	0.5	4
D	8.5	41
E	0.5	0
F	1.0	0
G	2.0	10
H	1.0	6
I	1.0	6
J	3.0	16
K	4.5	25
TOTAL	24	123

**NOTES:**

1. MAXIMUM SPACING FOR ANODES IS 610mm.
2. MINIMUM OF FOUR (4) ANODES PER REPAIR AREA, UNLESS OTHERWISE SPECIFIED BY THE CONTRACT ADMINISTRATOR.
3. ANODES WILL BE SUPPLIED BY THE CITY OF WINNIPEG.

NO.	REVISIONS	DATE	BY

DESIGNED BY	M.R.T.
DRAWN BY	M.R.T.
CHECKED BY	B.A.N.
APPROVED BY	B.A.N.
AUTHORIZED BY	DATE
B. A. NEIRINCK BRIDGE PLANNING & OPERATIONS ENGINEER	

ENGINEER'S SEAL

ENG OPPORTUNITY NO.  
196-2005

**THE CITY OF WINNIPEG**  
PUBLIC WORKS DEPARTMENT  
ENGINEERING DIVISION

ST. JAMES BRIDGE NORTHBOUND  
OVER ASSINIBOINE RIVER  
PIER 17 CONCRETE REPAIRS

REPAIR AREAS

SHEET 2 OF 2

HOR. SCALE: N.T.S.  
VERTICAL: N.T.S.

CITY DRAWING NUMBER  
8102-05-02