

NOTES:

- WIRE AND CONNECT HOOD SUPPRESSION SYSTEM AS SUPPLIED BY MECHANICAL. COORDINATE REQUIREMENTS WITH EQUIPMENT SHOP DRAWINGS.
- 2. INTERCONNECT HOOD SUPPRESSION SYSTEM TO SEPARATE ZONE IN FIRE ALARM SYSTEM. PROVIDE ISOLATION MODULES AS REQUIRED. COORDINATE REQUIREMENTS WITH EQUIPMENT SHOP DRAWINGS.
- 3. PROVIDE RELAY/CONTACTOR CONTROL FOR ELECTRICAL DEVICES LOCATED BELOW AND WITHIN 1500mm OF HOOD SUCH THAT ALL SHUT DOWN UPON INITIATION OF FIRE SUPPRESSION SYSTEM. COORDINATE REQUIREMENTS WITH EQUIPMENT SHOP DRAWINGS.
- 4. WIRE AND CONNECT EXISTING DEEP FRYER AS SUPPLIED BY OWNER C/W 100A FUSIBLE DISCONNECT C/W 100A FUSES. CONFIRM BREAKER AND FUSE SIZES WITH EQUIPMENT NAMEPLATE RATINGS.
- 5. PROVIDE ONE(1) 14-50R RECEPTACLE FOR EXISTING COOKTOP. CONFIRM REQUIREMENTS WITH EQUIPMENT NAMEPLATE RATINGS.
- ITEMS IDENTIFIED IN NOTES 1,2, AND 3SHALL BE INCLUDED IN SEPARATE PRICE #10.

