


SUPPLEMENTARY CONSTRUCTION NOTES

1. LOCATE CATWALK FRAMING TO SUIT EXISTING NATURAL GAS PIPING (INSPECT SITE CONDITIONS)
2. PROVIDE STEEL END CAPS ON ALL OPEN TUBINGS (RAILINGS, FRAMES ETC)
3. CONNECT GRATING PLANKS (AT FLANGES) WITH SELF-TAPPING SCREWS ($\frac{1}{4}$ " ϕ) AT 24" o/c SPACING
4. CONNECT GRATING PLANKS WITH $\frac{1}{4}$ "x2"x6" BANDS & $\frac{1}{2}$ " ϕ THRU BOLTS AT EACH END - TYPICAL ALL ENDS
5. STAGGER GRATING PLANKS ON CONTINUOUS LENGTHS SO THAT GRATINGS JOINTS ARE AT SAME LOCATION
6. PROVIDE CARRIAGE BOLTS FOR CONNECTIONS OF RAILING TO VERTICAL POSTS

SK-15

Typical Details

Roof Equip. Service Platform
Waverley Heights CC
1885 Chancellor Dr. Wpg. MB.



GC ENGINEERING LTD.
675 ELM ST.
WINNIPEG MB R3M 3N8
PH 793-3948 FAX 487-4616
EMAIL CALGRAY@MTS.NET