

PART 1 - GENERAL

1.1 SUBMITTALS

- .1 Shop drawings to show:
 - .1 Operating and maintenance clearances.
- .2 Shop drawings and product data accompanied by:
 - .1 Acoustical sound power data, where applicable.
 - .2 Points of operation on performance curves.
 - .3 Certification of compliance to applicable codes.
- .3 Closeout Submittals:
 - .1 Operation and maintenance manual approved by, and final copies deposited with, Contract Administrator before final inspection.
 - .2 Operation data to include:
 - .1 Control schematics for systems including environmental controls.
 - .2 Description of systems and their controls.
 - .3 Description of operation of systems at various loads together with reset schedules and seasonal variances.
 - .4 Operation instruction for systems and component.
 - .5 Description of actions to be taken in event of equipment failure.
 - .6 Valves schedule and flow diagram.
 - .7 Colour coding chart.
 - .3 Maintenance data to include:
 - .1 Servicing, maintenance, operation and trouble-shooting instructions for each item of equipment.
 - .2 Data to include schedules of tasks, frequency, tools required and task time.
 - .4 Performance data to include:
 - .1 Equipment manufacturer's performance datasheets with point of operation as left after commissioning is complete.
 - .2 Equipment performance verification test results.
 - .3 Special performance data as specified.
 - .4 Testing, adjusting and balancing reports.
 - .5 Approvals:
 - .1 Submit 2 copies of draft Operation and Maintenance Manual to Contract Administrator for approval. Submission of individual data will not be accepted unless directed by Contract Administrator.
 - .2 Make changes as required and re-submit as directed by Contract Administrator.
 - .6 Additional data:
 - .1 Prepare and insert into operation and maintenance manual additional data when need for it becomes apparent during specified demonstrations and instructions.

1.2 DELIVERY, STORAGE, AND HANDLING

- .1 Waste Management and Disposal:
-

PART 3 - EXECUTION

3.1 PAINTING REPAIRS AND RESTORATION

- .1 Prime and touch up marred finished paintwork to match original.
- .2 Restore to new condition, finishes which have been damaged.

3.2 CLEANING

- .1 Clean interior and exterior of all systems including strainers. Vacuum interior of ductwork and air handling units.

3.3 DEMONSTRATION

- .1 Contract Administrator use equipment and systems for test purposes prior to acceptance. Supply labour, material, and instruments required for testing.
- .2 Trial usage to apply to following equipment and systems:
 - .1 Ventilation system.
- .3 Supply tools, equipment and personnel to demonstrate and instruct operating and maintenance personnel in operating, controlling, adjusting, trouble-shooting and servicing of all systems and equipment during regular work hours, prior to acceptance.
- .4 Use operation and maintenance manual, and audio visual aids as part of instruction materials.
- .5 Instruction duration time requirements as specified in appropriate sections.

3.4 PROTECTION

- .1 Protect equipment and systems openings from dirt, dust, and other foreign materials with materials appropriate to system.

PART 1 - GENERAL

1.1 REFERENCES

- .1 American National Standards Institute/National Fire Protection Association (ANSI/NFPA)
 - .1 ANSI/NFPA 13-2002 Select Edition, Standard for the Installation of Sprinkler Systems.
 - .2 ANSI/NFPA 25-2002 Select Edition, Standard for the Inspection, Testing and Maintenance of Water-Based Fire Protection Systems.

1.2 SUBMITTALS

- .1 Shop Drawings:
 - .1 Certificates: submit certificates signed by manufacturer certifying that materials comply with specified performance characteristics and physical properties.
 - .2 Instructions: submit manufacturer's installation instructions.
- .2 Closeout Submittals:
 - .1 Provide detailed hydraulic calculations including: summary sheet, Contractor's Material and Test Certificate for aboveground and underground piping, as well as other deliverables.

1.3 QUALITY ASSURANCE

- .1 Qualifications:
 - .1 Installer: company or person specializing in dry sprinkler systems with documented experience.

1.4 ENGINEERING DESIGN CRITERIA

- .1 Design system in accordance with ANSI/NFPA 13, using following parameters:
 - .1 Hazard:
 - .1 To suit occupancy as indicated.
 - .2 Pipe size and layout:
 - .1 Hydraulic design or pipe schedule sizing design.
 - .2 Sprinkler head layout: to ANSI/NFPA.
 - .3 Water supply:
 - .1 Conduct flow and pressure test of water supply in vicinity of project to obtain criteria for bases of design in accordance with ANSI/NFPA 13.

PART 2 - PRODUCTS

2.1 PIPE, FITTINGS AND VALVES

- .1 Pipe:
 - .1 Ferrous: to ANSI/NFPA 13.
 - .2 Copper tube: to ANSI/NFPA 13.
- .2 Fittings and joints to ANSI/NFPA 13:
 - .1 Ferrous: screwed, welded, flanged or roll grooved.
 - .2 Copper tube: screwed, soldered, brazed.
- .3 Auxiliary valves:
 - .1 ULC listed for fire protection service.
 - .2 Up to NPS 2: bronze, screwed ends, OS & Y gate.
 - .3 NPS 2 1/2 and over: cast iron, flanged or roll grooved ends, indicating butterfly valve.
 - .4 Swing check valves.
 - .5 Ball drip.
 - .6 Tamper devices wired back to fire alarm panel.
- .4 Pipe hangers:
 - .1 ULC listed for fire protection services.

2.2 SPRINKLER HEADS

- .1 General: to ANSI/NFPA 13 and ULC listed for fire services.

2.3 SPRINKLER HEAD TYPE A

- .1 Upright bronze.

2.4 SPRINKLER HEAD TYPE B

- .1 Pendant chrome link and lever type.

2.5 SPRINKLER HEAD TYPE C

- .1 Pendant chrome glass bulb type.

2.6 SPRINKLER HEAD TYPE D

- .1 Recessed polished satin chrome glass bulb fusible link type with ring and cup.

2.7 SPRINKLER HEAD TYPE E

- .1 Flush polished satin chrome link and lever type.

2.8 SPRINKLER HEAD TYPE F

- .1 Side wall polished satin chrome link and lever type.

2.9 AUXILIARY SUPERVISORY SWITCHES

- .1 General: to ANSI/NFPA 13 and ULC listed for fire service.
- .2 Valves:
 - .1 Mechanically attached to valve body, with normally open and normally closed contacts and supervisory capability.
- .3 Flow switch type:
 - .1 With normally open and normally closed contacts and supervisory capability.
- .4 Pressure alarm switch:
 - .1 With normally open and normally closed contacts and supervisory capability.

2.10 FIRE DEPARTMENT CONNECTION

- .1 To ANSI/NFPA 13 and ULC listed, siamese type, location as indicated. Thread specifications to be compatible with local fire department.
- .2 Polished bronze or chrome plated, exposed with identifying sign cast on plate. Threaded metal caps and chains.

2.11 DRY PIPE VALVE

- .1 ULC listed.
- .2 Cast iron, flanged type, sized to suit water main.
- .3 Components:
 - .1 Accelerator.
 - .2 Air maintenance device with low pressure alarm.
 - .3 Alarm pressure switch with supervisory capability.
 - .4 Pressure gauges.
 - .5 Drain valve.
 - .6 Test valve with associated piping.
 - .7 Shut off valve - OS & Y with tamper-proof device wired back to fire alarm panel.

2.12 COMPRESSED AIR SUPPLY

- .1 Automatic Air Compressor.
- .2 ULC listed.
- .3 Capacity:
 - .1 To restore normal air pressure in system within 30 minutes.
 - .2 To provide air pressure in accordance with instruction sheet furnished with dry pipe valve.
- .4 Piping: ferrous, NPS 3/4 screwed joints and fittings, to ANSI/NFPA 13.

2.13 PRESSURE GAUGES

- .1 Maximum limit of not less than twice normal working pressure at point where installed.
-

2.14 RELIEF VALVE

- .1 ULC listed.

PART 3 - EXECUTION

3.1 MANUFACTURER'S INSTRUCTIONS

- .1 Compliance: comply with manufacturer's written recommendations or specifications, including product technical bulletins, handling, storage and installation instructions, and datasheet.

3.2 INSTALLATION

- .1 Install, inspect and test to acceptance in accordance with ANSI/NFPA 13 and NFPA 25.
- .2 Testing to be witnessed by authority having jurisdiction.
- .3 Install fire department connections as indicated.
- .4 Pressure gauges:
 - .1 Location:
 - .1 On water side and air side of dry pipe valve.
 - .2 At air receiver.
 - .3 In each independent pipe from air supply to dry pipe valve.
 - .4 At exhausters and accelerators.
 - .2 Install to permit removal.
 - .3 Locate so as not subjected to freezing.
- .5 Valve identification:
 - .1 Identify drain valve, by-pass valves and main shut-off valve and all auxiliary valves.

3.3 CLEANING

- .1 Upon completion and verification of performance of installation, remove surplus materials, excess materials, rubbish, tools and equipment.