

THE CITY OF WINNIPEG

BID OPPORTUNITY

BID OPPORTUNITY NO. 69-2010

ENDERTON PARK PLAYGROUND REDEVELOPMENT

TABLE OF CONTENTS

PART A	A - BID SUBMISSION	
	m A: Bid m B: Prices	1 3
PART E	3 - BIDDING PROCEDURES	
B2. B3. B4. B5. B6. B7. B8. B10 B11 B12 B13 B14 B15	Contract Title Submission Deadline Site Investigation Enquiries Addenda Substitutes Bid Components Bid Prices Design Drawings Component Description Qualification Copening of Bids and Release of Information Irrevocable Bid Withdrawal of Bids Evaluation of Bids Award of Contract	1 1 1 1 1 2 2 3 4 4 4 4 5 5 6 6 7
PART C	C - GENERAL CONDITIONS	
C0.	General Conditions	1
PART D	O - SUPPLEMENTAL CONDITIONS	
D1. D2. D3. D4. D5.	General Conditions Scope of Work Definitions Contract Administrator Contractor's Supervisor Notices	1 1 1 1 1
D7. D8. D9.	Authority to Carry on Business Safe Work Plan Insurance Subcontractor List	2 2 2 3
D11 D12 D13 D14 D15 D16	nedule of Work I. Commencement 2. Substantial Performance 3. Total Performance 4. Liquidated Damages 5. Existing Services and Utilities 6. Access To Site 7. Damage to Existing Structures, Trees and Property	3 4 4 4 5 5
D18	ntrol of Work 3. Job Meetings 9. Prime Contractor – The Workplace Safety and Health Act (Manitoba)	5 6
	asurement and Payment D. Payment	6

Table of Contents

Template Version: C320090615 - C LR

D21. D22.	ranty . Warranty . Site Restoration n J: Subcontractor List	6 6 7
PART E	- SPECIFICATIONS	
Gene	eral	
E1.	Applicable Specifications and Drawings	1
E2.	General Comments	1
E3.	Playstructures	2
E4.	Independent Components	4
E5.	Swing Standard	4
E6.	Foundations	6
E7.	Maintenance Kits	6
E8.	Excavation and Disposal	7
E9.	Timber Edging	8
E10.	Protective Surfacing	8
E11.	Sodding and Site Restoration	10

PART B - BIDDING PROCEDURES

B1. CONTRACT TITLE

B1.1 ENDERTON PARK PLAYGROUND REDEVELOPMENT

B2. SUBMISSION DEADLINE

- B2.1 The Submission Deadline is 4:00 p.m. Winnipeg time, March 30, 2010.
- B2.2 Bids determined by the Manager of Materials to have been received later than the Submission Deadline will not be accepted and will be returned upon request.
- B2.3 The Contract Administrator or the Manager of Materials may extend the Submission Deadline by issuing an addendum at any time prior to the time and date specified in B2.1.

B3. SITE INVESTIGATION

B3.1 Further to C3.1, the Bidder may view the Site without making an appointment.

B4. ENQUIRIES

- B4.1 All enquiries shall be directed to the Contract Administrator identified in D4.1.
- B4.2 If the Bidder finds errors, discrepancies or omissions in the Bid Opportunity, or is unsure of the meaning or intent of any provision therein, the Bidder shall notify the Contract Administrator of the error, discrepancy or omission, or request a clarification as to the meaning or intent of the provision at least five (5) Business Days prior to the Submission Deadline.
- B4.3 Responses to enquiries which, in the sole judgment of the Contract Administrator, require a correction to or a clarification of the Bid Opportunity will be provided by the Contract Administrator to all Bidders by issuing an addendum.
- B4.4 Responses to enquiries which, in the sole judgment of the Contract Administrator, do not require a correction to or a clarification of the Bid Opportunity will be provided by the Contract Administrator only to the Bidder who made the enquiry.
- B4.5 The Bidder shall not be entitled to rely on any response or interpretation received pursuant to B4 unless that response or interpretation is provided by the Contract Administrator in writing.

B5. ADDENDA

- B5.1 The Contract Administrator may, at any time prior to the Submission Deadline, issue addenda correcting errors, discrepancies or omissions in the Bid Opportunity, or clarifying the meaning or intent of any provision therein.
- B5.2 The Contract Administrator will issue each addendum at least two (2) Business Days prior to the Submission Deadline, or provide at least two (2) Business Days by extending the Submission Deadline.
- B5.2.1 Addenda will be available on the Bid Opportunities page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt
- B5.2.2 The Bidder is responsible for ensuring that he has received all addenda and is advised to check the Materials Management Division website for addenda regularly and shortly before the Submission Deadline, as may be amended by addendum.
- B5.2.3 The Bidder shall acknowledge receipt of each addendum in Paragraph 8 of Form A: Bid. Failure to acknowledge receipt of an addendum may render a Bid non-responsive.

B6. SUBSTITUTES

- B6.1 The Work is based on the Plant, Materials and methods specified in the Bid Opportunity.
- B6.2 Substitutions shall not be allowed unless application has been made to and prior approval has been granted by the Contract Administrator in writing.
- B6.3 Requests for approval of a substitute will not be considered unless received in writing by the Contract Administrator at least five (5) Business Days prior to the Submission Deadline.
- B6.4 The Bidder shall ensure that any and all requests for approval of a substitute:
 - (a) provide sufficient information and details to enable the Contract Administrator to determine the acceptability of the Plant, Material or method as either an approved equal or alternative;
 - (b) identify any and all changes required in the applicable Work, and all changes to any other Work, which would become necessary to accommodate the substitute:
 - (c) identify any anticipated cost or time savings that may be associated with the substitute;
 - (d) certify that, in the case of a request for approval as an approved equal, the substitute will fully perform the functions called for by the general design, be of equal or superior substance to that specified, is suited to the same use and capable of performing the same function as that specified and can be incorporated into the Work, strictly in accordance with the proposed work schedule and the dates specified in the Supplemental Conditions for Substantial Performance and Total Performance;
 - (e) certify that, in the case of a request for approval as an approved alternative, the substitute will adequately perform the functions called for by the general design, be similar in substance to that specified, is suited to the same use and capable of performing the same function as that specified and can be incorporated into the Work, strictly in accordance with the proposed work schedule and the dates specified in the Supplemental Conditions for Substantial Performance and Total Performance.
- B6.5 The Contract Administrator, after assessing the request for approval of a substitute, may in his sole discretion grant approval for the use of a substitute as an "approved equal" or as an "approved alternative", or may refuse to grant approval of the substitute.
- B6.6 The Contract Administrator will provide a response in writing, at least two (2) Business Days prior to the Submission Deadline, only to the Bidder who requested approval of the substitute.
- B6.6.1 The Bidder requesting and obtaining the approval of a substitute shall be entirely responsible for disseminating information regarding the approval to any person or persons he wishes to inform.
- B6.7 If the Contract Administrator approves a substitute as an "approved equal", any Bidder may use the approved equal in place of the specified item.
- B6.8 If the Contract Administrator approves a substitute as an "approved alternative", any Bidder bidding that approved alternative may base his Total Bid Price upon the specified item but may also indicate an alternative price based upon the approved alternative. Such alternatives will be evaluated in accordance with B16.
- B6.9 No later claim by the Contractor for an addition to the Total Bid Price because of any other changes in the Work necessitated by the use of an approved equal or an approved alternative will be considered.
- B6.10 Notwithstanding B6.2 to B6.9, and in accordance with B7.7, deviations inconsistent with the Bid Opportunity document shall be evaluated in accordance with B16.1(a).

B7. BID COMPONENTS

B7.1 The Bid shall consist of the following components:

- (a) Form A: Bid;
- (b) Form B: Prices;
- (c) Design Drawings (plan, perspective, and other submissions to illustrate the design intent);
- (d) Component Descriptions and/or other graphic or catalogue reference.
- B7.2 Further to B7.1, the Bidder should include the written correspondence from the Contract Administrator approving a substitute in accordance with B6.
- B7.3 All components of the Bid shall be fully completed or provided, and submitted by the Bidder no later than the Submission Deadline, with all required entries made clearly and completely, to constitute a responsive Bid.
- B7.4 The Bid Submission may be submitted by mail, courier or personal delivery, or by facsimile transmission.
- B7.5 If the Bid Submission is submitted by mail, courier or personal delivery, it shall be enclosed and sealed in an envelope clearly marked with the Bid Opportunity number and the Bidder's name and address, and shall be submitted to:

The City of Winnipeg Corporate Finance Department Materials Management Division 185 King Street, Main Floor Winnipeg, MB R3B 1J1

- B7.5.1 Samples or other components of the Bid Submission which cannot reasonably be enclosed in the envelope may be packaged separately, but shall be clearly marked with the Bid Opportunity number, the Bidder's name and address, and an indication that the contents are part of the Bidder's Bid Submission.
- B7.6 Bidders are advised not to include any information/literature except as requested in accordance with B7.1.
- B7.7 Bidders are advised that inclusion of terms and conditions inconsistent with the Bid Opportunity document, including the General Conditions, will be evaluated in accordance with B16.1(a).
- B7.8 If the Bid Submission is submitted by facsimile transmission, it shall be submitted to (204) 949-1178.
- B7.8.1 The Bidder is advised that the City cannot take responsibility for the availability of the facsimile machine at any time.
- B7.8.2 Bids submitted by internet electronic mail (e-mail) will not be accepted.

B8. BID

- B8.1 The Bidder shall complete Form A: Bid, making all required entries.
- B8.2 Paragraph 2 of Form A: Bid shall be completed in accordance with the following requirements:
 - (a) if the Bidder is a sole proprietor carrying on business in his own name, his name shall be inserted;
 - (b) if the Bidder is a partnership, the full name of the partnership shall be inserted;
 - (c) if the Bidder is a corporation, the full name of the corporation shall be inserted;
 - (d) if the Bidder is carrying on business under a name other than his own, the business name and the name of every partner or corporation who is the owner of such business name shall be inserted.
- B8.2.1 If a Bid is submitted jointly by two or more persons, each and all such persons shall identify themselves in accordance with B8.2.

- B8.3 In Paragraph 3 of Form A: Bid, the Bidder shall identify a contact person who is authorized to represent the Bidder for purposes of the Bid.
- B8.4 Paragraph 10 of Form A: Bid shall be signed in accordance with the following requirements:
 - (a) if the Bidder is a sole proprietor carrying on business in his own name, it shall be signed by the Bidder;
 - (b) if the Bidder is a partnership, it shall be signed by the partner or partners who have authority to sign for the partnership;
 - (c) if the Bidder is a corporation, it shall be signed by its duly authorized officer or officers;
 - (d) if the Bidder is carrying on business under a name other than his own, it shall be signed by the registered owner of the business name, or by the registered owner's authorized officials if the owner is a partnership or a corporation.
- B8.4.1 The name and official capacity of all individuals signing Form A: Bid should be printed below such signatures.
- B8.4.2 All signatures shall be original.
- B8.5 If a Bid is submitted jointly by two or more persons, the word "Bidder" shall mean each and all such persons, and the undertakings, covenants and obligations of such joint Bidders in the Bid and the Contract, when awarded, shall be both joint and several.

B9. PRICES

- B9.1 The Bidder shall state a price in Canadian funds for each item of the Work identified on Form B: Prices.
- B9.1.1 Notwithstanding C12.2.3(c), prices on Form B: Prices shall include the Manitoba Retail Sales Tax (MRST, also known as PST) but not include GST, which shall be extra where applicable.
- B9.2 The quantities listed on Form B: Prices are to be considered approximate only. The City will use said quantities for the purpose of comparing Bids.
- B9.3 The quantities for which payment will be made to the Contractor are to be determined by the Work actually performed and completed by the Contractor, to be measured as specified in the applicable Specifications.
- B9.4 Prices from Non-Resident Bidders are subject to a Non-Resident Withholding Tax pursuant to the Income Tax Act (Canada).

B10. DESIGN DRAWINGS

B10.1 The Bidder should submit drawings that illustrate the proposed design and play equipment, such as plan, perspective, and any other submission to illustrate the design intent. Additional drawings may be requested prior to award for more detailed evaluation.

B11. COMPONENT DESCRIPTION

B11.1 The Bidder shall submit component description and/or graphic or catalogue reference outlining the specifications of play equipment components.

B12. QUALIFICATION

- B12.1 The Bidder shall:
 - (a) undertake to be in good standing under The Corporations Act (Manitoba), or properly registered under The Business Names Registration Act (Manitoba), or otherwise properly registered, licensed or permitted by law to carry on business in Manitoba; and

- (b) be financially capable of carrying out the terms of the Contract; and
- (c) have all the necessary experience, capital, organization, and equipment to perform the Work in strict accordance with the terms and provisions of the Contract.
- B12.2 The Bidder and any proposed Subcontractor (for the portion of the Work proposed to be subcontracted to them) shall:
 - (a) be responsible and not be suspended, debarred or in default of any obligations to the City. A list of suspended or debarred individuals and companies is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt/debar.stm
- B12.3 The Bidder and/or any proposed Subcontractor (for the portion of the Work proposed to be subcontracted to them) shall:
 - (a) have successfully carried out work similar in nature, scope and value to the Work; and
 - (b) be fully capable of performing the Work required to be in strict accordance with the terms and provisions of the Contract; and
 - (c) have a written workplace safety and health program if required pursuant to The Workplace Safety and Health Act (Manitoba);
- B12.4 The Bidder shall submit, within three (3) Business Days of a request by the Contract Administrator, proof satisfactory to the Contract Administrator of the qualifications of the Bidder and of any proposed Subcontractor.
- B12.5 The Bidder shall provide, on the request of the Contract Administrator, full access to any of the Bidder's equipment and facilities to confirm, to the Contract Administrator's satisfaction, that the Bidder's equipment and facilities are adequate to perform the Work.

B13. OPENING OF BIDS AND RELEASE OF INFORMATION

- B13.1 Bids will not be opened publicly.
- B13.2 Following the submission deadline, the names of the Bidders and their Total Bid Prices (unevaluated, and pending review and verification of conformance with requirements) will be available on the Closed Bid Opportunities (or Public/Posted Opening & Award Results) page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt/bidopp.asp
- B13.3 After award of Contract, the name(s) of the successful Bidder(s) and the Contract Amount(s) will be available on the Closed Bid Opportunities (or Public/Posted Opening & Award Results) page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt
- B13.4 The Bidder is advised that any information contained in any Bid may be released if required by City policy or procedures, by The Freedom of Information and Protection of Privacy Act (Manitoba), by other authorities having jurisdiction, or by law.

B14. IRREVOCABLE BID

- B14.1 The Bid(s) submitted by the Bidder shall be irrevocable for the time period specified in Paragraph 9 of Form A: Bid.
- B14.2 The acceptance by the City of any Bid shall not release the Bids of the next two lowest evaluated responsive Bidders and these Bidders shall be bound by their Bids on such Work for the time period specified in Paragraph 9 of Form A: Bid.

B15. WITHDRAWAL OF BIDS

- B15.1 A Bidder may withdraw his Bid without penalty by giving written notice to the Manager of Materials at any time prior to the Submission Deadline.
- B15.1.1 Notwithstanding C23.3, the time and date of receipt of any notice withdrawing a Bid shall be the time and date of receipt as determined by the Manager of Materials.
- B15.1.2 The City will assume that any one of the contact persons named in Paragraph 3 of Form A: Bid or the Bidder's authorized representatives named in Paragraph 10 of Form A: Bid, and only such person, has authority to give notice of withdrawal.
- B15.1.3 If a Bidder gives notice of withdrawal prior to the Submission Deadline, the Manager of Materials will:
 - (a) retain the Bid until after the Submission Deadline has elapsed;
 - (b) open the Bid to identify the contact person named in Paragraph 3 of Form A: Bid and the Bidder's authorized representatives named in Paragraph 10 of Form A: Bid; and
 - (c) if the notice has been given by any one of the persons specified in B15.1.3(b), declare the Bid withdrawn.
- B15.2 A Bidder who withdraws his Bid after the Submission Deadline but before his Bid has been released or has lapsed as provided for in B14.2 shall be liable for such damages as are imposed upon the Bidder by law and subject to such sanctions as the Chief Administrative Officer considers appropriate in the circumstances. The City, in such event, shall be entitled to all rights and remedies available to it at law.

B16. EVALUATION OF BIDS

- B16.1 Award of the Contract shall be based on the following bid evaluation criteria:
 - (a) Compliance by the Bidder with the requirements of the Bid Opportunity or acceptable deviation therefrom (pass/fail);
 - (b) Qualifications of the Bidder and the Subcontractors, if any, pursuant to B12 (pass/fail);
 - (c) Total Bid Price (20 points) pursuant to B16.4.4;
 - (d) Design Drawings and Component Description (80 points) pursuant to B16.5;
 - (e) Economic analysis of any approved alternative pursuant to B6.
- B16.2 Further to B16.1(a), the Award Authority may reject a Bid as being non-responsive if the Bid is incomplete, obscure or conditional, or contains additions, deletions, alterations or other irregularities. The Award Authority may reject all or any part of any Bid, or waive technical requirements or minor informalities or irregularities, if the interests of the City so require.
- B16.3 Further to B16.1(a), the Award Authority shall reject any Bid submitted by a Bidder who does not demonstrate, in his Bid or in other information required to be submitted, that he is responsible and qualified.
- B16.4 Further to B16.1(c), the Total Bid Price shall be the sum of the quantities multiplied by the unit prices for each item shown on Form B: Prices.
- B16.4.1 If there is any discrepancy between the Total Bid Price written in figures, the Total Bid Price written in words and the sum of the quantities multiplied by the unit prices for each item, the sum of the quantities multiplied by the unit prices for each item shall take precedence.
- B16.4.2 Further to B16.1(a), in the event that a unit price is not provided on Form B: Prices, the City will determine the unit price by dividing the Amount (extended price) by the approximate quantity, for the purposes of evaluation and payment.
- B16.4.3 Further to B16.1(c) the Award Authority may reject a Bid as being non-responsive if it exceeds the budget as shown on Form B: Prices.

- B16.4.4 The Total Bid Price shall be evaluated with a weighting of 20 points out of a total of 100 possible points. As such, the lowest Bidder shall receive the full 20 points, and the second lowest Bidder and subsequent Bidders shall be pro-rated accordingly.
- B16.5 Further to B16.1(d) Design Drawings shall be evaluated with a weighting of 80 points out of a total of 100 possible points. Design / Submission will be evaluated considering the Bidder's Bid Submission and any other information required.
- B16.5.1 The Design shall be evaluated on the following criteria:
 - (a) compliance with CSA Standards (pass/fail);
 - (b) play value (maximum 45 points):
 - (i) 10 points Variety of activities provided;
 - (ii) 5 points Variety of access points & egress points;
 - (iii) 10 points Provides opportunities for social / interpersonal interaction and cooperative play;
 - (iv) 10 points Provides for fine and gross motor and sensory development;
 - (v) 5 points Fosters creative play;
 - (vi) 5 points Uniqueness of components as compared to similar playgrounds components within walking distance (400m) of the park.
 - (c) Designed for inclusive play using Universal Design principles (maximum 10 points):
 - (i) 10 points Integration of wheelchair accessible components to promote inclusive play.
 - (d) Layout/circulation (maximum 15 points):
 - (i) 4 points Efficient use of space within and between play elements;
 - (ii) 4 points Flow and relationship between play area activities;
 - (iii) 2 points Layout / orientation of components on Site and in relation to park entrances;
 - (iv) 2 points orientation to provide good visibility to play area from the adjacent road;
 - (v) 3 points slide orientation (metal facing north).
 - (e) Durability (maximum 10 points):
 - (i) 3 points Uses durable / tamper-resistant materials;
 - (ii) 2 points Low maintenance finishes and connector systems;
 - (iii) 3 points Ease of repair / replacement;
 - (iv) 2 points Manufacturer's warranty.
- B16.6 Further to B16.5.1(d), if Contractor states play equipment components are compliant with CSA Standards which are not, liquidated damages shall be charged as per D14.3 should this result in additional design and/or meeting time on the part of the Contract Administrator.

B17. AWARD OF CONTRACT

- B17.1 The City will give notice of the award of the Contract or will give notice that no award will be made.
- B17.2 The City will have no obligation to award a Contract to a Bidder, even though one or all of the Bidders are determined to be responsible and qualified, and the Bids are determined to be responsive.
- B17.2.1 Without limiting the generality of B17.2, the City will have no obligation to award a Contract where:
 - (a) the prices exceed the available City funds for the Work;
 - (b) the prices are materially in excess of the prices received for similar work in the past;

- (c) the prices are materially in excess of the City's cost to perform the Work, or a significant portion thereof, with its own forces;
- (d) only one Bid is received; or
- (e) in the judgment of the Award Authority, the interests of the City would best be served by not awarding a Contract.
- B17.3 Where an award of Contract is made by the City, the award shall be made to the responsible and qualified Bidder submitting the lowest evaluated responsive Bid, in accordance with B16.
- B17.3.1 Following the award of contract, a Bidder will be provided with information related to the evaluation of his Bid upon written request to the Contract Administrator.
- B17.4 Notwithstanding C4, the City will issue a Purchase Order to the successful Bidder in lieu of the execution of a Contract.
- B17.5 The Contract, as defined in C1.1, in its entirety shall be deemed to be incorporated in and to form a part of the Purchase Order notwithstanding that it is not necessarily attached to or accompany said Purchase Order.

PART C - GENERAL CONDITIONS

CO. GENERAL CONDITIONS

- C0.1 The General Conditions for Construction (Revision 2006 12 15) are applicable to the Work of the Contract.
- C0.1.1 The General Conditions for Construction are available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt/gen_cond.stm
- C0.2 A reference in the Bid Opportunity to a section, clause or subclause with the prefix "C" designates a section, clause or subclause in the *General Conditions for Construction*.

PART D - SUPPLEMENTAL CONDITIONS

GENERAL

D1. GENERAL CONDITIONS

D1.1 In addition to the *General Conditions for Construction*, these Supplemental Conditions are applicable to the Work of the Contract.

D2. SCOPE OF WORK

- D2.1 The major components of the Work are as follows:
 - (a) Excavate and legally dispose for new play areas;
 - (b) Supply and install new play equipment;
 - (c) Supply and install new swing set;
 - (d) Supply and install new timber edging;
 - (e) Supply and install wood fibre safety surfacing;
 - (f) Supply and install peastone safety surfacing.

D3. DEFINITIONS

- D3.1 When used in this Bid Opportunity:
 - (a) "**User**" means a person, department or other administrative unit of the City authorized by the Contract Administrator to order Work under this Contract;

D4. CONTRACT ADMINISTRATOR

D4.1 The Contract Administrator is:

Christina Harris

Urban Designer

City of Winnipeg

Parks, Riverbanks and Community Initiatives Branch

Planning and Land Use Division

Planning, Property and Development Department

15-30 Fort St.

Winnipeg. MB R3C 4X5

Telephone No. (204) 986-7436

Facsimile No. (204) 986-7524

D4.2 At the pre-construction meeting, the Contract Administrator will identify additional personnel representing the Contract Administrator and their respective roles and responsibilities for the Work.

D5. CONTRACTOR'S SUPERVISOR

D5.1 At the pre-construction meeting, the Contractor shall identify his designated supervisor and any additional personnel representing the Contractor and their respective roles and responsibilities for the Work.

D6. NOTICES

D6.1 Except as provided for in C23.2.2, all notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications to the Contractor

- shall be sent to the address or facsimile number identified by the Contractor in Paragraph 2 of Form A: Bid.
- D6.2 All notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications to the City, except as expressly otherwise required in D6.3, D6.4 or elsewhere in the Contract, shall be sent to the attention of the Contract Administrator at the address or facsimile number identified in D4.1.
- D6.3 Notwithstanding C21., all notices of appeal to the Chief Administrative Officer shall be sent to the attention of the Chief Financial Officer at the following address or facsimile number:

The City of Winnipeg Chief Financial Officer Administration Building, 3rd Floor 510 Main Street Winnipeg MB R3B 1B9

Facsimile No.: (204) 949-1174

D6.4 All notices, requests, nominations, proposals, consents, approvals, statements, authorizations, documents or other communications required to be submitted or returned to the City Solicitor shall be sent to the following address or facsimile number:

The City of Winnipeg Internal Services Department Legal Services Division Attn: City Solicitor 185 King Street, 3rd Floor Winnipeg MB R3B 1J1

Facsimile No.: (204) 947-9155

SUBMISSIONS

D7. AUTHORITY TO CARRY ON BUSINESS

D7.1 The Contractor shall be in good standing under The Corporations Act (Manitoba), or properly registered under The Business Names Registration Act (Manitoba), or otherwise properly registered, licensed or permitted by law to carry on business in Manitoba, or if the Contractor does not carry on business in Manitoba, in the jurisdiction where the Contractor does carry on business, throughout the term of the Contract, and shall provide the Contract Administrator with evidence thereof upon request.

D8. SAFE WORK PLAN

- D8.1 The Contractor shall provide the Contract Administrator with a Safe Work Plan at least five (5) Business Days prior to the commencement of any Work on the Site but in no event later than the date specified in C4.1 for the return of the executed Contract.
- D8.2 The Safe Work Plan should be prepared and submitted in the format shown in the City's template which is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt/Safety/default.stm

D9. INSURANCE

- D9.1 The Contractor shall provide and maintain the following insurance coverage:
 - (a) commercial general liability insurance, in the amount of at least two million dollars (\$2,000,000.00) inclusive, with The City of Winnipeg added as an additional insured, with a cross-liability clause, such liability policy to also contain contractual liability, unlicensed motor vehicle liability, non-owned automobile liability and products and completed

- operations, to remain in place at all times during the performance of the Work and throughout the warranty period:
- (b) automobile liability insurance for owned automobiles used for or in connection with the Work in the amount of at least two million dollars (\$2,000,000.00) at all times during the performance of the Work and until the date of Total Performance;
- (c) all risks course of construction insurance in the amount of one hundred percent (100%) of the total Contract Price, written in the name of the Contractor and The City of Winnipeg, at all times during the performance of the Work and until the date of Total Performance.
- D9.2 Deductibles shall be borne by the Contractor.
- D9.3 The Contractor shall provide the Contract Administrator with a certificate(s) of insurance, in a form satisfactory to the City Solicitor, at least two (2) Business Days prior to the commencement of any Work but in no event later than seven (7) Calendar Days from notification of the award of Contract by Purchase Order.
- D9.4 The Contractor shall not cancel, materially alter, or cause each policy to lapse without providing at least thirty (30) Calendar Days prior written notice to the Contract Administrator.

D10. SUBCONTRACTOR LIST

D10.1 The Contractor shall provide the Contract Administrator with a complete list of the Subcontractors whom the Contractor proposes to engage (Form J: Subcontractor List) at least two (2) Business Days prior to the commencement of any Work on the Site but in no event later than seven (7) Calendar Days from notification of the award of Contract.

SCHEDULE OF WORK

D11. COMMENCEMENT

- D11.1 The Contractor shall not commence any Work until he is in receipt of a Purchase Order from the Award Authority authorizing the commencement of the Work.
- D11.2 The Contractor shall not commence any Work on the Site until:
 - (a) the Contract Administrator has confirmed receipt and approval of:
 - (i) evidence of authority to carry on business specified in D7;
 - (ii) evidence of the workers compensation coverage specified in C6.15;
 - (iii) the Safe Work Plan specified inD8;
 - (iv) evidence of the insurance specified in D9;
 - (v) the Subcontractor list specified in D10.
 - (b) the Contractor has attended a pre-construction meeting with the Contract Administrator, or the Contract Administrator has waived the requirement for a pre-construction meeting.
 - (c) the Contractor has provided a written schedule of work outlining dates and duties to be performed.
- D11.3 The Contractor shall commence the Work on the Site within eight (8) weeks of receipt of the Purchase Order.
- D11.4 The City intends to award this Contract within (4) weeks after the Closing Date.
- D11.4.1 If the actual date of award is later than the intended date, the dates specified for Critical Stages, Substantial Performance, and Total Performance will be adjusted by the difference between the aforementioned intended and actual dates.

D12. SUBSTANTIAL PERFORMANCE

- D12.1 The Contractor shall achieve Substantial Performance within fifteen (15) consecutive Working Days of the commencement of the Work as specified in D11.
- D12.2 When the Contractor considers the Work to be substantially performed, the Contractor shall arrange, attend and assist in the inspection of the Work with the Contract Administrator for purposes of verifying Substantial Performance. Any defects or deficiencies in the Work noted during that inspection shall be remedied by the Contractor at the earliest possible instance and the Contract Administrator notified so that the Work can be reinspected.
- D12.3 The date on which the Work has been certified by the Contract Administrator as being substantially performed to the requirements of the Contract through the issue of a certificate of Substantial Performance is the date on which Substantial Performance has been achieved.

D13. TOTAL PERFORMANCE

- D13.1 The Contractor shall achieve Total Performance within Twenty (20) consecutive Working Days of the commencement of the Work as specified in D11.
- D13.2 When the Contractor or the Contract Administrator considers the Work to be totally performed, the Contractor shall arrange, attend and assist in the inspection of the Work with the Contract Administrator for purposes of verifying Total Performance. Any defects or deficiencies in the Work noted during that inspection shall be remedied by the Contractor at the earliest possible instance and the Contract Administrator notified so that the Work can be reinspected.
- D13.3 The date on which the Work has been certified by the Contract Administrator as being totally performed to the requirements of the Contract through the issue of a certificate of Total Performance is the date on which Total Performance has been achieved.

D14. LIQUIDATED DAMAGES

- D14.1 If the Contractor fails to achieve Substantial Performance in accordance with the Contract by the day fixed herein for Substantial Performance, the Contractor shall pay the City five hundred dollars (\$500) per Working Day for each and every Working Day following the day fixed herein for Substantial Performance during which such failure continues.
- D14.2 The amount specified for liquidated damages in D14.1 is based on a genuine pre-estimate of the City's damages in the event that the Contractor does not achieve Substantial Performance by the day fixed herein for same.
- D14.3 If the Contractor misrepresents the CSA compliance of play equipment being installed and this results in additional design and/or meeting time on the part of the Contract Administrator, the Contractor shall pay the City five hundred dollars (\$500) per Working Day for each and every Working Day during which such additional work continues.
- D14.4 The amount specified for liquidated damages in D14.3 is based on a genuine pre-estimate of the City's damages in the event that the Contractor causes such additional work.
- D14.5 The City may reduce any payment to the Contractor by the amount of any liquidated damages assessed.

D15. EXISTING SERVICES AND UTILITIES

D15.1 No responsibility will be assumed by the City for correctness or completeness of the Drawings, when provided, with respect to the existing utilities, pipes or other objects either underground or on the surface; the City shall not be liable for the incorrectness and inadequacy thereof. It shall be the responsibility of the Contractor to determine the location of all such utilities, pipes and other objects and to make good any damage done to them.

D16. ACCESS TO SITE

- D16.1 Access to the Site as required by the Contractor shall be provided and maintained by the Contractor at his own expense and approved by the Contract Administrator.
- D16.2 The Contractor's operations shall be limited to the minimum area necessary for undertaking the Work and he shall be responsible for all damage resulting from his Work on private property.

D17. DAMAGE TO EXISTING STRUCTURES, TREES AND PROPERTY

- D17.1 All necessary precautions shall be exercised by the Contractor so as not to remove, disturb, or damage any existing trees, shrubs, sod, pavements, streets, roads, boulevards, poles, hydrants, water pipes, gas pipes, electrical wires, cables, conduits, sewers or other existing facilities and equipment at the Site of the Work. For all damage incurred in the performance of the Work (either directly or indirectly), the Contractor shall either replace and repair such damage, whichever may be deemed necessary in the opinion of, and acceptable to City of Winnipeg Contract Administrator, and the cost of which shall be borne entirely by the Contractor. The Contractor shall also indemnify and save harmless the City from all claims made directly or indirectly against it in respect to any such damage.
- D17.2 The Contractor shall take the following precautionary steps to prevent damage from construction activities to existing park trees within the limits of the construction area.
- D17.3 The Contractor shall not stockpile materials and soil or park vehicles and equipment within 2 metres of trees.
- D17.4 Trees identified to be at risk by the Contract Administrator are to be strapped with 25x100x2400 wood planks, or suitable protected as approved by the Contract Administrator.
- D17.5 Excavation shall be performed in a manner that minimizes damage to the existing root systems. Where possible, excavation shall be carried out such that the edge of the excavation shall be a minimum of 1.5 times the diameter (measured in inches), with the outcome read in feet, from the closest edge of the trunk. Where roots must be cut to facilitate excavation, they shall be pruned neatly by a certified arborist at the face of excavation.
- D17.6 Operation of equipment within the drip line of the trees shall be kept to a minimum required to perform the Work required. Equipment shall not be parked, repaired, refuelled; construction materials shall not be stored, and earth materials shall not be stockpiled within the drip lines of trees. The drip line of a tree shall be considered to be all of the ground surface located beneath the tree and radiating out to the tips of its outermost branches. The Contractor shall ensure that the operations do not cause flooding or sediment deposition on areas where trees are located.
- D17.6.1 All damage to existing trees caused by the Contractor's activities shall be repaired to the requirements and satisfaction of the Contract Administrator and the City Forester or his/her designate.
- D17.7 No separate measurement or payment will be made for the protection of trees.

CONTROL OF WORK

D18. JOB MEETINGS

D18.1 Regular weekly job meetings, or as otherwise specified by the Contract Administrator, will be held at the Site. These meetings shall be attended by a minimum of one representative of the Contract Administrator, one representative of the City and one representative of the Contractor. Each representative shall be a responsible person capable of expressing the position of the Contract Administrator, the City and the Contractor respectively on any matter discussed at the meeting including the Work schedule and the need to make any revisions to the Work schedule. The progress of the Work will be reviewed at each of these meetings.

D18.2 The Contract Administrator reserves the right to cancel any job meeting or call additional job meetings whenever he deems it necessary.

D19. PRIME CONTRACTOR – THE WORKPLACE SAFETY AND HEALTH ACT (MANITOBA)

D19.1 Further to C6.24, the Contractor shall be the Prime Contractor and shall serve as, and have the duties of the Prime Contractor in accordance with The Workplace Safety and Health Act (Manitoba).

MEASUREMENT AND PAYMENT

D20. PAYMENT

D20.1 Further to C12, the City may at its option pay the Contractor by direct deposit to the Contractor's banking institution.

WARRANTY

D21. WARRANTY

D21.1 Notwithstanding C13.2, the warranty period shall begin on the date of Total Performance and shall expire one (1) year thereafter except where longer warranty periods are specified in the respective specification sections, unless extended pursuant to C13.2.2, in which case it shall expire when provided for thereunder.

D22. SITE RESTORATION

D22.1 Total Performance of the Work shall not be attained until the Contractor has cleaned up the Site and has removed all tools, equipment, waste, debris and surplus foundation earth to the satisfaction of the Contract Administrator. Unless otherwise specified, the Contractor shall restore all areas of the Site beyond the established limit of Work, which have been disturbed by the Contractor's operations to as good as or better than the original condition to the satisfaction of the Contract Administrator. The Contractor shall pay all costs associated with this Work.

FORM J: SUBCONTRACTOR LIST

(See D10)

ENDERTON PARK PLAYGROUND REDEVELOPMENT

<u>Name</u>	Address

PART E - SPECIFICATIONS

GENERAL

E1. APPLICABLE SPECIFICATIONS AND DRAWINGS

- E1.1 These Specifications shall apply to the Work.
- E1.2 The City of Winnipeg Standard Construction Specifications in its entirety, whether or not specifically listed on Form B: Prices, shall apply to the Work.
- E1.2.1 The City of Winnipeg Standard Construction Specifications is available on the Information Connection page at The City of Winnipeg, Corporate Finance, Materials Management Division website at http://www.winnipeg.ca/matmgt/Spec/Default.stm
- E1.2.2 The version in effect three (3) Business Days before the Submission Deadline shall apply.
- E1.2.3 Further to C2.4(d), Specifications included in the Bid Opportunity shall govern over *The City of Winnipeg Standard Construction Specifications*.
- E1.3 The following are applicable to the Work:

<u>Drawing No.</u>	<u>Drawing Name/Title</u>
E.12-E	Existing Site Conditions and Removals
E.12-F	Proposed Playground
SCD-651	Single Timber Edging Detail
SCD-651a	Double Timber Edging Detail
SCD-650a	Wood Fibre Safety Surfacing Drainage Diagran

E2. GENERAL COMMENTS

- E2.1 This specification shall cover the supply and installation of the Play Equipment as listed below.
- E2.2 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the drawings and specifications.
- E2.3 The Contractor shall obtain all approvals including the requisite Development Permit.
- E2.4 Play Equipment
 - (a) One Play Structure and/or independent components to accommodate children ages 2 to 12 years of age:
 - (b) Minimum one (1) metal slide (which must face north or east):
 - (c) One (1) Swingset [2 Bays (2 Belt Seats, 2 Baby Seats)];
 - (d) To include accessible play equipment or components.
- E2.5 If colour is a feature of posts or top caps the Contract Administrator shall have the ability to modify specified colours from the proposed design after Contract Award. If the price of the equipment in the Bid Submission is subject to the colours of the proposed design, this must be indicated in the Bid Submission.
- E2.6 Components which are unacceptable are the following:
 - (a) Wooden structures;

- (b) Tube (enclosed) slides and crawl tubes;
- (c) Play panels with many small moving parts;
- (d) Cable rides;
- (e) Sand diggers;
- (f) Merry-go-rounds;
- (g) Tire Swings;
- (h) Talk tubes;
- (i) Binoculars / telescopes;
- (i) Barrel rollers; and
- (k) Large number of plastic components.

E3. PLAYSTRUCTURES

- E3.1 General Description
- E3.1.1 This specification shall cover the supply and installation of one or more Playstructures as specified herein.
- E3.1.2 Further to B16.5.1(b)(vi) which reads "uniqueness of components as compared to similar playgrounds components within walking distance (400m) of the park", the play equipment within walking distance (400m) to Enderton Park is located at:
 - (a) Benson Park McMillan @ Cockburn
 - (b) Grosvenor School 1045 Grosvenor Avenue
- E3.1.3 Play equipment shall be installed in the play areas as shown on the attached Drawing E.12-F. The play equipment and their safety zones must fit into the proposed play areas as shown on Drawing E.12-F.
- E3.2 Materials
- E3.2.1 Posts / Caps
 - (a) All posts shall be a minimum 5" O.D. round or 4" square tubing.
 - (b) 3.5 "O.D. round or 3.0" square tubing will be permitted in circumstances where a multi-deck structure has decks of varied heights which are all under 4', or for structures with 2 decks or less.
 - (c) All posts shall be fabricated from either aluminum (0.125" min. wall thickness) or galvanized steel (0.120" min. wall thickness) tubing. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating. The bottom end of the posts is to be sealed with a moisture barrier.
 - (d) Top caps shall be made of steel construction and shall be factory installed and secured in place with tamper proof, self-sealing rivets. Plastic top caps will be accepted if made of solid construction (hollow caps not accepted).
 - (e) If painted colour is a feature of posts and top caps, it shall be a baked-on polyester powder coating. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance.
- E3.2.2 Decks (if applicable)
 - (a) All decks shall be manufactured from vinyl-coated perforated steel or a steel core composite. Deck heights may vary to a maximum height of 6'.

E3.2.3 Clamping System

(a) All deck, rail and play component clamping systems shall be fabricated from zinc plated, galvanized steel, stainless steel or aluminum. Tamper proof, corrosion resistant fasteners shall be used to retain clamping systems.

E3.2.4 Handrails, Safety Rails and Handloops (if applicable)

- (a) All handrails, safety rails and handloops shall be fabricated using a minimum of 15/16" (24mm) O.D. with a 120" wall thickness steel tubing. After all fabrication activities have occurred including end cuts, drill holes, bends and weld joints, all components shall be hot dipped galvanized.
- (b) Smooth all cut edges and weld joints prior to hot dip galvanizing and ensure that all tubing is free from burrs, cracks, defects and other imperfections.

E3.2.5 Hardware

- (a) All fasteners shall be socketed and tamper proof in design, and either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel.
- (b) All necessary hardware shall be provided.

E3.2.6 Poly Components

- (a) Poly components such as slides and hoods shall be fabricated from U.V. stabilized, rotationally molded linear low-density polyethylene.
- (b) Poly components such as play panels shall be fabricated from compression molded solid colour, U.V. stabilized, high-density polyethylene.

E3.2.7 Slides (if applicable)

- (a) Stainless steel is preferred for slide beds, although a plastic slide may be used if there is a stainless steel slide also on the Site. North or east orientation preferred.
- E3.2.8 Each playstructure shall have kick plates and hand loops as required to meet the most recent Canadian Standards Association Standards.

E3.3 Installation

- E3.3.1 Play equipment shall be installed as per manufacturer's specifications and in accordance with the most recent Canadian Standards Association Standards.
- E3.3.2 All posts and other vertical items shall be plumb and true to vertical, if so designed.
- E3.3.3 All decks shall be level, if so designed.
- E3.4 Method of Measurement and Basis of Payment
- E3.4.1 Method of Measurement shall be as follows:
 - (a) Playstructures will comprise only part of the overall Play Equipment, measured on a lump sum basis for the following:
 - Item 2: "Supply & Install New 2-12 yr. Play Equipment "on Form B: Prices. This shall include all play equipment, including independent components proposed for this area, but excluding swings;
 - (ii) Swings shall be paid for as per E5.

E3.4.2 Basis of Payment shall be as follows:

(a) Playstructures will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E4. INDEPENDENT COMPONENTS

- E4.1 General Description
- E4.1.1 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the specifications.
- E4.1.2 This specification shall cover the supply and installation of Independent Components as specified herein.
- E4.1.3 Independent Components shall be installed as per the proposed design, as the proposed budget will allow.
- E4.1.4 Independent Components shall be installed in the available area as shown on Drawing E.12-F. The Components and their safety zones must fit into the proposed play area.
- E4.2 Materials
- E4.2.1 All materials shall be structurally sound and suitable for safe play. Durability shall be ensured on all parts and materials.
- E4.2.2 There shall be a minimum (or no) amount of hollow plastic components. Solid plastic is acceptable.
- E4.2.3 There shall be a minimum amount of solid elements which limit visibility through the Site.
- E4.2.4 Fasteners
 - (a) All hardware shall be tamper-proof in design and requiring special tools. It shall be either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel. All necessary hardware and tools shall be provided.
- E4.2.5 Finishes
 - (a) Finishes shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating.
- E4.2.6 Slides
 - (a) If an independent slide is proposed, stainless steel is preferred. If other slides are proposed on the Site one may be plastic. North or east orientation preferred. If independent slide over 4' high is proposed, support posts must be minimum 5"O.D.
 - (b) Tube (enclosed) slides and plastic spiral slides will not be accepted.
- E4.3 Method of Measurement and Basis of Payment
- E4.3.1 Method of Measurement shall be as follows:
 - (a) As identified in E3.4.1, measurement will be incorporated into the lump sum costs for the play area. As such, no separate measurement will be made for Independent Components.
- E4.3.2 Basis of Payment shall be as follows:
 - (a) Independent Components, if proposed, shall be included in Item 2: "Supply & Install New 2-12 yr. Play Equipment "on Form B: Prices. No separate payment shall be made.

E5. SWING STANDARD

- E5.1 General Description
- E5.1.1 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the specifications.

- E5.1.2 This specification shall cover the supply and installation of two (2) complete swing standard, as specified herein:
 - (a) Three Leg Heavy Duty Swing Frame, 8ft. high, complete with two (2) slash-proof rubber belt seats and two (2) slash-proof rubber enclosed infant seats, heavy-duty chain, swing hangers and "S" hooks / bolt links.

E5.2 Materials

E5.2.1 Topbeam

(a) Topbeam shall be fabricated from 3 1/2" O.D. 7 gauge, RS40 galvanized steel pipe OR 2 3/8" O.D. 5 gauge, RS40 galvanized steel pipe with anti-wrap swings and with a baked-on polyester powdercoating. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating prior to powdercoating.

E5.2.2 Legs

(a) All legs shall be fabricated from 2 3/8" O.D. 10 gauge, RS40 galvanized steel pipe with a baked-on polyester powdercoating. The powder coating finish shall meet or exceed ASTM standards for hardness, adhesion, impact and salt spray resistance. All fabrication cuts, drill holes and weld joints shall be sprayed with a corrosion resistant coating prior to powdercoating. The bottom end of the posts is to be sealed with a moisture barrier.

E5.2.3 Yoke Clamps

(a) All yoke clamps shall be either one piece construction and fabricated from 8 gauge, RS40 galvanized steel pipe or two piece, compression clamping cast aluminum or galvanized metal complete with tamper-proof hardware.

E5.2.4 Swing Hangers

(a) All swing hangers shall be fabricated from galvanized malleable iron and have oil impregnated bearings pressed in.

E5.2.5 Swing Chain

(a) All swing chain shall be 4/0 straight link, galvanized steel.

E5.2.6 Enclosed Infant (Bucket) Seats

(a) Enclosed infant seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the seat slashproof. Infant seats shall be fully enclosed to prevent slipping out and provide extra lower back support.

E5.2.7 Belt Seats

(a) Belt seats shall be moulded of U.V. stabilized, high quality, rubber with a tempered stainless steel reinforcement plate insert moulded inside, rendering the seats slashproof. The perimeter shall be moulded to form a blunt, impact absorbing edge.

E5.2.8 Hardware

(a) All fasteners shall be tamper proof in design, requiring special tools. The fasteners shall be either carbon steel plated with zinc/nickel and iridescent chromate finish or stainless steel.

E5.2.9 Concrete Foundations

 (a) Post shall be installed into a concrete footing the composition of which is detailed in E6.

E5.3 Installation

E5.3.1 Installation shall be in accordance with Manufacturer's specifications.

- E5.3.2 Top rail is to be level and posts securing anchored in concrete.
 - (a) Swing seats shall not be installed until the protective surfacing (in accordance with E10) has been installed.
- E5.4 Method of Measurement and Basis of Payment
- E5.4.1 Method of Measurement shall be as follows:
 - (a) Swing Standard will be measured on a per unit basis for Item 3: "Supply & Install New 2-Bay Swingset (2 Belts, 2 Baby)" on Form B: Prices.
- E5.4.2 Basis of Payment shall be as follows:
 - (a) Swing Standard will be paid for at the Contract Unit Prices on Form B: Prices. The amount to be paid for shall be the total number of units, measured as specified herein, which price shall be for full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E6. FOUNDATIONS

- E6.1 General Description
- E6.1.1 All playground equipment posts, bases and anchors are to be set in concrete footings or piles to ensure stability and prevent frost heaving. The current Standard Construction Specifications of the City of Winnipeg, CW 2160-R7.Concrete to be used in Underground Works, is to be utilized in the installation of the concrete works for all below ground components.
- E6.2 Materials
- E6.2.1 The specific concrete requirements shall be:
 - (a) Sulfate resistant, Type 50 Cement;
 - (b) 28 day compressive strength of 30 Mpa;
 - (c) maximum aggregate size of 20mm, nominal;
 - (d) slump 80 +/- 20mm;
 - (e) maximum water/cement ratio 0.49.
- E6.3 Installation
- E6.3.1 All posts and supports shall be centred in the concrete footing such that there is a complete collar of concrete around each post and support. Where posts are not perfectly centred there should be a minimum of 2" concrete at any point around the post.
- E6.3.2 All concrete footings for play equipment shall be a minimum of 3' depth, or in accordance with Manufacturer's specifications, whichever is greater.
- E6.4 Method of Measurement and Basis of Payment
- E6.4.1 Method of Measurement shall be as follows:
 - (a) Foundations shall be incidental to the measurement of Playstructures, Independent Components and Swing Standard listed above and as shown on Form B: Prices.
- E6.4.2 Basis of Payment shall be as follows:
 - (a) No separate payment shall be made for play equipment foundations.

E7. MAINTENANCE KITS

E7.1 All play equipment shall include the supply of maintenance kits. Maintenance kits shall include maintenance manuals, complete manufacturer's parts lists, touch-up paint, PVC repair paint,

10% extra of each bolt, washer and any other hardware utilized on the play equipment, and all special tools necessary for assembly and maintenance.

E7.2 There shall be no payment for maintenance kits.

Site Development

E8. EXCAVATION AND DISPOSAL

- E8.1 General Description
- E8.1.1 New areas for play equipment are to be removed and legally disposed of.
- E8.1.2 Work shall include but not be limited to the following:
 - (a) Excavate and dispose for new play areas as required.
- E8.1.3 All extraneous materials are to be removed from the Site and disposed of in a safe and legal manner. This specification shall amend and supplement City of Winnipeg Standard Construction Specifications CW 3110 R11. The Work to be done by the Contractor under this specification shall include all labour, equipment and material necessary for and incidental to the satisfactory performance and completion of the Work herein specified.
- E8.2 Materials
- Excavation and disposal includes the removal of items as indicated on the Drawings and as directed by the Contract Administrator. Work includes the satisfactory disposal of unsuitable Site material such as clays susceptible to frost-heaving, silts, rock rubble rubbish and any surplus suitable Site material. Do not disturb adjacent items designated to remain in place.
- E8.3 Construction Methods
- E8.3.1 Swingset Area:
 - (a) The Swingset Area to be excavated to the depths required to accept a minimum 300mm depth of safety play stone. The area shall be within the maximum area as shown on Drawing E.12-F, to the dimensions as per the design submission, in accordance with the Double Timber Edging Detail on Drawing SCD 651a.
- E8.3.2 Play Equipment Area:
 - (a) The Play Equipment Area is to be excavated to the depths required to accept adequate wood fibre surfacing for the proposed equipment, as per manufacturer's instructions. The area shall be within the maximum area as shown on Drawing E.12-F, to the dimensions as per the design submission, in accordance with the Single Timber Edging Detail on Drawing SCD 651.
- E8.3.3 Disposal of material shall be understood to mean the hauling of all unsuitable material from the Site and the unloading in a legal manner acceptable to the Contract Administrator. If arrangements are made in advance excavated material may be disposed of on Site at a location designated by the Contract Administrator.
- E8.3.4 Contractor must coordinate with the Contract Administrator to ensure all removals have occurred.
- E8.4 Method of Measurement and Basis of Payment
- E8.4.1 Method of Measurement shall be as follows:
 - (a) Excavation and disposal for new play areas shall be measured on a cubic metre basis for Item 1: "Excavate and Legally Dispose Existing Surface for New Play Areas" on Form B: Prices.
- E8.4.2 Basis of Payment shall be as follows:

(a) Excavation and Disposal will be paid for at the Contract Unit Prices on Form B: Prices. The amount to be paid for shall be the total number of units, measured as specified herein, which price shall be for full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E9. TIMBER EDGING

- E9.1 General Description
- E9.1.1 The Contractor shall furnish all labour, materials, equipment and services necessary to complete the Work according to the drawings and specifications.
- E9.1.2 This specification shall cover the supply and installation of 1-tier timber edging to contain the wood fibre safety surfacing for the proposed play area as per Drawing SCD 651 and the installation of 2-Tier timber edging to contain the peastone safety surfacing for the swingset area as per Drawing SCD 651a.
- E9.2 Materials and Method
- E9.2.1 Cap shall be Pedra and shall not be treated. Top edges of all exposed timbers shall have an 8mm (45°) chamfer. The Pedra cap shall be pre-drilled and screwed with two screws at each end of the timber and at alternating sides at 600mm O.C.
- E9.2.2 All wood for the bottom row shall be pressure treated spruce, pine or fir, No. 2 or better, no wane, bark, checking or splitting permitted. Wood shall be smooth and free of rough areas. All timbers to be 150 x 150mm with a minimum length of 1200mm. All ends and cuts shall be treated with preservative before being secured.
- E9.2.3 Edging material shall be cut neatly for a proper fit with no spaces or gaps between. Finished elevations shall ensure that all edging material is smooth, level, set plumb and spaced uniformly.
- E9.2.4 Turf shall be repaired as required around edging in accordance with City of Winnipeg Standard Specifications for Topsoil and Sodding.
- E9.3 Method of Measurement and Basis of Payment
- E9.3.1 Method of Measurement shall be as follows:
 - (a) Edging will be measured on a linear metre basis for Item 4: "Supply and Install 2-Tier Timber Edging" and Item 5: "Supply and Install 1-Tier Timber Edging" on Form B: Prices.
- E9.3.2 Basis of Payment shall be as follows:
 - (a) Timber edging will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E10. PROTECTIVE SURFACING

- E10.1 General Description
- E10.2 This specification shall cover the supply and install of two types of safety surfacing: playstone and wood fibre.
- E10.3 Wood Fibre Surfacing
- E10.3.1 Description
 - (a) This specification shall cover the supply and installation of Wood Fibre Surfacing within the Play Equipment Area.

(b) This specification shall cover the supply and installation of Wood Fibre Surfacing to drain externally as per Drawing SCD-650a.

E10.3.2 Materials

- (a) Wood Fibre product shall be either Zeager Woodcarpet or Fibar FibarSystem 200 or 300 products or substitute acceptable to Contract Administrator.
 - (i) Contact for Woodcarpet:

Zeagar Bros. Inc.

4000 East Harrisburg Pike ·

Middletown, PA 17057

USA

Ph: (1-888) 346-8524 or (717) 944-7481 ·

Fax (717) 944-7681

sales@zeager.com

(ii) Contact for FibarSystem 200 or 300:

The Fibar Group LLC 80 Business Park Drive, Suite 300 Armonk, NY 10504-1705 USA

Ph: (800) 342-2721 Fax: (914) 273-8659

info@FibarPlaygrounds.com

(b) Wood Fibre surfacing shall include wood fibre, filter cloth, subsurface drainage system and mats for bottom of slides, if applicable.

E10.3.3 Construction Methods

- (a) Wood Fibre shall be installed within the play area, as defined by the timber edging to a minimum depth of 200 mm (after compaction). In the case where proposed play equipment includes a maximum fall height greater than 2.4m (8'), depth of material to directly correspond to maximum fall height of play equipment in accordance with manufacturer's specifications.
- (b) The installation of the Wood Fibre shall be done immediately after the play equipment has been installed.
- (c) Installation of entire system, including fibre, filter cloth, subsurface drainage and mats shall be done according manufacturer's instructions. Adequate drainage within play equipment area must be ensured as per same.
- (d) Subsurface of play area shall be graded to drain to the north. 100mm drainage pipe shall be installed from the subsurface drainage system within the play area to run north to drain towards and tie into the existing catch basin. This shall be installed in coordination with the installation of a new limestone pathway (to be done by others) as per instruction from the Contract Administrator. The cost of this shall be included in the price for the wood fibre supply and installation.
- (e) Installation shall be done by equipment sized to suit the Work being done and the Wood Fibre shall be spread by hand as necessary in the immediate vicinity of the play equipment so as not to damage same. The play equipment shall be swept clean to the satisfaction of the Contract Administrator after installation of the Wood Fibre.

E10.4 Method of Measurement and Basis of Payment

E10.4.1 Method of Measurement shall be as follows:

(a) Protective Surfacing will be measured on a square metre basis for Item 7: "Supply and Install New Wood Fibre Safety Surfacing (includes associated drainage)" on Form B: Prices.

E10.4.2 Basis of Payment shall be as follows:

(a) Protective Surfacing will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E10.5 Safety Stone Surfacing (Playstone)

E10.5.1 Description

(a) This specification shall cover the supply and installation of Safety Stone Surfacing within the Swingset Area.

E10.5.2 Materials

(a) Safety Stone shall be 6.0mm Playground Stone, composition shall be Typical Birds Hill glacial till material, 100% clean river-washed granite conforming to the following sizes of sieve:

> 100% passing 10mm 45% passing 5mm Up to 10% passing 2.5mm Up to 4% passing 1.25mm 0% passing 0.8mm sieve

E10.5.3 Construction Methods

- (a) Safety Stone shall be installed within the Swingset Area, as defined by the timber edging, to a minimum depth of 300 mm.
- (b) Subsurface of swings area shall be graded to drain to the west towards the catch basin.
- (c) The installation of the Safety Stone shall be done immediately after the swingset has been installed.
- (d) Installation shall be done by equipment sized to suit the Work being done and the Stone shall be spread by hand as necessary in the immediate vicinity of the play equipment so as not to damage same. The play equipment shall be swept clean to the satisfaction of the Contract Administrator after installation of the Stone.

E10.6 Method of Measurement and Basis of Payment

E10.6.1 Method of Measurement shall be as follows:

(a) Protective Surfacing will be measured on a cubic metre basis for Item 6: "Supply & Install New Peastone Safety Surfacing to 300mm depth" on Form B: Prices.

E10.6.2 Basis of Payment shall be as follows:

(a) Protective Surfacing will be paid for at the Contract Unit Prices. The amount to be paid for shall be the total number of units, as indicated on Form B: Prices. This price shall be full payment for supplying all labour, equipment and materials, and performing all operations herein described and all other items incidental to the Work and as accepted by the Contract Administrator.

E11. SODDING AND SITE RESTORATION

E11.1 Description

(a) Total Performance of the Work shall not be attained until the Contractor has cleaned up the Site and has removed all tools, equipment, waste, debris and surplus foundation earth to the satisfaction of the Contract Administrator. Unless otherwise

- specified, the Contractor shall restore all areas of the Site beyond the established limit of Work, which have been disturbed by the Contractor's operations to as good as or better than the original condition to the satisfaction of the Contract Administrator. The Contractor shall pay all costs associated with this Work.
- (b) Sod and Topsoil: The Contractor shall install mineral sod and a minimum 75mm compacted thickness of topsoil, as required, and in accordance with CW 3510-R9 and CW 3540-R5.
 - (i) The Contractor shall install mineral sod and topsoil in any areas requiring repair as a result of damage from the Work.
- E11.2 Method of Measurement and Basis of Payment
- E11.2.1 Method of Measurement shall be as follows:
 - (a) Sodding and Site Restoration shall be incidental to the measurement of play equipment installation and siteworks.
- E11.2.2 Basis of Payment shall be as follows:
 - (i) No separate payment shall be made for Sodding and Site Restoration.