

WINNIPEG

DEMOLITION NOTES:

- REMOVE AND CLEAN EXISTING FORCEFLOW UNIT FROM ATHLETE ENTRY TO ALLOW FOR THE DEMOLITION OF THE WALL UNIT TO BE REINSTALLED AT LATER. DATE.
- (2) REMOVE GHS AND GHR DROPS AT WALL TO ALLOW FOR THE DEMOLITION OF THE WALL. GLYCOL SOLUTION TO BE DRAINED BACK TO GLYCOL FEED SYSTEM IN DELIVERY ROOM. CAP LINES.
- (3) REMOVE SIDEWALL SPRINKLER HEAD AND ASSOCIATED PIPING FOR THE DEMOLITION OF THE EXISTING WALL. CAP REMAINING SERVICE.
- (4) REMOVE EXISTING 12" x 12" LOUVRE
- 5 REMOVE EXISTING 12" x 12" LOUVRE.
- 6 REMOVE EXISTING EXHAUST FAN, DUCTWORK, LOUVRE AND SUPPORTS. COORDINATE THE INFILL OF THE OPENING WITH THE GENERAL CONTRACTOR.
- (7) REMOVE EXISTING FORCE FLOW UNIT FROM WALL TO ALLOW FOR THE INSTALLATION OF A NEW DOOR.
- (8) EXISTING CO2 SENSOR TO REMAIN.
- EXISTING SCALE FOR CO2 TANKS TO REMAIN.
- EXISTING SIDEWALL SPRINKLER HEAD TO REMAIN.
- (1) EXISTING FORCE FLOW UNIT TO REMAIN.
- 2 EXISTING PIPE TO REMAIN.

JDB 3	MECHANICAL DEMOLITION PLANS	SHEET NO.
WED BY PDT (ED BY	PAN AM POOL ELECTRICAL UPGRADE	PROJECT NO. 137300