


## METRIC WHOLE NUMBERS INDICATE MILLIMETRES DECIMALIZED NUMBERS INDICATE METRES

· · · ·	GAS		0	MANHOLE	•		CONCRETE PAVEMENT		LOCATION APPROVED	BM -							PROFESSIONAL'S SEAL
· · · 🔀 -	MTS / PEDESTAL			CATCH BASIN / CATCH PIT			CONC SIDEWALK / MEDIAN			ELEV -			CCVL		IILLER + I	<b>IIIDD AV</b>	itoba as
· — — – 🕀	HYDRO / CABINET		Δ	CURB INLET WITH BOX	<b>A</b>		ASPHALT PAVEMENT						JUAI		IILLEN - I	MUNNAT	and and
· · · · ·	CATV / FIBRE OPTIC		$\odot$	TREE			PAVING STONE		SUPR. U/G STRUCTURES DATE				١	visionary urba	n design + lands	capes	2 V
	TRAFFIC SIGNALS / PIT		🔶 TH-12	TEST HOLE			GRAVEL		COMMITTEE								CHERYL DIXON
	LAND DRAINAGE SEWER			PROPERTY LINE			RAMP CURB		<b>NOTE:</b> LOCATION OF UNDERGROUND STRUCTURES					CD		DM	n Member No. 117
	SANITARY/COMBINED SEWER		+	SURVEY BAR			PLANING / REMOVAL		AS SHOWN ARE BASED ON THE BEST				ы		Ы		- 2
	CB LEAD / SSP / DCP		××	FENCE					INFORMATION AVAILABLE BUT NO GUARANTEE IS GIVEN THAT ALL EXISTING				DRAWN BY	WF	APPROVED BY	СО	311, 1006
·	WATER MAIN	—·—		BOC / EDGE OF PAVEMENT					UTILITIES ARE SHOWN OR THAT THE GIVEN								YOUR ADR.
	SUBDRAIN		33.000	ELEVATION	( <u>33.333</u> )				<ul> <li>LOCATIONS ARE EXACT. CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL</li> </ul>	B ISSUED FOR TENDER	18/09/04	co	HOR SCALE	1:250	RELEASED FOR	CONSTRUCTION	
${\leftarrow}$	DITCH	•	-0-	TRAFFIC SIGN					SERVICES MUST BE OBTAINED FROM THE	A ISSUED FOR CLIENT REVIEW	18/06/27	CO	VERT SCALE	N/A		N/A	CONSULTANT FILE NAM
EXISTING	LEGEND - PLAN	NEW	EXISTING	LEGEND - PLAN	NEW	EXISTING	LEGEND - PLAN	NEW	WITH CONSTRUCTION.	No. REVISIONS	YY/MM/DD		DATE	18/06/27	DATE		602-2018_Drawing_P-3494-75-F
						-							<b>-</b>				

Ċ N Ш 000

## LANDSCAPE LEGEND



CITY OF WINNIPEG SPEC CW 3520 & CW 3540 NATIVE GRASSES 2 YEAR ACCEPTANCE PERIOD,

**TOPSOIL & SEEDING TO MEET** 

FOLLOWED BY A 1 YEAR MAINTENANCE AND WARRANTY

EXISTING TREES TO REMAIN

EXISTING TREES TO BE TRIMMED

EXISTING TREES TO BE REMOVED

## NOTES

ALL CONSTRUCTION MATERIALS AND METHODS TO BE IN ACCORDANCE WITH "THE CITY OF WINNIPEG, STANDARD CONSTRUCTION SPECIFICATION AND STANDARD DETAILS" (LATEST REVISION).

- 2. CONTRACTOR TO TAKE PRECAUTIONARY STEPS AS OUTLINED IN THE SPECIFICATIONS TO PROTECT EXISTING TREES WITHIN THE LIMITS OF CONSTRUCTION FROM DAMAGE FROM CONSTRUCTION ACTIVITIES.
- 3. CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.
- 4. CONTRACTOR MUST FOLLOW THE REQUIREMENTS OF THE
- VARIOUS UTILITIES. 5. FINAL LOCATION OF REST STOPS TO BE CONFIRMED ON
- SITE PRIOR TO CONSTRUCTION.
- 6. CONTRACTOR SHALL INSTALL TOPSOIL AND SEEDING / NATIVE GRASS TO ALL AREAS WHERE MATERIAL IS REMOVED AND NOT RE-ESTABLISHED. FINAL EXTENT & SEEDING TYPE TO BE CONFIRMED ON SITE PRIOR TO CONSTRUCTION.
- 7. TOPSOIL AND SEEDING / NATIVE GRASS SHALL BE PLANTED AT A DISTANCE AS INDICATED BELOW, UNLESS NOTED OTHERWISE ON PLAN:
- a. TYPICAL 1.0m OFFSET FROM SIDEWALK / PATHWAY b. TYPICAL 0.6m OFFSET FROM SILT FENCING
- 8. CONTRACTOR TO STAKE PROPOSED TREE LOCATION ON SITE, LAYOUT TO BE APPROVED BY LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- 9. SEE SHEET 84 FOR PROPOSED TREE PLANTING DETAILS 10. BOULEVARD TREES SHALL BE PLANTED AT A MINIMUM DISTANCE FROM ABOVE GROUND STRUCTURES AS INDICATED BELOW:
- a. MINIMUM DISTANCE FROM STREET INTERSECTIONS: 6m
- b. MINIMUM DISTANCE FROM LIGHT STANDARDS: 3m c. MINIMUM DISTANCE FROM PRIVATE APPROACHES:
- 1.5m d. MINIMUM DISTANCE FROM HYDRANTS: 3m
- e. MINIMUM DISTANCE FROM HYDRO POLES: 3m
- f. MINIMUM DISTANCE FROM MANHOLES/CB'S/SEWER GRATES: 3m

PLANT LIST

(REFER TO SHEET 84 FOR FULL PLANT SCHEDULE & DETAILS)

11. ALSO REFER TO WRITTEN SPECIFICATION.

