



MAIN FLOOR REFLECTED CEILING PLAN

SCALE 1:100

CEILING GENERAL NOTES:

- DIMENSIONS INDICATED ARE TAKEN FROM FINISHED FACE TO FINISHED FACE UNLESS OTHERWISE INDICATED.
- VERIFY DIMENSIONS AND DATA HERE IN WITH CONDITIONS ON SITE. REPORT ANY DISCREPANCY TO THE DESIGNER FOR ADJUSTMENT.
- LIGHTING FIXTURES, DIFFUSERS, ETC. ARE SHOWN FOR LOCATION COORDINATION PURPOSES ONLY. REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR SPECIFICATIONS.
- ALL LIGHT FIXTURES, DIFFUSERS, ETC. TO BE CENTERED ON GYPSUM BOARD CEILING UNLESS OTHERWISE INDICATED.
- ALL GYPSUM BOARD CEILINGS AND BULKHEADS TO RECEIVE PAINT FINISH UNLESS OTHERWISE NOTED.
- ALL CEILING HEIGHT ELEVATIONS ARE RELATIVE TO THE FLOOR BELOW UNLESS OTHERWISE NOTED.
- CONFIRM HEIGHTS OF ALL SUSPENDED FIXTURES WITH ARCHITECT.

CEILING ABBREVIATIONS:

ACS	ACOUSTICAL CEILING SYSTEM (SEE 09 51 00 FOR ACS TYPES)
CJ	CONTROL JOINT
ES - P	EXPOSED STRUCTURE - PAINT FINISH
ES - U	EXPOSED STRUCTURE - UNFINISHED
GB - BH	GYPSUM BOARD BULKHEAD - PAINT FINISH 16 mm GYPSUM BOARD STEEL STUD FRAMING AS INDICATED (REFER TO INTERIOR SECTIONS)
GB - EP	GYPSUM BOARD CEILING SYSTEM - EPOXY PAINT FINISH 16 mm GYPSUM BOARD 22 mm FURRING CHANNELS @ 400 mm O.C. 38 mm CARRYING CHANNELS @ 1200 mm O.C.
GB - P	GYPSUM BOARD CEILING SYSTEM - PAINT FINISH 16 mm GYPSUM BOARD 22 mm FURRING CHANNELS @ 400 mm O.C. 38 mm CARRYING CHANNELS @ 1200 mm O.C.
LWCS	LINEAR WOOD CEILING SYSTEM (SEE 09 54 26 FOR CONSTRUCTION)
WSP	WEATHERING STEEL PANEL
WVPW	WOOD VENEER PANEL REFER TO SECTION DETAILS AP3 - AP8.5

REFLECTED CEILING PLAN LEGEND:

REFER TO MECHANICAL AND ELECTRICAL	
	RECESSED OR SURFACE MOUNTED LIGHT FIXTURE
	SUSPENDED LINEAR LIGHT FIXTURE
	LINEAR RECESSED SOFFIT FIXTURE
	PENDANT LIGHT FIXTURE - US OF FIXTURE @ 3350 A.F.F.
	RECESSED DOWNLIGHT
	WALL MOUNTED LIGHT FIXTURE
	UPLIGHTING MOUNTED TO BOTTOM MEMBER OF STRUCTURAL TRUSS
	SUSPENDED ACOUSTIC PANEL CW LIGHT - US OF FIXTURE @ 3000 A.F.F.
	SUSPENDED ACOUSTIC PANEL CW LIGHT - US OF FIXTURE @ 3350 A.F.F.
	SUSPENDED ACOUSTIC PANEL CW LIGHT - US OF FIXTURE @ 3960 A.F.F.
	SUPPLY AIR DIFFUSER
	RETURN AIR / EXHAUST GRILLE
	RADIANT PANELS
	ACTIVE CHILLED BEAM
	CARBON MONOXIDE DETECTOR - SURFACE MOUNTED
	EXIT SIGN
	EMERGENCY LIGHT - SURFACE MOUNTED
	EMERGENCY LIGHT - CEILING MOUNTED
	EMERGENCY BATTERY BANK UNIT
	CEILING ACCESS PANEL

DRAWING REFERENCE NOTES:

	REFERENCE NOTE TAG DESCRIPTION
3.01	WOOD SOFFIT TO CONSIST OF STAGGERED ROWS OF RANDOMLY ALTERNATING 38 x 89 mm, 38 x 140 mm, AND 38 x 184 mm FRAMING.
3.02	RECESSED LINEAR STRIP LIGHT, REFER TO ELECTRICAL.
3.03	CONTINUOUS PREFINISHED PERFORATED STEEL SOFFIT VENT.
3.04	WEATHERING STEEL CANOPY.
3.05	WEATHERING STEEL HEADER & TRIM.
3.06	CUSTOM SUSPENDED LIGHT FIXTURE WITH STAGGERED BULBS - FIXTURE STRUCTURAL GRID TO BE MOUNTED AT 4270 A.F.F., REFER TO ELECT.
3.07	SUSPENDED ACOUSTIC BAFFLES. TOP OF BAFFLE TO BE MOUNTED AT 3800 A.F.F. (300 mm O.C.). SUSPENDED LINEAR LIGHT FIXTURES BETWEEN BAFFLES AS INDICATED.
3.08	DASHED LINE INDICATES MILLWORK BELOW CEILING.
3.09	ALIGN ACTIVE CHILLED BEAM WITH EDGE OF ACCESS PANEL (TYPICAL ALONG GRIDLINE 1, BETWEEN GRIDLINE G THRU M).

No.	Date	Issue / Revision	By
5	July 08, 2019	Issued for Construction	HW
3	May 13, 2019	Issued for Pre-Tender Review	HW
2	Feb. 22, 2019	Design Development Submission	CG
1	Dec. 17, 2018	Schematic Design Review	CG

Drawn By: HW
Printing Date: 07.08.19



500-136 Market Ave
Winnipeg, Manitoba
Canada R3B 0P4
t: (204) 943.8676
f: (204) 943.8676
www.lm-architects.com

Drawings and specifications, as instruments of service are the property of the architects. The copyright in the same being reserved to them. No reproduction may be made without the permission of the architects, and when made, must bear their names. All prints to be returned.
The contractor is to verify dimensions and data noted herein with conditions on the site and is held responsible for reporting any discrepancy to the architects for adjustment.

Bill and Helen Norrie Library
Project No.: 2017-082
Tender No.: 542-2019
Address: 15 Poseidon Bay, Winnipeg, MB.

Reflected Ceiling Plan