



Fleet Management
Gestion des véhicules

TENDER 738-2020

OFFER OF SURPLUS GOODS

FIRE RESCUE BOAT

APPENDIX A

2008 Harbor Guard Firehawk 24' Fire rescue Boat

General Specifications:

Overall Length	Approx. 24'
Length of hull	22'
Beam	95"
Overall Height (without bridge)	8' 5"
Draft with engines	19"
Approx. Dry Weight	5500 lbs.
Load Capacity (gross weight)	4500 lbs.
Towing; Capacity	10,000 lbs.
Fuel Capacity	100 gallons
Seating	5

Engines:

- Twin Mercury Verado Outboard V6 Gas Engines
- 225 HP/Each (4-stroke)
- Approx. 705 hours each
- 1250 GPM midship Hale pump system

Technical

- Marine Grade Electrical Harness
- 12 Volt System circuit fuse protection, circuit breakers
- 3 Way Main Power Control (battery) Switch
- Marine Grade 316 Stainless Hardware
- Heavy Duty Electric and Mechanical Bilge System
- 1 set of Mercury Gauges/engine,
- Illuminated labeled rocker switches, waterproof
- Cabled Steering
- 100 Gallon Aluminum - baffled Fuel Tank w/ Gauge

- 3 Marine Batteries

Hull and Deck

- Progressive Deep V-Hull
- Full closed cell injected flotation foam with Secondary Impact Wall
- Self Bailing Deck
- Self Contained Operators Helm for Vessel Operation w/ storage compartment
- Water Tight built-in Storage Compartments
- 8' Port and Starboard electrically controlled side platform dive doors (with built-in flotation)
- Non skid flooring entire deck and dive doors
- (2) Back board storage along inner dive door
- White Gelcoat Hull and Deck
- Upholstery- Heavy duty marine grade custom vinyl (Red)
- (3) backboard retainment areas (1 in bow, 2 in stern)
- Bow seat/ backboard support with cushion

Equipment:

- Navigation Lights
- 1000 watt power inverter
- Plexiglass Windshield with grab rail
- Tubular Polished Anodized AL gunwale hand rails and fiberglass hard top canopy with overhead helm light
- Whelen Light Bar 28" with Whelen 100w low profile Siren/Hailer/PA System
- (2) Remote controlled- spot lights-mounted port and starboard - separate remote-controlled joy sticks
- Bow mounted Deck Monitor: Elkhart Stinger
- Elkhart Quad Stack Tip w/ flow straightener

- Foam system - Elkhart Foam Educator / Nozzle rated for 500 GPM Foam System (Pick-ups, SS Ball Valve, 50 Gal. Tank and foam level gauge)
- Bow 2.5" NFT Water Discharge System, (2) Separate Connections for 2.5" supply lines
- Canvas Helm Encloser
- Full Boat Cover – 2-piece snap on
- Tandem Axle, Galvanized Trailer
- Illuminated Compass
- Tow Post
- Hand Held Spot Light mounted
- Najo Floatable backboard
- Mounted Shakespeare VHF Antenna, cable routed to radio mount area
- Shore Power Connection w/ onboard battery charger
- Garmin 3210c GPS/Sounder/Depth Finder, sonar module and sensor pack







