



Fleet Management
Gestion des véhicules

TENDER 768-2020

OFFER OF SURPLUS GOODS

ASPHALT PAVER

APPENDIX A

2009 LeeBoy 5000 Asphalt Paver

Specifications:

- Approx. 451 hours
- Dimensions 12'10"L x 5'6"W x 7'4"H
- Engine: HATZ diesel 37HP air cooled, Tier III
- Fuel capacity 13 gallons.
- Hopper: dual 18" feeding conveyors
- Paving width 5' to 9'
- Paving depth 0" to 6"
- Screed full floating 22" with 15" x 5" main screen.
- Screed extensions two (2) 24" hydraulic extensions
- Screed heat approx. 50,000 BTU propane burners, 35,000 BTU each screed extension
- Screed vibrator 3000 rpm
- Screed crown: crown/invert adjustable 1.5" each way with level indicator
- Material flow gates hydraulically operated located under the augers.
- Operator controls on both lefty and right side of paver
- Movable steering box to left or right side
- Wash down: electronic pump with (1) 15' X 5/16" diameter hose with hose reel
- Hydraulic reservoir ~30 gallons
- Drive system: hydrostatically powered, self cleaning tracks
- Push Rollers: two (2) 3" rollers with sealed bearing
- **NOTE: Trailer Not Included**



