



10-2021 ADDENDUM 1

2021 LOCAL STREET/ALLEY RENEWAL PROGRAM: KINGSTON ROW,
REGIS DR & OTHER LOCATIONS

ISSUED: January 26, 2021
BY: Blair Cockrell
TELEPHONE NO. 204 928-8431

URGENT

**PLEASE FORWARD THIS DOCUMENT TO
WHOEVER IS IN POSSESSION OF THE
BID/PROPOSAL**

**THIS ADDENDUM SHALL BE INCORPORATED
INTO THE BID/PROPOSAL AND SHALL FORM
A PART OF THE CONTRACT DOCUMENTS**

Template Version: A20160708

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid/Proposal, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid/Proposal may render your Bid/Proposal non-responsive.

PART A – BID/PROPOSAL SUBMISSION

Replace: 10-2021 Form B- Prices with 10-2021 Addendum 1 - Form B- Prices. The following is a summary of changes incorporated in the replacement Form B-Prices:

Form B(R1): Revise Items A3 i), A3 ii), A4 i) and A6 i).

Delete item A4 ii).

PART B – BIDDING PROCEDURES

Delete: B17.4.3.

Delete: B17.4.5.

PART E – SPECIFICATIONS

Revise: E12.1.1 to read: This specification covers the bidding instructions for 100mm Limestone A Sub-Base Materials, Recycled Concrete, and 100mm Granular B Interim.

Delete: E12.2.2.

Revise: E13 as follows: E13. 100MM GRANULAR B INTERIM RECYCLED CONCRETE

DESCRIPTION

E13.1 General

E13.1.1 Further to CW-3110 100mm Granular B Interim Recycled Concrete is a well-graded recycled aggregate intended for use as a sub-base within the pavement structure.

E13.1.2 100mm Granular B Interim Recycled Concrete material shall have the following properties:

Tests	Testing Method	Interim Granular B	
		50 mm	100 mm
Los Angeles Abrasion, % maximum	ASTM C535 (Grading 1)	--	35
Los Angeles Abrasion, % maximum	ASTM C131 (Grading A)	35	--
California Bearing Ratio (CBR) – 4 days soaked, % minimum @ 2.54 mm	ASTM D1883	50	--
Micro-Deval Abrasion, % maximum	ASTM D6928	20	20
Percentage of Fractured Particles, minimum two or more fractured faces, % mass	ASTM D5821	70	60
Atterberg Limits* Liquid Limit, % maximum	ASTM D4813	22	25
Plasticity Index, % maximum		4	6
Content Composition, maximum	Mass %	10% asphalt material 3% clay 3% deleterious material	

*Atterberg Limits shall not be a basis for rejection of Granular B Interim.

MEASUREMENT

E13.2 100mm Granular B Interim Recycled Concrete shall be measured on a weight basis and paid for at the Contract Unit Price per tonne for “100 mm Granular B Interim Recycled Concrete”. The weight to be paid for shall be the total square meters of sub-base 100 mm Granular B Interim Recycled Concrete supplied and placed in accordance with this specification, accepted and measured by the Contract Administrator.

DRAWINGS

Replace: 10-2021 _Drawing_CT32-R0 with 10-2021 _Addendum_1 Drawing CT32-R1

10-2021 _Drawing_CT33-R0 with 10-2021 _Addendum_1 Drawing CT33-R1