

## 146-2021 ADDENDUM 2

## SUPPLY AND DELIVERY OF LIMESTONE

**URGENT** 

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID/PROPOSAL

ISSUED: April 7, 2021 BY: Jean-Luc Lambert TELEPHONE NO. 204 986-7087

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID/PROPOSAL AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid/Proposal, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid/Proposal may render your Bid/Proposal non-responsive.

## **FORM B: PRICES**

Replace: 146-2021 Form B: Prices with 146-2021 Addendum 2 - Form B: Prices. The following is a summary of changes

incorporated in the replacement Bid/Proposal Submission:

Form B(R1): changes to Items No. 17 and 33 specification reference.

Page numbering on some forms may be changed as a result.

## PART E - SPECIFICATIONS

Revise: E2.1 to read: Item No. 1,5, 9, 13, 37, 38 45, 46 and 47 - "Limestone Clean" shall be in accordance with

gradation and physical properties requirements listed in the table below.

| Canadian<br>Metric Sieve              | Percent of Total Dry Weight Passing Each Sieve |                  |                  |                  |  |
|---------------------------------------|--|------------------|------------------|------------------|--|
| Size                                  | 10 mm  | 20 mm            | 50 mm            | 100 mm           |  |
| 200 000                               |  |                  |                  |                  |  |
| 150 000                               |  |                  |                  |                  |  |
| 125 000                               |  |                  |                  | 100%             |  |
| 100 000                               |  |                  | 100%             | 90% - 100%       |  |
| 50 000                                |  |                  | 90% - 100%       |                  |  |
| 25 000                                |  | 100%             |                  | 0% - 5%          |  |
| 20 000                                |  | 90% - 100%       | 0% - 5%          |                  |  |
| 12 500                                | 100%   |                  |                  |                  |  |
| 10 000                                | 75% - 100%                                     |                  |                  |                  |  |
| 5 000                                 | 0% - 40%                                       | 0% - 5%          |                  |                  |  |
| 2 500                                 | 0% - 25%                                       |                  |                  |                  |  |
| 1 250                                 |  |                  |                  |                  |  |
| 425                                   | 0% - 10%                                       |                  |                  |                  |  |
| 315                                   |  |                  |                  |                  |  |
| 80                                    | 0% - 5%  | 0% - 5%          | 0% - 5%          | 0% - 5%          |  |
| Los Angeles<br>Abrasion,<br>% maximum |  | 35%<br>ASTM C131 | 35%<br>ASTM C131 | 35%<br>ASTM C535 |  |

Revise: E2.2 to read:

Item No. 21, 25, 29, 39, 40, 42, 43, 44 - "Limestone Down" shall be in accordance with CW 3110 Granular C Gradation Requirements and Physical Properties.

Add: E2.3

Item No. 17 and 33 - "Limestone Clean" shall be in accordance with gradation and physical properties requirements listed in the table below.

| Canadian                              | Percent of Total Dry Weight Passing Each Sieve |                  |  |  |  |
|---------------------------------------|--|------------------|--|--|--|
| Metric Sieve<br>Size                  | 8 mm   | 150 mm           |  |  |  |
| 200 000                               |  | 100%             |  |  |  |
| 150 000                               |  | 90% - 100%       |  |  |  |
| 125 000                               |  |                  |  |  |  |
| 100 000                               |  | 65% - 85%        |  |  |  |
| 50 000                                |  | 30% - 70%        |  |  |  |
| 25 000                                |  | 10% - 40%        |  |  |  |
| 20 000                                |  |                  |  |  |  |
| 12 500                                | 100%   |                  |  |  |  |
| 10 000                                | 95% - 100%                                     |                  |  |  |  |
| 5 000                                 | 70% - 95%                                      | 4% - 20%         |  |  |  |
| 2 500                                 | 40% - 75%                                      |                  |  |  |  |
| 1 250                                 |  |                  |  |  |  |
| 630                                   | 15% - 40%                                      |                  |  |  |  |
| 315                                   |  |                  |  |  |  |
| 80                                    | 8% - 20%                                       | 0% - 10%         |  |  |  |
| Los Angeles<br>Abrasion,<br>% maximum |  | 35%<br>ASTM C131 |  |  |  |