

276-2021 ADDENDUM 1

KEEWATIN UNDERPASS PUMPING STATION - 2021 UPGRADES

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE TENDER

ISSUED: 2021-06-02 BY: Brian Cleven TELEPHONE NO. 204 786-8080

THIS ADDENDUM SHALL BE INCORPORATED INTO THE TENDER AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Tender, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid may render your Bid non-responsive.

PART E - SPECIFICATIONS

Revise: E19.2.5 to read: Provide **Schedule 40 PVC** drainage piping system from pump seal water leakage

connections and backflow preventer drain to the wet well as shown on the drawings.

DRAWINGS

Replace: 276-2021 Drawing 1-0304U-E0004-001-00 with 276-2021 Addendum 1 Drawing 1-0304U-E0004-001-0A

Replace: 276-2021_Drawing_1-0304U-E0009-001-00 with 276-2021_Addendum_1_Drawing_1-0304U-E0009-001-0A

NMS SPECIFICATIONS

Revise: 07 61 00 clause 2.2.1 to read: Self-adhesive, modified bitumen sheet, minimum 1 mm (40 mils) thick,

non-slip surface. Acceptable material: IKO Armour Gard Ice and Water Protector, W.R. Grace Ice and Water Shield; Domtar Eaveshield; Nordshield Water Stopper; Bakor/Henry Eave Guard; BPCO ProGard; EMCO Gripgard, Bakor/Henry WP200, WR Meadows Mel-Rol, or

approved equal in accordance with B7.

Revise: 23 33 15 clause 2.1.11 to read: Acceptable materials: Tamco 9000SC, **Alumavent**, or approved equal in

accordance with B7.

Revise: 23 33 15 clause 2.2.11 to read: Acceptable materials: Tamco 1000, **Alumavent**, or approved equal in

accordance with B7.

Revise: 23 41 00 clause 2.3.6 to read: Acceptable material: Camfil Farr 30/30, AAF/Flanders, or approved

equal in accordance with B7.

Revise: 26 28 21 clause 2.5.1.2 to read: Sensor Rating: 250A

Revise: 26 28 21 clause 2.5.1.3 to read: Trip Unit Type: Electronic LSI, Factory Sealed

Tender No. 276-2021 Addendum 1 Page 2 of 2

Revise: 26 28 21 clause 2.5.1.4 to read: Long Time PU: **70A - 250A** Revise: 26 28 21 clause 2.5.1.5 to read: Long Time Delay: Non-Adjustable 26 28 21 clause 2.5.1.6 to read: Revise: Short Time PU: 1.5 - 10 x Sensor Rating Revise: 26 28 21 clause 2.5.1.7 to read: Short Time Delay: Non-Adjustable Revise: 26 28 21 clause 2.5.1.8 to read: Instantaneous: 1.5 - 12

26 28 21 clause 2.5.1.10 to read: Revise: Model: Schneider Electric PowerPact J series with Micrologic 3.25 series

trip unit, or approved equal in accordance with B7.

26 32 10 clause 2.2.A to read: The engine shall be a stationary, liquid cooled, 150 kW, 60 Hz, 1,800 Revise:

rpm, four-cycle design, vertical inline or V-type, with dry exhaust manifolds. It shall have minimum six (6) cylinders with minimum total displacement of 8.8 liters and be manufactured in the United States or

Canada.

26 32 10 clause 2.2.O to read: Acceptable manufacturers: Revise:

1. Generac,

2. Caterpillar (CAT),

3. Or approved equal in accordance with B7.

Revise: 33 41 01 clause 2.1.15.9 to read: Motors shall be capable of six (6) starts per hour on a continuous basis

without temperature rise that could damage the motor.

Add: Efficiency: Premium. 33 41 01 clause 2.1.15.12:

Delete: 33 41 01 clause 2.1.17.2.1

Delete: 33 41 01 clause 2.1.17.2.2

33 41 01 clause 2.1.17.2.5 Delete: