

### **STANDARD LIMITATIONS**

This report was prepared by MMM Group Limited (MMM) for the account of the City of Winnipeg – Water and Waste Department (the Client). The disclosure of any information contained in this report is the sole responsibility of the Client. The material in this report reflects MMM's best judgment in light of the information available to it at the time of preparation. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. MMM accepts no responsibility for damages, if any, suffered by a third party as a result of decisions made or actions based on this report.

(This page was intentionally left blank)

**COVER PAGE**

**INDEX**

**1.0 LIFT STATION INFORMATION ..... 1**

**2.0 OBSERVATIONS ..... 3**

2.1 General..... 3

2.2 Lifting Devices ..... 3

**ANALYSIS AND LOAD RATING ..... 4**

**CONCLUSIONS AND RECOMMENDATIONS ..... 5**

**APPENDIX A – Photographs**

(This page was intentionally left blank)

## 1.0 LIFT STATION INFORMATION

<b>Station Name:</b>	<u>Conway Lift Station</u>
<b>Location of Station:</b>	<u>2206 Portage Avenue (at Conway Street)</u>
<b>Date of Inspection:</b>	<u>February 19, 2010</u>
<b>Inspected By:</b>	<u>Damir Muhurdarevic, EIT</u>
<b>Inspecting Firm:</b>	<u>MMM Group Limited (MMM)</u>
<b>Client:</b>	<u>City of Winnipeg – Water and Waste Department</u>

(This page was intentionally left blank)

## **2.0 OBSERVATIONS**

### **2.1 General**

Conway Lift Station is a conventional lift station with a main floor at ground level and four (4) floors below ground level. The lift station is constructed of cast-in-place concrete below ground level and masonry and wood framing above ground level. The main floor contains typical lift station components and controls, the first and second floors below grade are a combined chamber room, the third floor below ground level is a motor room containing the pump motors, and the fourth floor below ground level is a pump room containing wastewater/land drainage pumps. The condition and operation of the pumps and motors was not observed.

### **2.2 Lifting Devices**

The main floor has a steel wide flange lifting beam (175mm high by 93mm wide) that spans the entire length of the room and has an attached sliding hook. There is no posted rating on the beam and wall connections were unable to be observed due to Styrofoam wall insulation.

The motor room has one (1) U-shaped hook, fabricated of 19.4mm diameter steel rod and embedded into the cast-in-place concrete floor above.

The pump room has three (3) eye-shaped hooks, fabricated of 19.4mm diameter steel rod embedded into the cast-in-place concrete floor above.

## ANALYSIS AND LOAD RATING

The W-beam on the main floor was analyzed for bending resistance of the beam and the shear resistance of an assumed bolted connection. The assumed shear resistance was found to be the governing factor which was calculated to be 3.0 tons. This resistance was reduced by a safety factor of 3.0, due to the wall connection assumptions, to yield a **load rating of 1.0 ton**.

The analysis of the U-shaped hook determined a resistance 6.8 tons. However, due to many assumptions, it is recommended that an additional factor of safety of 4.5 be applied to the hooks, to yield a **load rating of 1.5 tons**.

The three (3) eye-shaped hooks were analyzed for pullout resistance of the concrete embedment and the tension resistance of the hook. A concrete thickness of 200mm and an embedment length of 150mm were used. The governing factor was the pullout resistance, which was calculated to be 3.4 tons. However, it is recommended that an additional factor of safety of 3.4 be applied to the hooks, to yield a **load rating of 1.0 tons**.

Table 3.1 below is a summary table of lifting device load ratings:

*Table 3.1 Load Rating Summary*

Type	Quantity	Location	Calculated Resistance	Safety Factor	Load Rating
Main Floor Lifting Beam	1	Main Floor	3.0 tons	3.0	<b>1.0 ton</b>
U-Shaped Hook	1	Underside of Second Cast-In-Place Concrete Floor	6.8 tons	4.5	<b>1.5 ton</b>
Eye-Shaped Lifting Hooks	3	Underside of Cast-In-Place Concrete Floors	3.4 tons	3.4	<b>1.0 ton</b>



## CONCLUSIONS AND RECOMMENDATIONS

MMM, through this inspection, does not warrant the lifting devices installation or warrant that the design complies with current codes or standards. As per MMM's analysis it was found that the eye-shaped hooks should be rated at 1.0 tons, and the U-shaped hook at 1.5 tons. The main floor W-Beam is rated at 1.0 tons.

This lift station inspection is limited to a visual inspection lifting members and connections. The inspection pertains to surface material condition only.

Prepared by:

**MMM Group Limited**

Damir Muhurdarevic, EIT  
Inspector

Reviewed by:

**MMM Group Limited**

Jim Lukashenko, P.Eng.  
Manager, Structures  
Associate

(This page was intentionally left blank)







**Photograph No. 1**

Typical pump room eye-shaped hooks



**Photograph No. 2**

Motor room U-shaped hook



**Photograph No. 3**

Main floor lifting beam with sliding hook



**Photograph No. 4**

Main floor lifting beam