


CONCRETE NOTES:

REINFORCING STEEL SHALL CONFORM TO CAN/CSA - G-30.18
GRADE 400W

CONCRETE MATERIALS & PLACEMENT SHALL CONFORM TO CAN /CSA - A23.1-04
EXPOSURE CLASS C-1
35 MPa AT 28 DAYS, CEMENT TYPE GU
MAXIMUM WATER /CEMENT RATIO 0.40
5-8% AIR ENTRAINMENT

PROVIDE 1/2" WIDE CONTROL JOINT FITTED W/ 1/2" FLEXCELL BOARD BETWEEN
ALL ADJACENT SLABS AND AT CONSTRUCTION JOINTS. UPON CURE OF
CONCRETE, CAULK ALL JOINTS W/ BASF/SONNEBORN SL-1 (LIMESTONE
COLOUR) PER MANUFACTURER'S SPECIFICATIONS.



 CITY OF WINNIPEG PLANNING, PROPERTY AND DEVELOPMENT DEPARTMENT CIVIC ACCOMMODATIONS DIVISION 300-65 GARRY STREET R3C 4K4		PROJECT BROOKSIDE CEMETERY MONUMENT SUPPORT BEAMS 3001 NOTRE DAME AVENUE		SHEET TITLE TYPICAL SLAB PLAN VIEW & CONCRETE NOTES	
DRAWN BY JAW/EAG	CHECKED BY BDN	APPROVED BY BDN	DATE 2020.07.27 eFILE 2020040SV0.dwg	SCALE AS SHOWN	SHEET NO. DS1
			PROJECT NO. 2020-040		