LIGHTING AND CONTROLS

- D1 a / A,1 — LIGHTING FIXTURE TYPE "D1" CONTROLLED BY SWITCH "a" FED BY BREAKER #1 OF PANEL "A"
- 24H LIGHTING FIXTURE
- WALL MOUNTED LIGHTING FIXTURE
- RECESSED CEILING LIGHTING FIXTURE
- WALL MOUNTED ROUND LIGHTING FIXTURE
- PENDANT/SURFACE LIGHTING FIXTURE
- STREET LAMP AND POST FOR OUTDOOR LIGHTING (1 HEAD)
- STREET LAMP AND POST FOR OUTDOOR LIGHTING (2 HEADS)
- $ — SINGLE POLE SWITCH 15A, 125V
- $3 — 3-WAY SWITCH 15A, 125V
- $4 — 4-WAY SWITCH 15A, 125V
- $ — SINGLE POLE SWITCH 15A, 347V
- Ø — SINGLE POLE DIMMER 15A, 125V
- Ø3 — 3-WAY DIMMER 15A, 125V
- Ø0-10V — DIMMER 0-10V
- SINGLE POLE SWITCH WITH INDICATOR LIGHT
- DOOR SWITCH
- SINGLE POLE KEY SWITCH
- P — PHOTOCELL
- P 2 — TYPE 2 WALLMOUNTED MOTION DETECTOR
- P 1 — TYPE 1 MOTION DETECTOR
- L — LIGHT LEVEL DETECTOR

EMERGENCY

- "A" U,1 — EMERGENCY EXIT LIGHT, FED BY BREAKER #1 FROM "U" PANEL AND BATTERY "A". SHADED AREA INDICATES LIGHTED FACES, WITH OR WITHOUT ARROWS.
- "A" U,1 — EMERGENCY EXIT LIGHT WALLMOUNTED, FED BY BATTERY "A" AND BREAKER #1 OF "U" PANEL. SHADED AREA INDICATES LIGHTED FACES, WITH OR WITHOUT ARROWS.
- "A" U,1 — EMERGENCY EXIT DOUBLE FACES LIGHT WALLMOUNTED, FED BY BATTERY "A" AND BREAKER #1 OF "U" PANEL. SHADED AREA INDICATES LIGHTED FACES, WITH OR WITHOUT ARROWS.
- "A" "A" U,1 — EMERGENCY EXIT LIGHT WALLMOUNTED WITH EMERGENCY LIGHTS, FED BY BATTERY "A" AND BREAKER #1 OF "U" PANEL. SHADED AREA INDICATES LIGHTED FACES, WITH OR WITHOUT ARROWS.
- "A" — BATTERY C/W MOUNTING ACCESSORIES FED BY A 15A OUTLET AND A DEDICATED BREAKER.
- "A" — BATTERY WITH EMERGENCY EXIT LIGHT C/W MOUNTING ACCESSORIES FED BY A 15A OUTLET AND A DEDICATED BREAKER.
- "A" — BATTERY WITH EMERGENCY LIGHTS C/W MOUNTING ACCESSORIES FED BY A 15A OUTLET AND A DEDICATED BREAKER.
- "A" — BATTERY WITH EMERGENCY LIGHTS C/W MOUNTING ACCESSORIES FED BY A 15A OUTLET AND A DEDICATED BREAKER.
- "A" — SINGLE HEADLIGHT FOR EMERGENCY LIGHTING CONNECTED TO ACCUMULATOR "A"
- "A" — DOUBLE HEADLIGHT FOR EMERGENCY LIGHTING CONNECTED TO ACCUMULATOR "A"

MECHANICAL EQUIPMENT

- SINGLE PHASE MOTOR PROVIDED BY MECHANICAL (TO BE CONNECTED)
- THREE PHASES MOTOR PROVIDED BY MECHANICAL (TO BE CONNECTED)
- H — KITCHEN HOOD PROVIDED BY MECHANICAL (TO BE CONNECTED)
- VS — DRYER DUCT EXHAUST FAN PROVIDED BY MECHANICAL (TO BE CONNECTED)
- C E — ELECTRIC WATER HEATER PROVDED BY MECHANICAL (TO BE CONNECTED)

FIRE ALARM

- 120V SMOKE DETECTOR C/W EMERGENCY BATTERY (INTER-CONNECTED WITH OTHERS IN THE UNITS)
- CO — 120V SMOKE DETECTOR C/W EMERGENCY BATTERY (INTER-CONNECTED WITH OTHERS IN THE UNITS) AND CO2 DETECTOR FOR THE APARTMENTS DIRECTLY ABOVE A PARKING LOT, ALL WITH FIREPLACE AND/OR GAS STOVE AND IN THE ADJACENT.
- SMOKE DETECTOR
- T — THERMAL DETECTOR
- SMOKE DETECTOR C/W SAMPLE TUBE INSTALLED IN VENTILATION DUCT
- SMOKE DETECTOR FOR FIRE AND SMOKE DAMPER
- F — MANUAL PULL STATION
- F — FIRE ALARM HORN
- F — FIRE ALARM HORN C/W STROBE 15 cd MIN.
- ROOM FIRE ALARM HORN C/W STROBE 110cd MIN.
- PZ — PIEZO ELECTRIC MINI HORN
- RM — HOLDER MAGNET
- END OF LINE RESISTANCE
- PAI — MAIN FIRE ALARM PANEL
- ANN — FIRE ALARM ANNUNCIATOR PANEL
- CO — CARBON MONOXYDE DETECTOR
- ISO — ADRESSABLE LOOP ISOLATION MODULE
- RA — FIRE ALARM ADRESSABLE RELAY
- MS — FIRE ALARM SINGLE ADRESSABLE TRANSMISSION MODULE
- MD — FIRE ALARM DOUBLE ADRESSABLE TRANSMISSION MODULE
- M10 — FIRE ALARM 10 INPUTS ADRESSABLE TRANSMISSION MODULE
- ID — FLOW SWITCH BY FIRE PROTECTION AND CONNECTED TO FIRE ALARM.
- IP — PRESSURE SWITCH BY FIRE PROTECTION AND CONNECTED TO FIRE ALARM
- IS — VALVE SWITCH BY BY FIRE PROTECTION AND CONNECTED TO FIRE ALARM
- FIRE DEPARTEMENT PHONE OUTLET

COMMUNICATION

- ANALOGUE TELEPHONE OUTLET WITH PULL CORD
- ANALOGUE TELEPHONE OUTLET 1070mm (42") FROM THE FLOOR
- DATA OUTLET
- DATA OUTLET 1070mm (42") FROM THE FLOOR
- TELEPHONE/DATA COMBINED OUTLET
- TELEPHONE/DATA COMBINED OUTLET 1070mm (42") FROM THE FLOOR
- 1T-2D — TELEPHONE/DATA COMBINED OUTLET (1 TELEPHONE/2 DATA)
- BP200 — BOX PROVIDED BY THE SUPPLIER IN COMMUNICATION INSTALLED BY COMMUNICATION DISCIPLINE
- TV — TELEVISION OUTLET
- WF — WIRELESS ROUTER (WIFI)
- INTERCOM MASTER STATION C/W CALL BOUTON AND MICROPHONE

RECEPTACLES AND SERVICES

- DUPLEX CONVENIENCE RECEPTACLE 15A 125V
- DUPLEX RECEPTACLE 5-15R, 125V 1070mm (42") FROM THE FLOOR
- DUPLEX RECEPTACLE 5-20R, 125V
- DUPLEX RECEPTACLE 5-20R, 125V 1070mm (42") FROM THE FLOOR
- G.F.I. DUPLEX RECEPTACLE 5-15R, 125V
- G.F.I. DUPLEX RECEPTACLE 5-20R, 125V 1070mm (42") FROM THE FLOOR
- G.F.I. DUPLEX RECEPTACLE 5-15R, 125V 1070mm (42") FROM THE FLOOR
- DUPLEX RECEPTACLE 5-15R, 125V ON EMERGENCY CIRCUIT
- DUPLEX RECEPTACLE 5-15R, 125V 1070mm (42") FROM THE FLOOR
- DUPLEX RECEPTACLE 5-20R, 125V ON EMERGENCY CIRCUIT
- DUPLEX RECEPTACLE 5-20R, 125V ON EMERGENCY CIRCUIT 1070mm (42") FROM THE FLOOR
- DUPLEX RECEPTACLE 5-15R, 125V C/W USB CHARGER
- DUPLEX RECEPTACLE 5-15R, 125V C/W USB CHARGER 1070mm (42") FROM THE FLOOR
- C — DUPLEX RECEPTACLES 5-15R, 125V IN CEILING
- L — RECEPTACLE FOR WASHING MACHINE 5-15R, 125V
- S — RECEPTACLE FOR DRYER 14-30R, 250V
- RECEPTACLE FOR OVEN, 14-50A, 250V
- SINGLE PHASE RECEPTACLE, 6-15A, 250V OR AMP. SPECIFIED ON DRAWING
- SINGLE PHASE RECEPTACLE, 6-15A, 347V OR AMP. SPECIFIED ON DRAWING
- SINGLE PHASE RECEPTACLE, 6-20A, 347V OR AMP. SPECIFIED ON DRAWING
- THREE PHASES RECEPTACLE, 14-15A, 125/250V OR AMP. SPECIFIED ON DRAWING
- THREE PHASES RECEPTACLE, 15-15A, 250V OR AMP. SPECIFIED ON PLAN
- DUPLEX RECEPTACLE 5-15R, 125V, FLOOR MOUNTED
- FLOOR MONUMENT WITH A 15A 125V RECEPTACLE WITH A COMBINED PHONE/DATA OUTLET
- BR — DOUBLE CHARGING STATION FROM FLO MODEL C+ V2-EVSE-30-25-LC1-RR1-NSL-FL-NRRV-ST / C+ V1-PED-RV-GRRV
- S — HAND DRYER DYSON AIRBLADE V

DISTRIBUTION

- 30A — 30A SAFETY SWITCH WITHOUT FUSE
- 30A F:15A — 30A SAFETY SWITCH WITH 15A FUSE
- 30A — 30A SAFETY SWITCH WITH AUXILIARY CONTACT
- MANUAL STARTER
- MAGNETIC STARTER
- COMBINED MAGNETIC STARTER
- MAGNETIC CONTACTOR
- SERVICE PANEL 120/208V, 3PH, 4W, SURFACE MOUNTED
- SERVICE PANEL120/208V, 3PH, 4W, RECESSED MOUNTED
- SERVICE PANEL120/208V, 3PH, 4W, RECESSED MOUNTED
- SERVICE PANEL 120/240V, 1PH, 3W, RECESSED MOUNTED
- SERVICE PANEL 347/600V, 3PH, 4W, SURFACE MOUNTED
- SERVICE PANEL 347/600V, 3PH, 4W, RECESSED MOUNTED
- H — TRANSFERT SWITCH
- JUNCTION BOX
- GROUNDING BAR

HEATING

- T G — LINE VOLTAGE THERMOSTAT FROM STELPRO #STE403NPW24, 347V C/W LOCKABLE GUARD
- T — LOW VOLTAGE THERMOSTAT, BY AUTOMATIC REGULATION C/W LOCKABLE GUARD
- T — LOW VOLTAGE THERMOSTAT, BY AUTOMATIC REGULATION
- R — RELAY
- RT — ELECTRIC RELAY SUPPLIED, INSTALLED AND CONNECTED ON THE POWER SIDE BY THE ELECTRICITY AND CONNECTED ON THE CONTROL SIDE BY THE AUTOMATIC REGULATION.
- ELECTRIC BASEBOARD
- T — BASEBOARD HEATER C/W THERMOSTAT
- R — BASEBOARD HEATER C/W INTEGRATED RELAY
- RT — BASEBOARD HEATER C/W ELECTRONIC RELAY
- ARCHITECTURAL ELECTRIC BASEBOARD
- PATIO ELECTRIC BASEBOARD
- ELECTRIC HEATER
- RECESSED CONVECTOR
- CEILING OR WALL MOUNTED CONVECTOR

AUXILIARY SERVICES

- M — TIMER
- BELL OR CHIME ENTRANCE PUSH BUTTON
- B — PUSH BUTTON FOR PERSON WITH DISABILITY
- C — BELL OR CHIME ENTRANCE
- P — PRESENCE DETECTOR
- EA — DOOR MAGNET
- EXT — EXPANDER
- OP — DOOR OPERATOR

SECURITY

- C — CAMERA
- DOME TYPE CAMERA
- CP — DOOR CONTACT
- LC — ACCESS CARD
- G — ELECTRIC STRIKE
- REX — EXIT REQUEST DETECTOR
- CL — INTRUSION ALARM KEYPAD
- BYPASS KEY
- INTRUSION ALARM MOTION SENSOR
- PA — INTRUSION ALARM PANEL

ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE PROPERTY OF THE ARCHITECT. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN ANY FORMS IS STRICTLY FORBIDDEN WITHOUT THE WRITTEN PERMISSION OF THE ARCHITECT.

CLIENT :
CITY OF WINNIPEG

PROJECT :
MARKET LANDS SITE DEVELOPMENT

ARCHITECT :
DAOUST LESTAGE
architecture - design urbain - paysage
DAOUST LESTAGE
3575 St-Laurent Blvd #710, Montreal QC., H2X 2T7
info@daoustlestage.com
+1 514 982 0877
NUMBER TEN ARCHITECURAL GROUP
100 Bannatyne Ave. Winnipeg, MB, R3B 0R3
winnipeg@numberten.com
+1 204-942-0981

MECHANICAL CONSULTANT ENGINEERS :
TETRA TECH
3475 East Foothill Blvd, Pasadena CA, 91107-6024
info@tetratech.com
+1 626 351 4664

STRUCTURAL CONSULTANT :
ENTUITIVE
200 University Ave, 7th Floor, Toronto ON, M5H 3C6
entuitive.com
+1 416 477 5832

SUSTAINABILITY CONSULTANT :

CIVIL CONSULTANT :
WSP CANADA INC.
1600 Buffalo Place, Winnipeg, Manitoba, R3T 6B8
info@wsp.com
+1 204 259 1659

ELECTRICAL CONSULTANT ENGINEERS :
PONTON GUILLOT
Structure • Civil • Mécanique • Électricité
www.pontonguillot.com
Courriel : info@pontonguillot.com

SEAL :

NO.	DESCRIPTION	DATE
0	ISSUED FOR TENDER	2024-02-02

KEY PLAN :



DISCIPLINE : ELECTRIC

LOT :

TITLE : LEGEND

DRAWN BY : C.Gauthier	FILE : 38690TT
DEVELOPED BY : D.Ménard	SCALE : 1 : 1
APPROVED BY : N.Hurens	PAGE : E001.1
PRINT DATE : 2023-03-15	