



169-2024 ADDENDUM 3

SUPPLY AND DELIVERY OF LUBRICANTS

URGENT

PLEASE FORWARD THIS DOCUMENT TO WHOEVER IS IN POSSESSION OF THE BID/PROPOSAL

ISSUED: May 23, 2024
BY: Ekie Oseghale
TELEPHONE NO. 204 986-2451

THIS ADDENDUM SHALL BE INCORPORATED INTO THE BID/PROPOSAL AND SHALL FORM A PART OF THE CONTRACT DOCUMENTS

Template Version: Add 2024-02-01

Please note the following and attached changes, corrections, additions, deletions, information and/or instructions in connection with the Bid/Proposal, and be governed accordingly. Failure to acknowledge receipt of this Addendum in Paragraph 10 of Form A: Bid/Proposal may render your Bid/Proposal non-responsive.

FORM B: PRICES

Replace: 169-2024 Addendum 1-Form B: Prices with 169-2024 Addendum 3 - Form B: Prices. The following is a summary of changes incorporated in the replacement Bid/Proposal Submission:

Form B(R2): Add Items No. 89 to 90 inclusive.

Page numbering on some forms may be changed as a result.

PART E – SPECIFICATIONS

Revise: E2.21 to read: Item No. 70 to 83 and 89 to 90 – Grease – Multipurpose and Synthetic shall be:

Item No.		70. to 71.	72.	73.	74. to 77.	78.	79.	80.	81.	82. to 83.	89. to 90.
Description		Grease EP00 lithium complex	Grease EP000 lithium complex	Grease EP1 lithium complex	Grease EP2 lithium complex	Grease with Moly for Low Temperature Applications	Grease General Purpose EP2 lithium	Grease Synthetic lithium complex	Grease Non-EP Multi-Purpose	Grease Calcium Sulphonate Complex	Grease Synthetic 220
NLGI	Grade	00	000	1	2	1	2	1	2	2	2
	GC-LB	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆
Timken OK Load (D-2509)		18kg	18kg	27kg	27kg	18kg	18kg	27kg			
Dropping Point		191°C	189°C	291°C	302°C	185°C	198°C	292°C	>308°C	314°C	305°C
Molybdenum disulphide (% weight)					3 to 5%	3 to 5%					
Operating Range		-35 to 100°C	-25 to 100°C	-25 to 160°C	-20 to 160°C	-45 to 135°C	-25 to 135°C	-40 to 170°C	-40 to 170°C	-25 to 163°C	-35 to 170°C
Base Oil Viscosity cSt @ 40°C		117	325	220	220	34	162	130	114	73	220
cSt @ 100°C		13.6	23.8	17.9	17.9	6.1	15.3	15.6	15.6	9.4	23.5