







LEGEND				
⊕	HEAT DETECTOR (FIXED TEMP)			
F	MANUAL PULL STATION			
HΩ	FIRE ALARM SIGNAL HORN			
H)(i)	FIRE ALARM SIGNAL HORN & STROBE - WALL MOUNTED			
V (0)	FIRE ALARM STROBE — WALL MOUNTED			
ISO	ISOLATOR			
ММ	MONITORING MODULE			
EOL	END OF LINE RESISTOR			
	LINEAR HEAT CABLE (RISER SYMBOL)			
□/ □	SYSTEM PANELBOARD - SURFACE MOUNT/FLUSH MOUNT			
	LINEAR HEAT CABLE			
EX	EXISTING TO REMAIN			

SCOPE OF WORK

- A. EXISTING SPRINKLER SYSTEM TO BE DECOMMISSIONED FOR REPAIRS. HEAT DETECTION TO BE PROVIDED THROUGHOUT AS REQUIRED TO PROVIDE SUFFICIENT COVERAGE. SPACE WILL BE CONSIDERED UNHEATED AND UNSPRINKLERED WHILE SPRINKLER SYSTEM IS DOWN.
- B. PROVIDE LINEAR HEAT DETECTION OVER THE BACK OF STAGE AREA ATTACHED TO SPRINKLER PIPING AT HIGH
- C. PROVIDE LINER HEAT/ SPOT TYPE HEAT DETECTORS IN ALL STORAGE ROOMS/WAREHOUSE AREAS.

DRAWING NOTES:

- HEAT DETECTORS TO BE KIDDE FENWELL (CAT. #27021) TYPICAL.
- 2. LINEAR HEAT DETECTION TO BE SAFE CABLE LINEAR HEAT DETECTOR (CAT. #TC190) TYPICAL.
- 3. LINEAR HEAT CABLE TO BE MOUNTED TO SPRINKLER PIPING WITH MANUFACTURER APPROVED TIE STRAPS. EXTEND LINEAR HEAT DETECTION TO END OF LINE RESISTOR WITH NORMAL WIRING METHODS TO ACCESSIBLE LOCATION ON MAIN FLOOR.
- 4. PROVIDE ADDRESSABLE MONITORING MODULES IN MAIN ELECTRICAL ROOM FOR LINEAR HEAT DETECTION
- EXISTING ADDRESSABLE NOTIFIER PANEL.
- 6. EXTEND LINEAR HEAT DETECTION TO END OF LINE RESISTOR WITH NORMAL WIRING METHODS TO ACCESSIBLE LOCATION ON MAIN FLOOR.
- 7. PROVIDE LINEAR HEAT CABLE ALONG LIGHT DECK WALKWAY CEILING. EXTEND LINEAR HEAT DETECTION TO END OF LINE RESISTOR WITH NORMAL WIRING METHODS TO ACCESSIBLE LOCATION ON MAIN FLOOR.
- 8. CONNECT NEW HEAT DETECTORS TO EXISTING FLOOR AREA DEVICES.
- 9. CONNECT NEW HEAT DETECTORS TO EXISTING DEVICES AT TOP OF STAIR.

Winnipeg: 204-925-1150 towereng.ca These design documents are prepared solely for the use by the party with whom the design professional has entered into a contract and there are no representations of any kind made by the design professional to any party with whom the design professional has not entered into a contract. Any use

Kelowna: 250-765-7224

of the drawing, disk or electronic data without the expressed written permission of Tower Engineering Group is strictly prohibited. The contractor is responsible to verify all dimensions with conditions on the site and report discrepancies to Tower Engineering for adjustment. All prints to be returned.

> ENGINEERS
> GEOSCIENTISTS Certificate of Authorization Tower Engineering Group No. 4156

ISSUED FOR CONSTRUCTION REVISION/DESCRIPTION

DESIGNED APPROVED DATE 2024-XX-XX USER APPROVAL



PROJECT

THE CITY OF WINNIPEG PLANNING, PROPERTY AND DEVELOPMENT DEPARTMENT MUNICIPAL ACCOMMODATIONS DIVISION 3-65 GARRY STREET, R3C 4K4

RAINBOW STAGE FIRE ALARM UPGRADES

2021 MAIN ST

SHEET TITLE

FIRE ALARM RENO MAIN FLOOR PLAN

ALE	PROJECT No:	SHEET No:	$\neg \neg$
AS SHOWN	2022-006		E1.0