FORM N: DETAILED SPECIFICATIONS 25007

MEDIUM ROOF CARGO VAN 9000 LBS. GVWR

1. INSTRUCTIONS FOR COMPLETION OF SPECIFICATIONS

- 1.1 All items in these specifications should be answered indicating compliance or non-compliance.
- 1.2 **Proponents shall state "yes" for compliance or state "deviation"**, or give a reply where requested to do so. Deviations and/or equivalents shall be clearly stated and fully detailed. Deviations and/or equivalents will be considered subject to evaluation. In every instance where a brand name or design specifications is used, the City will also consider deviations and/or equivalents.
- 1.3 Lengthy explanations of deviations may be included in a separate document and must reference the appropriate Detailed Specification.
- 1.4 Each Proponent is required to fill in every blank. Failure to do so may be used as a basis for rejection of bid.
- 1.5 It will be the responsibility of the Proponent to inform the City of any errors or omissions in these Detailed Specifications, for under this Contract, the Contractor shall be held responsible to ensure that the manufacturer will be responsible for the design, performance, reliability and satisfactory operational function of the unit.

2. DESCRIPTION OF EQUIPMENT

- 2.1 These specifications describe a <u>Medium Roof Cargo Van</u> and other equipment and features as specified herein.
- 2.2 The <u>Medium Roof Cargo Van</u> shall be a new 2024 model year or newer.
- 2.3 The <u>Medium Roof Cargo Van</u> and all other items/components shall be the manufacturer's latest model. The equipment shall be furnished complete and ready for operation. Any parts or accessories not specifically mentioned, but which are required to complete and place the equipment and associated attachments in successful operation shall be furnished as though specifically mentioned in these specifications. The equipment and associated attachments, and all parts thereof, shall conform in strength and quality of material and workmanship, to the best standards and engineering practice of the industry.
- 2.4 The <u>Medium Roof Cargo Van</u> shall be the manufacturer's latest model, as may be modified by these specifications. The <u>Medium Roof Cargo Van</u>, including all auxiliary equipment, shall be furnished complete and ready for use. All parts not specifically mentioned but which are required for the complete unit shall conform in strength, quality of material and workmanship, to the best standards and engineering practice in the industry.
- 2.5 The ratings specified herein merely state the minimum values acceptable to the City, not implying that those values are sufficient for the design of the particular equipment being bid.

3. OTHER SPECIFICATIONS AND STANDARDS

- 3.1 All applicable SAE Standards form an integral part of the vehicle specifications and shall have precedence in any conflict concerning minimum acceptable standards.
- 3.2 <u>Where applicable</u>, the <u>Medium Roof Cargo Van</u> shall comply with the applicable regulations:

Standard - Specification/Regulation	Internet URL
Transport Canada, National Safety Mark, NSM:	http://www.tc.gc.ca/eng/acts-regulations/acts-road.htm
Manitoba Safety and Health Regulation, Parts 12, 16, 22:	http://web2.gov.mb.ca/laws/regs/current/217.06.pdf
Canadian Motor Vehicle Safety Standards C.M.V.S.S.:	http://laws- lois.justice.gc.ca/eng/regulations/C.R.C.,_c1038/sect ion-sched3.html

Manitoba Highway Traffic Act regulations and requirements including, but not limited to, a Manitoba Government Inspection with Safety Sticker:

Canadian Standards Association CSA:

Under Writers of Canada U/L:

Society of Automotive Engineers SAE:

City of Winnipeg Lighting Visibility Standard:

Manitoba Building Code:

http://web2.gov.mb.ca/laws/regs/index.php?act=h60

http://www.csagroup.org

http://www.ulc.ca

http://www.sae.org

http://winnipeg.ca/matmgt/pdfs/PublicWorksEquipLight ingVisibility.pdf

https://web2.gov.mb.ca/laws/regs/current/_pdfregs.php?reg=31/2011

- 3.3 <u>Where applicable</u>, the completed unit shall include a Manitoba Government Inspection with Safety Sticker.
- 3.4 <u>Where applicable, the manufacturer/installer shall affix their National Safety Mark (NSM) certification</u> sticker on each unit.

4. FUEL

4.1 The equipment shall be fully fuelled upon delivery (no exceptions).

5. **REFERENCES**

5.1 Provide five (5) references where this equipment is used in a working environment where climatic conditions are similar to the City of Winnipeg.

6. MAKE & MODEL

6.1 State year, make and model being bid:

lodel Year:	
1ake:	
1odel:	

7. PERFORMANCE RELIABILITY

- 7.1 The responsibility for the design of the <u>Medium Roof Cargo Van</u> its performance and reliability shall rest upon the Contractor.
- 7.2 The term "repeated failures" as used herein is defined to mean that the same component, subassembly, or assembly develops repeated defects, breakdowns and/or malfunctions rendering the vehicle inoperative, or requiring repeated shop correction, service and/or replacement during the warranty period applicable for said component, subassembly, of assembly. Minor items or ordinary service adjustments are not included, or considered under the scope of "repeated failures", as well as other factors, such as operational damage due to accidents, misuse or lack of proper maintenance, service and lubrication attention by not following the manufacturer's preventative maintenance schedule.
- 7.3 Where the <u>Medium Roof Cargo Van</u> develops "repeated failures" in service, the Contractor shall make any necessary engineering changes, repairs, alterations or modifications in order to guarantee reliability of performance.

7.4 The equipment shall be capable of consistent top performance in City of Winnipeg Environment. Note: The City of Winnipeg has four seasons with ambient temperatures ranging from approximately 90°F (32°C) to -40°F (-40°C).

8. SERVICE FACILITY

8.1 For the purpose of warranty repairs, the Bidder shall have an authorized service facility. The facility, or a portion thereof, shall be dedicated to the service and maintenance of the type equipment being offered. Bidders shall provide a description of the service facility including, but not limited to, number of qualified service staff, years of service experience, and general service capabilities within three (3) Business Days upon request of the Contract Administrator or City representative.

9. QUALIFICATIONS OF MANUFACTURER & CONTRACTOR

- 9.1 The manufacturer of the <u>Medium Roof Cargo Van</u> shall have five (5) years continuous experience manufacturing <u>Medium Roof Cargo Van</u>.
- 9.2 The manufacturer shall have in effect a documented quality control program ensuring that the quality of materials and workmanship, including welding, conforms to the best standards and engineering practice of the industry.
- 9.3 The Contractor shall have five (5) years continuous experience servicing, repairing and maintaining <u>Medium Roof Cargo Van</u> of the type being offered.

10. SPECIFICATIONS

Medium Roof Cargo Van

10.1	Vehicle Make	State: make:	
10.2	Vehicle Model	State: model:	
10.3	Vehicle Model Year	State: model year:	
	Configuration		
10.4	GVWR	Approximately 9000 lbs. State: GVWR:	
10.5	Wheelbase (Regular)	Approximately 129.9 in. State: wheelbase:	
10.6	Vehicle Length	Approximately 217.8 in. State: vehicle length:	
10.7	Cargo Height (Interior)	Approximately 72.0 in. State: cargo height:	
10.8	Cargo Length at Floor	Approximately 126.0 in. State: cargo length:	

Powertrain

10.9	Engine	 3.5L PFDi V6 engine Horsepower: 275 hp @ 6,250 RPM Torque: 260 lb-ft @ 4,000 RPM 	
10.10	Transmission	10-speed automaticAuxiliary transmission oil cooler	
10.11	Coolant	Extended Life Coolant, -37°C (-35°F)	
	Drive		
10.12	Drive	Single Rear Wheel (SRW)	
10.13	Rear Wheel Drive (RWD)	Rear Wheel Drive (RWD)	
	Axle		
10.14	Front Axle	Heavy-duty front axle	
10.15	Rear Axle Differential	 4.10 axle ratio Limited slip State: axle ratio: 	
	Exterior		
10.16	Bumper - Front	BlackBody coloured with lower valence	
10.17	Bumper - Rear	BlackMolded-In-color with Integral Step	
10.18	Doors – Side	Sliding Passenger side door cargo doorNo glass	
10.19	Doors – Rear	 50/50 hinged rear doors Approximately 250-degree opening No glass	
10.20	Mirrors - Exterior	 Long Arm Power adjusting Manual folding Heated Turn signals Blind spot assist 	
10.21	Running Boards	Driver and passengerExtended length	
10.22	Tires & Wheels	 Wheels with All-terrain Winter Rated Tires or All-weather Winter Rated Tires Bearing the mountain snow flake symbol Meets specific snow traction performance requirements set by the Rubber Association of Canada Heavy duty 16-inch steel road wheels State: tire size:	

10.23	Tires & Wheels - Spare	Full-size spare wheel & tire with carrier	
10.24	Wheel Well Liners	BlackFront only	
10.25	Windows / Glass	 Standard: Side door glass - No Rear door glass - No All windows to be tinted 	
10.26	Exterior Lighting	High intensity discharge (HID) head lampsFront fog lights	
	Interior		
10.27	Centre Console	 Large centre console with integrated shifter Dual cup holders Additional storage area 	
10.28	Doors – Locks and Windows	 Glove box – locking Rear cargo door – interior exit handle Rear cargo door – exterior locking cylinder Power locks and windows 	
10.29	Floor Covering	VinylFloor Mats - Rubber	
10.30	Rear View Mirror	Interior rear view	
10.31	Interior Lighting	Front, side and rear domeMaps	
10.32	Cargo Lighting	 Full rear compartment lighting Includes cargo area LED lights at: C-Pillar D-Pillar Rear compartment LED lamp switch 	
10.33	Door Storage	Front door side pockets	
10.34	Rear View Camera	Rear view camera	
10.35	Seating	 Bucket Seats Cloth Driver and passenger Manual Reclining Adjustable Headrest Driver-side and passenger-side inboard armrest 	

Functional

10.36	Alternator	Dual alternators – heavy duty Approximately 250 amps each State: amperage:	
10.37	Engine Block Heater	Block heater/pan heater	
		State: yes or no to the following:	
		With cord through grille:	
		Two-way removable cord:	
10.38	Air Conditioning / Heating	 Front / Rear auxiliary Air Conditioning and Heater Driver controlled Heat distribution from rear of front passenger seat Air conditioning distributed from rear of van Rear heating shall be factory installed and insulated 	
10.39	Audio	 SYNC Technology AM-FM stereo Bluetooth® technology, for use with cellular phones, "hands-free" capable, voice command activated through vehicle's radio circuit Dual USB ports 	
10.40	Batteries	 Dual AGM batteries Heavy duty Approximately 70 amp-hr each State: CCA: 	
10.41	Instrumentation	Vehicle maintenance monitor including engine hour meter	
10.42	Brakes	 4-wheel anti-lock disc brakes Parking brake	
10.43	Telematics	Compatible with Geotab	
10.44	Interior Power	12V PowerPointQty two (2)	
10.45	Power Outlet	• 110V/400W	
		Note: High-power outlets deliver up to 400 watts of power, allowing drivers to easily charge smaller corded tools, battery chargers or mobile devices on-site	
10.46	Steering	PowerTiltTelescoping	

10.47	Ignition Keys and Key Fobs	Three (3) Remote keyless entry – three (3) key fobs and one (1) ignition key or if the keys and key fobs are one unit, supply 3 key fobs.	
10.48	Keyless Entry Pad	Keyless entry pad	
10.49	Blind Spot Assist	Provides a visual warning and resistive steering torque to prevent a Collison should an object be recognized in the vehicles blind spot while changing lanes	
10.50	Lane Keeping System	Alerts the driver if their vehicle is unintentionally leaving its intended lane	
10.51	Reverse Sensing System	Alerts the driver if there are obstacles behind the vehicle when reversing	
10.52	Windshield Wipers	 Automatic rain-sensing windshield wiper "Reflex" style wiper blades 	
	Automatic Engine Idle Shut-D	Down	
10.53	Engine Idle Shut-Down	Automatic10-minute timer	
	Safety/Security		
10.54	Roll Stability Control	Improves vehicle control on all driving surfaces, including snow, ice, gravel, rain-covered roads, and dry pavement	
10.55	Cruise Control	Cruise Control with display centre	
10.56	Perimeter Anti-Theft Alarm	The perimeter alarm is a deterrent against unauthorized access to the vehicle	
10.57	Remote Start	Remote start system	
10.58	Airbags	Driver and passenger	
10.59	Back Up Alarm	Approximately 102 dB(A) warning capability	
10.60	Heavy Duty Cargo Flooring	 Made of a rigid composite plastic cover with an anti- slip surface for better footing and a non-porous surface to keep mold from forming inside the van Include heavy duty scuff plate for both side and rear doors 	
	Upfitter Package		
10.61	Upfitter Package	High capacity Upfitter switchesAuxiliary fuse panelHigh spec interface connector	
10.62	Upfitter Interface Module (UIM)	Upfitter interface module (UIM)	
10.63	Vehicle Wiring System	Modified vehicle connections for customized wiring harness provisions	

	Towing		
10.64	Towing	Heavy-duty trailer tow packageTrailer brake controller	
	Mud Flaps		
10.65	Mud Flaps	Front and backOEMMoulded	
	Colour		
10.66	Colour	 Exterior - Bright white Interior – Black or grey 	
	Options: Note: Options to be priced only	y as indicated on Form B: Prices	
10.67	Option 1: Long Wheelbase, Me	edium Roof	
	Wheelbase (Long) - Approxima State: wheelbase:		
	Vehicle Length - Approximately State: vehicle length:		
	Cargo Height (Interior) - Appro. State: cargo height:		
	Cargo Length at Floor - Appro> State: cargo length:		
10.68	Option 2: 3.5L EcoBoost® V6	 3.5L EcoBoost® V6 Horsepower: 310 hp @ 5,500 RPM. Torque: 400 lb-ft @ 2,500 RPM 	
10.69	Option 3: All Wheel Drive (AWD)	All Wheel Drive (AWD)	
10.70	Option 4: Rear Heat Only (Cargo Area)	Rear heat without air conditioning in cargo area	
10.71	Option 5: Glass - Rear Cargo Door	 Side door glass - No Rear door glass - Yes Window defroster All windows to be tinted 	
10.72	Option 6: Glass - Rear Cargo Door and Side Cargo Door	 Side door glass - Yes Rear door glass - Yes Window defroster All windows to be tinted 	

WARRANTY

11.1	All warranty information shall be de	etailed and include all exclusions .	
	The Contractor shall provide all pu equipment.	blished warranty information upon delivery of the	
	Bidder shall state all warranty info	rmation.	
11.2		of Cargo Van shall cover the complete gainst any defects of workmanship, construction	
		efective during said warranty period and has not egligence on the part of the user shall be repaired	
	The warranty shall be effective from the City of Winnipeg	m the date the equipment is put into service by	
11.3	Basic Vehicle (Comprehensive)	State: Terms:	
11.4	Corrosion Perforation	State: Terms:	
11.5	Emission Control Components	State: Terms:	
11.6	Powertrain Coverage	State: Terms:	
	DELIVERY		
12.1	Delivery Point:		
		d, ready for operation and delivered F.O.B. with ce and N.V.I.S. (if applicable) to the WFMA 185	
12.2	Delivery Time:		
	Equipment shall be delivered betw	veen 8:00 am and 2:00 pm on Business Days.	
	State: earliest delivery time from c	late of award:	
12.3	Delivery Contact:		
	The Contractor shall contact the C equipment.	ontract Administrator prior to delivery of the	
12.4	<u>P.D.I:</u>		
	A pre-delivery inspection shall be p Proof upon inspection including co	performed by the Contractor on the equipment.	

MANUALS

13.1	Manuals: The manuals shall cover the complete equipment including all components thereof, CD or USB is preferred where available.	
13.2	Operator's Manual: One (1) per unit shall be supplied with the units when delivered.	
14.0	PARTS/LABOUR PRICING:	
14.1	Bidder to provide City of Winnipeg Parts Discount % Pricing from retail parts pricing. State: percentage discount:	
14.2	Bidder to provide City of Winnipeg Labor Discount % Pricing from retail shop labor rate. State: percentage discount:	

FIRST SERVICE PREVENTATIVE MAINTENANCE KIT:

- 15.1 <u>If applicable</u>, in order to assure minimum downtime of the Equipment in future service, the Contractor must provide one (1) complete replacement set of new OEM filters for each unit purchased. The set of required filters shall include (if applicable to the equipment type) air, fuel, oil, transmission, cab and hydraulic, or otherwise all known necessary common replacement filters required for the first preventative maintenance servicing and first transmission service.
- 15.2 The Contractor must provide a list of factory recommended lubricants to be used with the equipment, as well as a complete cross reference guide for all warranty approved lubricants and filters that can be used during Preventative Maintenance servicing.

FORM N: DETAILED SPECIFICATIONS 25008

HIGH ROOF CARGO VAN 9500 LBS. GVWR

1. INSTRUCTIONS FOR COMPLETION OF SPECIFICATIONS

- 1.1 All items in these specifications should be answered indicating compliance or non-compliance.
- 1.2 **Proponents shall state "yes" for compliance or state "deviation"**, or give a reply where requested to do so. Deviations and/or equivalents shall be clearly stated and fully detailed. Deviations and/or equivalents will be considered subject to evaluation. In every instance where a brand name or design specifications is used, the City will also consider deviations and/or equivalents.
- 1.3 Lengthy explanations of deviations may be included in a separate document and must reference the appropriate Detailed Specification.
- 1.4 Each Proponent is required to fill in every blank. Failure to do so may be used as a basis for rejection of bid.
- 1.5 It will be the responsibility of the Proponent to inform the City of any errors or omissions in these Detailed Specifications, for under this Contract, the Contractor shall be held responsible to ensure that the manufacturer will be responsible for the design, performance, reliability and satisfactory operational function of the unit.

2. DESCRIPTION OF EQUIPMENT

- 2.1 These specifications describe a <u>High Roof Cargo Van</u> and other equipment and features as specified herein.
- 2.2 The High Roof Cargo Van shall be a new 2024 model year or newer.
- 2.3 The <u>High Roof Cargo Van</u> and all other items/components shall be the manufacturer's latest model. The equipment shall be furnished complete and ready for operation. Any parts or accessories not specifically mentioned, but which are required to complete and place the equipment and associated attachments in successful operation shall be furnished as though specifically mentioned in these specifications. The equipment and associated attachments, and all parts thereof, shall conform in strength and quality of material and workmanship, to the best standards and engineering practice of the industry.
- 2.4 The <u>High Roof Cargo Van</u> shall be the manufacturer's latest model, as may be modified by these specifications. The <u>High Roof Cargo Van</u>, including all auxiliary equipment, shall be furnished complete and ready for use. All parts not specifically mentioned but which are required for the complete unit shall conform in strength, quality of material and workmanship, to the best standards and engineering practice in the industry.
- 2.5 The ratings specified herein merely state the minimum values acceptable to the City, not implying that those values are sufficient for the design of the particular equipment being bid.

3. OTHER SPECIFICATIONS AND STANDARDS

- 3.1 All applicable SAE Standards form an integral part of the vehicle specifications and shall have precedence in any conflict concerning minimum acceptable standards.
- 3.2 <u>Where applicable</u>, the <u>High Roof Cargo Van</u> shall comply with the applicable regulations:

Standard - Specification/Regulation	Internet URL
Transport Canada, National Safety Mark, NSM:	http://www.tc.gc.ca/eng/acts-regulations/acts-road.htm
Manitoba Safety and Health Regulation, Parts 12, 16, 22:	http://web2.gov.mb.ca/laws/regs/current/217.06.pdf
Canadian Motor Vehicle Safety Standards C.M.V.S.S.:	http://laws- lois.justice.gc.ca/eng/regulations/C.R.C.,_c1038/sect ion-sched3.html

Manitoba Highway Traffic Act regulations and requirements including, but not limited to, a Manitoba Government Inspection with Safety Sticker:

Canadian Standards Association CSA:

Under Writers of Canada U/L:

Society of Automotive Engineers SAE:

City of Winnipeg Lighting Visibility Standard:

Manitoba Building Code:

http://web2.gov.mb.ca/laws/regs/index.php?act=h60

http://www.csagroup.org

http://www.ulc.ca

http://www.sae.org

http://winnipeg.ca/matmgt/pdfs/PublicWorksEquipLight ingVisibility.pdf

https://web2.gov.mb.ca/laws/regs/current/_pdfregs.php?reg=31/2011

- 3.3 <u>Where applicable</u>, the completed unit shall include a Manitoba Government Inspection with Safety Sticker.
- 3.4 <u>Where applicable, the manufacturer/installer shall affix their National Safety Mark (NSM) certification</u> sticker on each unit.

4. FUEL

4.1 <u>Where applicable</u>, the equipment shall be fully fuelled upon delivery (no exceptions).

5. **REFERENCES**

5.1 Provide five (5) references where this equipment is used in a working environment where climatic conditions are similar to the City of Winnipeg.

6. MAKE & MODEL

6.1 State year, make and model being bid:

lodel Year:	
lake:	
1odel:	

7. PERFORMANCE RELIABILITY

- 7.1 The responsibility for the design of the <u>High Roof Cargo Van</u> its performance and reliability shall rest upon the Contractor.
- 7.2 The term "repeated failures" as used herein is defined to mean that the same component, subassembly, or assembly develops repeated defects, breakdowns and/or malfunctions rendering the vehicle inoperative, or requiring repeated shop correction, service and/or replacement during the warranty period applicable for said component, subassembly, of assembly. Minor items or ordinary service adjustments are not included, or considered under the scope of "repeated failures", as well as other factors, such as operational damage due to accidents, misuse or lack of proper maintenance, service and lubrication attention by not following the manufacturer's preventative maintenance schedule.
- 7.3 Where the <u>High Roof Cargo Van</u> develops "repeated failures" in service, the Contractor shall make any necessary engineering changes, repairs, alterations or modifications in order to guarantee reliability of performance.

7.4 The equipment shall be capable of consistent top performance in City of Winnipeg Environment. Note: The City of Winnipeg has four seasons with ambient temperatures ranging from approximately 90°F (32°C) to -40°F (-40°C).

8. SERVICE FACILITY

8.1 For the purpose of warranty repairs, the Bidder shall have an authorized service facility. The facility, or a portion thereof, shall be dedicated to the service and maintenance of the type equipment being offered. Bidders shall provide a description of the service facility including, but not limited to, number of qualified service staff, years of service experience, and general service capabilities within three (3) Business Days upon request of the Contract Administrator or City representative.

9. QUALIFICATIONS OF MANUFACTURER & CONTRACTOR

- 9.1 The manufacturer of the <u>High Roof Cargo Van</u> shall have five (5) years continuous experience manufacturing <u>High Roof Cargo Van</u>.
- 9.2 The manufacturer shall have in effect a documented quality control program ensuring that the quality of materials and workmanship, including welding, conforms to the best standards and engineering practice of the industry.
- 9.3 The Contractor shall have five (5) years continuous experience servicing, repairing and maintaining <u>High</u> <u>Roof Cargo Van</u> of the type being offered.

10. SPECIFICATIONS

	High Roof Cargo Van			
10.1	Vehicle Make	State: make:		
10.2	Vehicle Model	State: model:		
10.3	Vehicle Model Year	State: model year:		
	Configuration			
10.4	GVWR	Approximately 9500 lbs. State: GVWR:		
10.5	Wheelbase	Approximately 147.6 in. State: wheelbase:		
10.6	Vehicle Length	Approximately 235.5 in. State: vehicle length:		
10.7	Cargo Height (Interior)	Approximately 81.5 in. State: cargo height:		
10.8	Cargo Length at Floor	Approximately 143.7 in. State: cargo length:		

Powertrain

10.9	Engine	 3.5L PFDi V6 engine Horsepower: 275 hp @ 6,250 RPM Torque: 260 lb-ft @ 4,000 RPM 	
10.10	Transmission	10-speed automaticAuxiliary transmission oil cooler	
10.11	Coolant	Extended Life Coolant, -37°C (-35°F)	
	Drive		
10.12	Drive	Single Rear Wheel (SRW)	
10.13	Rear Wheel Drive (RWD)	Rear Wheel Drive (RWD)	
	Axle		
10.14	Front Axle	Heavy-duty front axle	
10.15	Rear Axle Differential	 4.10 axle ratio Limited slip State: axle ratio: 	
	Exterior		
10.16	Bumper - Front	BlackBody coloured with lower valence	
10.17	Bumper - Rear	BlackMolded-In-color with Integral Step	
10.18	Doors – Side	Sliding Passenger side door cargo doorNo glass	
10.19	Doors – Rear	 50/50 hinged rear doors Approximately 250-degree opening No glass	
10.20	Mirrors - Exterior	 Long Arm Power adjusting Manual folding Heated Turn signals Blind spot assist 	
10.21	Running Boards	Driver and passengerExtended length	
10.22	Tires & Wheels	 Wheels with All-terrain Winter Rated Tires or All-weather Winter Rated Tires Bearing the mountain snow flake symbol Meets specific snow traction performance requirements set by the Rubber Association of Canada Heavy duty 16-inch steel road wheels State: tire size:	

10.23	Tires & Wheels - Spare	Full-size spare wheel & tire with carrier	
10.24	Wheel Well Liners	BlackFront only	
10.25	Windows / Glass	 Standard: Side door glass - No Rear door glass - No All windows to be tinted 	
10.26	Exterior Lighting	High intensity discharge (HID) head lampsFront fog lights	
	Interior		
10.27	Centre Console	 Large centre console with integrated shifter Dual cup holders Additional storage area 	
10.28	Doors – Locks and Windows	 Glove box – locking Rear cargo door – interior exit handle Rear cargo door – exterior locking cylinder Power locks and windows 	
10.29	Floor Covering	VinylFloor Mats - Rubber	
10.30	Rear View Mirror	Interior rear view	
10.31	Interior Lighting	Front, side and rear domeMaps	
10.32	Cargo Lighting	 Full rear compartment lighting Includes cargo area LED lights at: C-Pillar D-Pillar Rear compartment LED lamp switch 	
10.33	Door Storage	Front door side pockets	
10.34	Rear View Camera	Rear view camera	
10.35	Seating	 Bucket Seats Cloth Driver and passenger Manual Reclining Adjustable Headrest Driver-side and passenger-side inboard armrest 	

Functional

10.36	Alternator	Dual alternators – heavy duty Approximately 250 amps each State: amperage:	
10.37	Engine Block Heater	Block heater/pan heater	
		State: yes or no to the following:	
		With cord through grille:	
		Two-way removable cord:	
10.38	Air Conditioning / Heating	 Front / Rear auxiliary Air Conditioning and Heater Driver controlled Heat distribution from rear of front passenger seat Air conditioning distributed from rear of van Rear heating shall be factory installed and insulated 	
10.39	Audio	 SYNC Technology AM-FM stereo Bluetooth® technology, for use with cellular phones, "hands-free" capable, voice command activated through vehicle's radio circuit Dual USB ports 	
10.40	Batteries	 Dual AGM batteries Heavy duty Approximately 70 amp-hr each State: CCA: 	
10.41	Instrumentation	Vehicle maintenance monitor including engine hour meter	
10.42	Brakes	 4-wheel anti-lock disc brakes Parking brake	
10.43	Telematics	Compatible with Geotab	
10.44	Interior Power	12V PowerPointQty two (2)	
10.45	Power Outlet	• 110V/400W	
		Note: High-power outlets deliver up to 400 watts of power, allowing drivers to easily charge smaller corded tools, battery chargers or mobile devices on-site	
10.46	Steering	PowerTiltTelescoping	

10.47	Ignition Keys and Key Fobs	Three (3) Remote keyless entry – three (3) key fobs and one (1) ignition key or if the keys and key fobs are one unit, supply 3 key fobs.	
10.48	Keyless Entry Pad	Keyless entry pad	
10.49	Blind Spot Assist	Provides a visual warning and resistive steering torque to prevent a Collison should an object be recognized in the vehicles blind spot while changing lanes	
10.50	Lane Keeping System	Alerts the driver if their vehicle is unintentionally leaving its intended lane	
10.51	Reverse Sensing System	Alerts the driver if there are obstacles behind the vehicle when reversing	
10.52	Windshield Wipers	 Automatic rain-sensing windshield wiper "Reflex" style wiper blades 	
	Automatic Engine Idle Shut-D	Pown	
10.53	Engine Idle Shut-Down	Automatic10-minute timer	
	Safety/Security		
10.54	Roll Stability Control	Improves vehicle control on all driving surfaces, including snow, ice, gravel, rain-covered roads, and dry pavement	
10.55	Cruise Control	Cruise Control with display centre	
10.56	Perimeter Anti-Theft Alarm	The perimeter alarm is a deterrent against unauthorized access to the vehicle	
10.57	Remote Start	Remote start system	
10.58	Airbags	Driver and passenger	
10.59	Back Up Alarm	Approximately 102 dB(A) warning capability	
10.60	Heavy Duty Cargo Flooring	 Made of a rigid composite plastic cover with an anti- slip surface for better footing and a non-porous surface to keep mold from forming inside the van Include heavy duty scuff plate for both side and rear doors 	
	Upfitter Package		
10.61	Upfitter Package	High capacity Upfitter switchesAuxiliary fuse panelHigh spec interface connector	
10.62	Upfitter Interface Module (UIM)	Upfitter interface module (UIM)	
10.63	Vehicle Wiring System	Modified vehicle connections for customized wiring harness provisions	

	Towing		
10.64	Towing	Heavy-duty trailer tow packageTrailer brake controller	
	Mud Flaps		
10.65	Mud Flaps	Front and backOEMMoulded	
	Colour		
10.66	Colour	 Exterior - Bright white Interior – Black or grey 	
	Options: Note: Options to be priced only	as indicated on Form B: Prices	
10.67	Option 1: Extended Length, High Roof		
	Wheelbase - Approximately 147.6 in. State: wheelbase:		
	Vehicle Length - Approximately 263.9 in. State: vehicle length: Cargo Height (Interior) - Approximately 81.5 in. State: cargo height:		
	Cargo Length at Floor - Approximately 172.2 in. State: cargo length:		
10.68	Option 2: 3.5L EcoBoost® V6	 3.5L EcoBoost® V6 Horsepower: 310 hp @ 5,500 RPM Torque: 400 lb-ft @ 2,500 RPM 	
10.69	Option 3: All Wheel Drive (AWD)	All Wheel Drive (AWD)	
10.70	Option 4: Rear Heat Only (Cargo Area)	Rear heat without air conditioning in cargo area	
10.71	Option 5: Glass - Rear Cargo Door	 Side door glass - No Rear door glass - Yes Window defroster All windows to be tinted 	
10.72	Option 6: Glass - Rear Cargo Door and Side Cargo Door	 Side door glass - Yes Rear door glass - Yes Window defroster All windows to be tinted 	

WARRANTY

11.1	All warranty information shall be detailed and include all exclusions .			
	The Contractor shall provide all published warranty information upon delivery of the equipment.			
	Bidder shall state all warranty information.			
11.2	The warranty for the <u>High Roof Cargo Van</u> shall cover the complete equipment,and all parts thereof against any defects of workmanship, construction and materials.			
	Any equipment that has become defective during said warranty period and has not proven to have been caused by negligence on the part of the user shall be repaired or replaced at no cost to the City.			
	The warranty shall be effective from the City of Winnipeg	The warranty shall be effective from the date the equipment is put into service by		
11.3	Basic Vehicle (Comprehensive)	State: Terms:		
11.4	Corrosion Perforation	State: Terms:		
11.5	Emission Control Components	State: Terms:		
11.6	Powertrain Coverage	State: Terms:		
	DELIVERY			
12.1	Delivery Point:	Delivery Point:		
	The complete unit shall be serviced, ready for operation and delivered F.O.B. with the freight prepaid, including invoice and N.V.I.S. (if applicable) to the WFMA 185 Tecumseh Street, Winnipeg MB.			
12.2	Delivery Time:			
	Equipment shall be delivered between 8:00 am and 2:00 pm on Business Days.			
	State: earliest delivery time from date of award:			
12.3	Delivery Contact:			
	The Contractor shall contact the Contract Administrator prior to delivery of the equipment.			
12.4	<u>P.D.I:</u>			
	A pre-delivery inspection shall be performed by the Contractor on the equipment. Proof upon inspection including completed check list			
	MANUALS			
13.1	Manuals: The manuals shall cover the comp CD or USB is preferred where ava	plete equipment including all components thereof, ilable.		

13.2 **Operator's Manual:**

One (1) per unit shall be supplied with the units when delivered.

PARTS/LABOUR PRICING:

- Bidder to provide City of Winnipeg Parts Discount % Pricing from retail parts pricing.
 State: percentage discount: ______
- Bidder to provide City of Winnipeg Labor Discount % Pricing from retail shop labor rate.
 State: percentage discount: ______

FIRST SERVICE PREVENTATIVE MAINTENANCE KIT:

- 15.1 <u>If applicable</u>, in order to assure minimum downtime of the Equipment in future service, the Contractor must provide one (1) complete replacement set of new OEM filters for each unit purchased. The set of required filters shall include (if applicable to the equipment type) air, fuel, oil, transmission, cab and hydraulic, or otherwise all known necessary common replacement filters required for the first preventative maintenance servicing and first transmission service.
- 15.2 The Contractor must provide a list of factory recommended lubricants to be used with the equipment, as well as a complete cross reference guide for all warranty approved lubricants and filters that can be used during Preventative Maintenance servicing.