



- REFERENCE NOTES:**
- PAVEMENT DIMENSIONS ARE TO BACK OF CURB
  - PROPERTY LINES OBTAINED FROM CITY OF WINNIPEG L.B.I.S., AND NO SCALE FACTOR WAS APPLIED
  - REFER TO AECOM FIELD BOOK NO. 5172

- CONSTRUCTION NOTES:**
- PLANE ASPHALT PAVEMENT (50-100mm DEPTH)
  - REMOVE ASPHALT PAVEMENT
  - REMOVE CONCRETE BARRIER CURB (SEPARATE)
  - REMOVE CONCRETE MODIFIED BARRIER CURB (INTEGRAL)
  - REMOVE 100mm CONCRETE SIDEWALK
  - CONSTRUCT NEW ASPHALT PAVEMENT OVERLAY TYPE MS1/MS2 85mm AVERAGE THICKNESS
  - REMOVE EXISTING CONCRETE PAVEMENT AND CONSTRUCT NEW 200mm REINFORCED CONCRETE PAVEMENT c/w ASPHALT PAVEMENT OVERLAY TYPE MS1/MS2 (85mm) AVERAGE THICKNESS
  - INSTALL NEW MONOLITHIC CONCRETE BARRIER CURB AND SPLASH STRIP (150mm HT, 750mm WIDTH) (SD-223A)
  - RENEW CONCRETE CURB RAMP (8-12mm HT, MONOLITHIC)
  - RENEW CONCRETE BARRIER CURB (150mm HT, DOWELLED)
  - RENEW 100mm CONCRETE SIDEWALK
  - INSTALL NEW 100mm CONCRETE SIDEWALK
  - INSTALL NEW MONOLITHIC CONCRETE MODIFIED BARRIER CURB AND SIDEWALK
  - INSTALL NEW MONOLITHIC CONCRETE BULLNOSE AND MEDIAN SLAB
  - INSTALL DETECTABLE WARNING SURFACE TILE
  - REMOVE EXISTING CATCH PIT / CATCH BASIN
  - INSTALL NEW 1200mm CATCH BASIN (SD-024) c/w BARRIER CURB AND GUTTER INLET FRAME AND COVER (AP-011/AP-012) AND CONNECT 250mm Φ PVC SEWER SERVICE TO EXISTING CATCH BASIN
  - ADJUST EXISTING MANHOLE / CATCH BASIN TO GRADE
  - INSTALL CAST IRON RISER RING
  - ADJUST EXISTING WATER VALVE TO GRADE
  - REPLACE SOLID FRAME AND COVER (AP-006/AP-007)
  - CONSTRUCT NEW MULTI-USE ASPHALT PATH (REFER TO CT-19, DETAIL 1)
  - REMOVE EXISTING CONCRETE PAVEMENT AND CONSTRUCT NEW 200mm REINFORCED CONCRETE PAVEMENT c/w SEPARATION GEOTEXTILE, 150mm SUB-BASE (50mm SIZE), 50mm BASE COURSE, ASPHALT PAVEMENT OVERLAY TYPE MS1/MS2 85mm AVERAGE THICKNESS
  - PLACE SUFFICIENT FILL MATERIAL

**PLAN**  
Scale 1:250

**PRELIMINARY  
NOT FOR CONSTRUCTION**

**ENGINEERS  
GEOLOGISTS  
MANITOBA**  
Certificate of Authorization  
AECOM Canada ULC  
No. 4671

**METRIC**  
WHOLE NUMBERS INDICATE MILLIMETRES  
DECIMALIZED NUMBERS INDICATE METRES

150 mm W.M.	WATERMAIN	150 mm W.M.	HYDRO	HYDRO	PROFILE
◇	HYDRANT	◆	M.T.S.	M.T.S.	WB GUTTER
⊙	VALVE	⊙	CONCRETE	CONCRETE	WB MEDIAN GUTTER
⊕	LAND DRAINAGE SEWER	⊕	ASPHALT	ASPHALT	EB GUTTER
⊖	WASTEWATER SEWER	⊖	PROPERTY LINE	PROPERTY LINE	EB MEDIAN GUTTER
○	MANHOLE	●	SURVEY BAR	SURVEY BAR	
□	CATCH BASIN	■	ELEVATION	ELEVATION (35.750)	
▽	CATCH PIT	⊗	TREE	TREE	
↑	TRAFFIC SIGNAL POLE	⊕	SIDEWALK RAMP	SIDEWALK RAMP	
↑	STREET LIGHT	⊕	CONCRETE SIDEWALK	CONCRETE SIDEWALK	
—	GAS	—	FENCE	FENCE	
---	EXISTING	---	LEGEND - PLAN	LEGEND - PLAN	LEGEND - PROFILE
---	LEGEND - PLAN	---	PROPOSED	PROPOSED	PROPOSED

**LOCATION APPROVED UNDERGROUND STRUCTURES**

SUPV. U/G STRUCTURES COMMITTEE DATE

**NOTE:**  
LOCATION OF UNDERGROUND STRUCTURES AS SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE, BUT NO GUARANTEE IS GIVEN THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT. CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL SERVICES MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES BEFORE PROCEEDING WITH CONSTRUCTION.

B.M. ELEV.	84R523 - S.W. Cor. Corydon Ave. & Park Blvd. N., Tblt. on top of 0.05 m dia. x 2.4 m iron pipe 2.6 m N. of S.L. of Corydon Ave. & 6.2 m E. of W.L. of Park Blvd. N. ELEVATION: 233.773		
HORIZONTAL	Northing: 552515.364, Easting: 627893.162		
NO.	REVISIONS	DATE	BY
1	ISSUED FOR ADDENDUM 01	04/02/2026	TLF
0	ISSUED FOR TENDER	03/26/2026	TLF

**AECOM**

DESIGNED BY	JRC	CHECKED BY	TLF
DRAWN BY	RAM	APPROVED BY	TLF
HOR. SCALE:	1:250	RELEASED FOR CONSTRUCTION BY:	
VERTICAL:	1:10	DATE	04/02/2026

**ENGINEER'S SEAL**

PROFESSIONAL ENGINEER  
23820  
2026-04-02  
CONSULTANT DRAWING NO. CT-11

**THE CITY OF WINNIPEG**  
PUBLIC WORKS DEPARTMENT  
ENGINEERING DIVISION

2026 REGIONAL STREET RENEWAL PROGRAM  
CORYDON AVENUE

ASPHALT PAVEMENT REHABILITATION  
STATION 1+020 TO STATION 1+160 WEST BOUND  
PLAN-PROFILE

CITY DRAWING NUMBER P-3601-11  
SHEET 12 OF 28