



- REFERENCE NOTES:**
- A. PAVEMENT DIMENSIONS ARE TO BACK OF CURB
  - B. PROPERTY LINES OBTAINED FROM CITY OF WINNIPEG L.B.I.S., AND NO SCALE FACTOR WAS APPLIED
  - C. REFER TO AECOM FIELD BOOK NO. 5172

- CONSTRUCTION NOTES:**
1. PLANE ASPHALT PAVEMENT (50-100mm DEPTH)
  2. REMOVE ASPHALT PAVEMENT
  3. REMOVE CONCRETE PAVEMENT
  4. REMOVE CONCRETE BARRIER CURB (SEPARATE)
  5. REMOVE 100mm CONCRETE SIDEWALK
  6. CONSTRUCT NEW ASPHALT PAVEMENT OVERLAY (TYPE MS1/MS2 85mm AVERAGE THICKNESS)
  7. REMOVE EXISTING CONCRETE PAVEMENT AND CONSTRUCT NEW 200mm REINFORCED CONCRETE PAVEMENT c/w ASPHALT PAVEMENT OVERLAY (TYPE MS1/MS2 85mm AVERAGE THICKNESS)
  8. INSTALL NEW MONOLITHIC CONCRETE BARRIER CURB AND SPLASH STRIP (150mm HT, 750mm WIDTH) (SD-223A)
  9. INSTALL NEW MONOLITHIC CONCRETE MODIFIED BARRIER CURB AND SPLASH STRIP (150mm HT, 750mm WIDTH) (SD-223A)
  10. INSTALL NEW CONCRETE BARRIER CURB (150mm HT, DOWELLED)
  11. INSTALL NEW MODIFIED CONCRETE BARRIER CURB (180mm HT, DOWELLED)
  12. INSTALL CONCRETE CURB RAMP (8-12mm HT, MONOLITHIC)
  13. RENEW 100mm CONCRETE SIDEWALK
  14. INSTALL NEW 100mm CONCRETE SIDEWALK
  15. INSTALL NEW MONOLITHIC CONCRETE BULLNOSE AND MEDIAN SLAB
  16. INSTALL DETECTABLE WARNING SURFACE TILE
  17. REMOVE EXISTING CATCH PIT / CATCH BASIN
  18. INSTALL NEW 1800mm CATCH BASIN (SD-024) c/w BARRIER CURB AND GUTTER INLET FRAME AND COVER (AP-011/AP-012) AND CONNECT 250mm Ø PVC SEWER SERVICE TO EXISTING 1050 CONC CS
  19. INSTALL NEW 1800mm CATCH BASIN (SD-024) c/w BARRIER CURB AND GUTTER INLET FRAME AND COVER (AP-011/AP-012) AND CONNECT 250mm Ø PVC SEWER SERVICE TO EXISTING LEAD
  20. ADJUST EXISTING MANHOLE / CATCH BASIN TO GRADE
  21. INSTALL CAST IRON RISER RING
  22. ADJUST EXISTING WATER VALVE TO GRADE
  23. ADJUST EXISTING WATER SERVICE SHUTOFF VALVE

**PRELIMINARY  
NOT FOR CONSTRUCTION**

**ENGINEERS  
GEOLOGISTS  
MANITOBA**  
Certificate of Authorization  
AECOM Canada ULC  
No. 4671

**METRIC**  
WHOLE NUMBERS INDICATE MILLIMETRES  
DECIMALIZED NUMBERS INDICATE METRES

150 mm W.M.	WATERMAIN	150 mm W.M.	HYDRO	HYDRO	PROFILE	LOCATION APPROVED UNDERGROUND STRUCTURES
◇	HYDRANT	◆	M.T.S.	M.T.S.	WB GUTTER	B.M. 84R523 - S.W. Cor. Corydon Ave. & Park Blvd. N., Tblt. on top of 0.05 m dia. x 2.4 m iron pipe 2.6 m N. of S.L. of Corydon Ave. & 6.2 m E. of W.L. of Park Blvd. N. ELEVATION: 233.773
⊙	VALVE	⊙	CONCRETE	CONCRETE	WB MEDIAN GUTTER	HORIZONTAL: Northing: 5525315.364, Easting: 627893.162
⊕	LAND DRAINAGE SEWER	⊕	ASPHALT	ASPHALT	EB GUTTER	
⊖	WASTEWATER SEWER	⊖	PROPERTY LINE	PROPERTY LINE	EB MEDIAN GUTTER	
○	MANHOLE	●	SURVEY BAR	SURVEY BAR		
□	CATCH BASIN	■	ELEVATION	ELEVATION (35.750)		
▽	CATCH PIT	⊙	TREE	TREE		
↑	TRAFFIC SIGNAL POLE	⊙	SIDEWALK RAMP	SIDEWALK RAMP		
↑	STREET LIGHT	⊙	CONCRETE SIDEWALK	CONCRETE SIDEWALK		
⊕	GAS	⊕	FENCE	FENCE		
---	EXISTING	---	LEGEND - PLAN	LEGEND - PLAN	LEGEND - PROFILE	
---	LEGEND - PLAN	---	PROPOSED	PROPOSED	PROPOSED	

**NOTE:**  
LOCATION OF UNDERGROUND STRUCTURES AS SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE, BUT NO GUARANTEE IS GIVEN THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT. CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL SERVICES MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES BEFORE PROCEEDING WITH CONSTRUCTION.

NO.	REVISIONS	DATE	BY
1	ISSUED FOR ADDENDUM 01	04/02/2026	TLF
0	ISSUED FOR TENDER	03/28/2026	TLF

DESIGNED BY	JRC	CHECKED BY	TLF
DRAWN BY	RAM	APPROVED BY	TLF
HOR. SCALE:	1:250	RELEASED FOR CONSTRUCTION BY:	
VERTICAL:	1:10	DATE	04/02/2026

**AECOM**

**THE CITY OF WINNIPEG**  
PUBLIC WORKS DEPARTMENT  
ENGINEERING DIVISION

2026 REGIONAL STREET RENEWAL PROGRAM  
CORYDON AVENUE

ASPHALT PAVEMENT REHABILITATION  
STATION 1+675 TO STATION 1+765 WEST BOUND  
PLAN-PROFILE

CITY DRAWING NUMBER P-3601-16  
SHEET 17 OF 28