



- NOTES:
1. ALL WORK AND MATERIALS TO BE IN ACCORDANCE WITH THE LATEST REVISION OF THE CITY OF WINNIPEG STANDARD CONSTRUCTION SPECIFICATIONS.
 2. CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.
 3. ALL ROADWAY DIMENSIONS SHOWN ARE TO BACK OF CURB.
 4. MODIFIED BARRIER CURB TO BE CONSTRUCTED AT ALL INTERSECTION RADI AND ALLEY RADI.
 5. RENEW CURB AND SIDEWALK AS IDENTIFIED BY CONTRACT ADMINISTRATOR.
 6. CONSTRUCT 200 REINFORCED CONCRETE APPROACHES WITH 75mm GRANULAR BASE COURSE, 300mm - 50mm GRANULAR A SUB-BASE AND SEPARATION/ FILTRATION GEOTEXTILE.
 7. INSTALL 6.0m SUBDRAINS IN EACH DIRECTION AT ALL CATCH BASIN INSTALLATIONS AS PER CW-3120.
 8. CONTRACTORS TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE LIMITS OF CONSTRUCTION FROM DAMAGE FROM CONSTRUCTION ACTIVITIES AS OUTLINED IN THE SPECIFICATIONS.
 9. LAMP STANDARDS, HYDRO POLES, AND ANCHORS THAT REQUIRE TEMPORARY SUPPORT, REMOVAL OR REPLACEMENT, TO BE DONE SO AT THE EXPENSE OF THE CONTRACTOR AS NECESSARY.
 10. ADJUST ALL WATER VALVES, HYDRANTS, MANHOLES, AND CATCH BASINS IN WORK AREA TO GRADE.
 11. SEE STREETSCAPING SHEETS FOR STREETSCAPING PLANS.
 12. SEE WATERMAIN SHEETS FOR WATERMAIN RENEWAL PLANS.
 13. SEE ELECTRICAL SHEETS FOR ROADWAY AND SIDEWALK LIGHTING PLANS.

---	WATER MAIN	---	⊗	VALVE	---	---	EDGE OF SIDEWALK	---
---	LAND DRAINAGE SEWER	---	⊗	CURB STOP	---	---	EDGE OF ASPHALT	---
---	WASTE WATER SEWER	---	⊗	HYDRO POLE & LIGHT STANDARD	---	---	EDGE OF CONCRETE	---
---	HYDRO	---	⊗	LIGHT STANDARD OR TRAFFIC SIGNAL	---	---	MODIFIED BARRIER CURB	---
---	GAS	---	⊗	HYDRO POLE / ANCHOR	---	---	BARRIER CURB	---
---	COMMUNICATIONS	---	⊗	FENCE	---	---	BARRIER CURB AND GUTTER	---
---	SIGNALS	---	⊗	PROPERTY LINE	---	---	PAVING STONE	---
○	MANHOLE	●	⊗	TEST HOLE / PAVEMENT CORE	---	---	CONCRETE SIDEWALK	---
□	CATCH BASIN/CATCH PIT	■	⊗	ELEVATIONS	(231.000)	---	CONCRETE SLAB	---
△	CURB INLET	▽	⊗	CURB RAMP	---	---	ASPHALT	---
◇	UTILITIES ADJUSTED	△ ○	⊗	DETECTABLE WARNING SURFACE TILE	---	---	MILLED SURFACE	---
◇	HYDRANT	◆	⊗			---	PAVEMENT REPAIR FABRIC	---
---	EXISTING	---	---	LEGEND-PLAN	---	---	LEGEND-PLAN	---
---	LEGEND-PLAN	---	---	LEGEND-PLAN	---	---	LEGEND-PLAN	---

LOCATIONS APPROVED UNDERGROUND STRUCTURES	
SIGNED BY: _____	DATE: _____
SUPV. U/G STRUCTURES: _____	DATE: _____
LOCATION OF UNDERGROUND STRUCTURES AS SHOWN ARE BASED ON THE BEST INFORMATION AVAILABLE BUT NO GUARANTEE IS GIVEN THAT ALL EXISTING UTILITIES ARE SHOWN OR THAT THE GIVEN LOCATIONS ARE EXACT CONFIRMATION OF EXISTENCE AND EXACT LOCATION OF ALL SERVICES. MUST BE OBTAINED FROM THE INDIVIDUAL UTILITIES BEFORE PROCEEDING.	

G.B.M. ELEV.	TOH20 @ SE CORNER CARLTON ST AND ST MARY AVE	
232.838		
7		
6		
5		
4		
3		
2		
1		
0	ISSUED FOR TENDER	2026/02/06 S.S.
NO.	REVISIONS	DATE BY

wsp		WSP Canada Inc. 1600 Buffalo Place Winnipeg, MB R3T 6B8 t. 204.477.6650 f. 204.474.2864 www.wsp.com	
DESIGNED BY	M.V.	CHECKED BY	S.S.
DRAWN BY	K.C.W.D.	APPROVED BY	S.S.
HOR. SCALE	1:250	RELEASED FOR CONSTRUCTION	
VERTICAL	1:10		
DATE	APRIL 2025	DATE	

ENGINEER'S SEAL	
CONSULTANT ACAD DWG. NO.	CA0051531.7175-06

THE CITY OF WINNIPEG PUBLIC WORKS DEPARTMENT ENGINEERING SERVICES DIVISION		CITY DRAWING NUMBER P-3596-06
2026 DOWNTOWN STREET RENEWALS		SHEET 06 OF 36
ST MARY AVENUE		TENDER NO. 3-2026
CONCRETE RECONSTRUCTION STA. 0+92.01 TO STA. 2+50		