



METRIC					
WHOLE NUMBERS INDICATE MILLIMETRES DECIMALIZED NUMBERS INDICATE METRES					
⊕	HYDRANT	◆	---	LDS / WWS	---
⊗	VALVE	⊙	---	WATER MAIN	---
⊙	CURB STOP	⊙	---	GAS	---
⊙	MANHOLE	●	---	TRAFFIC SIGNALS	---
□	CATCH BASIN / CATCH PIT	■	---	HYDRO / STREET LIGHT	---
△	CURB INLET	▲	---	COMMUNICATIONS	---
•	POLE	•	---	CURB RENEWAL	---
•	LIGHT STANDARD	•	---	PROPERTY LINE	---
•	TRAFFIC SIGNAL POLE	•	---	RAMP CURB	---
⊕	SURVEY BAR	⊕	---	ELEVATIONS	(33.333)
⊕	GEODETIC BENCH MARK	⊕	---	TREE / TREELINE	---
EXISTING	LEGEND - PLAN	PROPOSED	EXISTING	LEGEND - PLAN	PROPOSED

CONCRETE		LOCATION APPROVED UNDERGROUND STRUCTURES
EXISTING	PROPOSED	
---	---	CONCRETE CONC SIDEWALK / MEDIAN ASPHALT PAVING STONE GRAVEL PLANING / REMOVAL DITCH FLOW TOP OF SLOPE CULVERT SEWER FLOW DIRECTION TEST HOLE / CORE HOLE
---	---	

LOCATION APPROVED UNDERGROUND STRUCTURES		DATE
DESIGNED BY	CHECKED BY	
JGK	GFC	
DRAWN BY	APPROVED BY	
DML	RPB	
HOR SCALE		
1:250		
VERT SCALE		
1:10		
RELEASED FOR CONSTRUCTION		
0 ISSUED FOR TENDER		26/03/11
No. REVISIONS		YY/MM/DD BY
		JGK
		DATE March 11, 2026

500 - 311 Portage Avenue, Winnipeg M8 Canada R3B 2B9
Tel. 204.489.5900 Fax. 204.453.9012 www.stantec.com

DESIGNED BY	JGK	CHECKED BY	GFC
DRAWN BY	DML	APPROVED BY	RPB
HOR SCALE		RELEASED FOR CONSTRUCTION	
1:250			
VERT SCALE			
1:10			
DATE		DATE	
March 11, 2026			

PROFESSIONAL FILE NAME
01009c-le maire.dwg

THE CITY OF WINNIPEG
PUBLIC WORKS DEPARTMENT
ENGINEERING DIVISION

2026 LOCAL STREET RENEWAL PROGRAM
LE MAIRE STREET ALLEY
SOUTH LIMIT TO NORTH LIMIT
REHABILITATION
PAVING AND GRADING
STA 0+500 TO LE MAIRE ST

CITY DRAWING NUMBER	N/A
SHEET	19 OF 41
DRAWING NUMBER	19

- NOTES
- ADJUST MH AND CB RIMS TO NEW GRADES.
 - LAMP STANDARDS, HYDRO POLES, AND ANCHORS THAT REQUIRE TEMPORARY SUPPORT, REMOVAL OR REPLACEMENT, TO BE DONE SO AT THE EXPENSE OF THE CONTRACTOR AS NECESSARY.
 - CONTRACTOR TO REGRADE/RENEW EXISTING PRIVATE SIDEWALKS TO LIMITS AS SHOWN. SIDEWALKS TO BE RENEWED WITH CONCRETE UNLESS NOTED OTHERWISE.
 - CONTRACTOR TO TAKE PRECAUTIONARY STEPS TO PROTECT EXISTING TREES WITHIN THE LIMITS OF CONSTRUCTION FROM DAMAGE FROM CONSTRUCTION ACTIVITIES AS OUTLINED IN THE SPECIFICATIONS.
 - CONTRACTOR TO CONFIRM THE LOCATION OF ALL UTILITIES/SERVICES IN THE FIELD PRIOR TO CONSTRUCTION.
 - MODIFIED BARRIER CURB TO BE USED AT ALL INTERSECTION RADII, BACK LANE RADII AND BULLNOSES.
 - CONTRACTOR TO OVERLAY DRIVEWAYS TO ENSURE POSITIVE DRAINAGE TO NEW STREET GRADES. FINAL LIMITS TO BE DETERMINED IN THE FIELD BY CONTRACT ADMINISTRATOR.
 - CB SD-023 & SD-024 OFFSETS ARE DIMENSIONED TO BOC. CB SD-025 OFFSETS ARE DIMENSIONED O/C.
 - REFER TO TENDER FOR DETAILS REGARDING TRAFFIC MANAGEMENT.
 - MATCH EXISTING GRADES AT DOOR SILLS.
 - ADJUST EXISTING WATER VALVES AND WATER SERVICE CURB STOPS TO GRADE.
 - ADD 200.000 m TO ABBREVIATED ELEVATIONS TO OBTAIN GEODETIC ELEVATIONS.