



**NOTE**

1. EXISTING REINFORCING STEEL SHALL BE REPLACED WITH NEW REINFORCING STEEL AS SHOWN.
2. IF JOINT REPAIR IS GREATER THAN 1000 WIDE ADDITIONAL 12.7mm LONGITUDINAL PLAIN BARS AT 450 O.C. OR USE BAR MAT REF. SD-217.
3. WHERE BAR MAT IS USED, CUT OFF FINGER ENDS SO THE 150 GAP HAS NO FINGER ENDS.
4. ONLY TIE BARS AND DOWELS ARE REQUIRED ON PLAIN DOWELLED PAVEMENTS.
5. INSTALL DOWELS AT PATCH ENDS, REF. SD-213B.

DIMENSIONS ARE IN MILLIMETRES



**THE CITY OF WINNIPEG**  
PUBLIC WORKS DEPARTMENT

Reference Spec. No.  
CW 3230, CW 3310, SD 213B

Revisions

No.	Date	Description	By
2	FEB.04	GENERAL REVISION	J.G.
1	JAN.03	GENERAL REVISION	lwb

LONGITUDINAL JOINT PATCH DETAILS  
ONE SIDE ONLY

Designed By: L.S.W.L.	Drawn By: A.R.	Scale : N.T.S.
Checked By: B.P.	Date: 12.12.15	Drawing No.
Approved: SURFACE WORKS COMMITTEE		SD-214C