



## Designated Floodway Fringe Area Regulation 266/91 Schedule C

### General information

Applicant's name:	Date:
Address:	Application number:
Type of structure:	Flood protection level:

### Required documentation

- Plans of structure     Existing geodetic elevations     Proposed site grading     Status of title

### Floodproofing criteria

7(4) Where a structure **is supported by piles**,

- (a) the design of the foundation shall be certified by a professional engineer  
will comply  (letter from engineer confirming inspections and certification)
- (b) the structure shall be supported in accordance with the requirements illustrated in Schedule C or an equivalent support system
- proposed geodetic elevation of grade at building \_\_\_\_\_
  - required geodetic elevation of grade at building \_\_\_\_\_
- will comply                       waiver requested
- (c) the structure shall be so constructed as not to be buoyant when the surface of any flood waters is higher than the bottom of the horizontal members supporting the structure  
will comply  (letter from engineer confirming compliance of design)
- (d) the elevation of a floor containing finished or occupied space shall be at least 1.0 m above the applicable flood protection level
- proposed geodetic elevation of finished/occupied space \_\_\_\_\_
  - required geodetic elevation of finished/occupied space \_\_\_\_\_
- will comply                       waiver requested

8 In addition to the floodproofing criteria set out in Section 7, every structure, shall meet the following requirements:

- (a) all windows, exterior doors and other exterior openings, including openings between a house and an attached garage, shall be located above the applicable flood protection level  
will comply                       waiver requested

- (b) the electrical service and panelboard shall be located above the main floor unless an existing service and panelboard located below the main floor within a structure existing before August 15, 1981 is being replaced or added to in the same location  
will comply                       waiver requested
- (c) the potable water shut-off valve shall be located on the main floor with no take-off fittings on the service pipe side of the valve and shall have a dual check valve type backflow preventer to provide protection against possible contamination of the potable water supply  
will comply                       waiver requested
- (d) if the structure has floor space below the applicable flood protection level, the drain between the structure and a septic or holding tank or a common sanitary sewer line shall have a backwater valve  
will comply                       waiver requested

This application is intended for floodproofing criteria as required under Section 158 of The City of Winnipeg Charter. The building is subject to all zoning or building by-laws and other regulations as may be applicable.

Applicant's Signature: \_\_\_\_\_

c: February 2003 Floodway Fringe Regulation Schedule C

Your personal information is being collected consistent with the requirements and limitations set out under *The Freedom of Information and Protection of Privacy Act (FIPPA)*. This collection of personal information is authorized by section 36(1)(b) of The FIPPA for permit management and administration. Your information is protected by FIPPA's privacy provisions and will not be used or disclosed for any other purpose, except as authorized by law. Contact the City of Winnipeg's Corporate Access and Privacy Officer by mail (City Clerk's Department, Susan A. Thompson Building, 510 Main Street, Winnipeg MB, R3B 1B9) or by telephone (311) if you have questions about this collection of your personal information.